

ACCESSIBILITY NOTES:

- ACCESSIBLE PATH (A.P.) SHALL CONFORM TO THE FOLLOWING:
 - A COMMON BARRIER FREE ACCESSIBLE ROUTE AT LEAST 48" WIDE WITHOUT ANY ABRUPT VERTICAL CHANGES EXCEEDING 1/2" BEVELED AT 1/2" MAXIMUM SLOPE. EXCEPT THAT LEVEL CHANGES DO NOT EXCEED 1/4" VERTICAL.
 - THE PATH SURFACE IS SLIP RESISTANT, STABLE, FIRM, AND SMOOTH.
 - CROSS-SLOPE DOES NOT EXCEED 2%.
 - SLOPE IN THE DIRECTION OF TRAVEL IS LESS THAN 5% UNLESS OTHERWISE INDICATED AS A RAMP.
 - MINIMUM 10' FC ALONG PATH FROM BUILDING TO PUBLIC WAY.
- WALKS, SIDEWALKS AND PEDESTRIAN WAYS SHALL BE FREE OF GRATINGS WHENEVER POSSIBLE. FOR GRATINGS LOCATED IN THE SURFACE OF ANY OF THESE AREAS, GRID OPENINGS IN GRATINGS SHALL BE LIMITED TO 1/2" MAXIMUM IN THE DIRECTION OF TRAFFIC FLOW IN ALL DIRECTIONS IN PLAZAS AND LARGE OPEN AREAS.
- GATES IN PATH OF TRAVEL MUST COMPLY WITH EXIT DOOR REQUIREMENTS PER CBC SECTION 10B-404.2.4 (1) SPECIFY HARDWARE, KICK PLATES, 5 LBS PRESSURE TO OPERATE, STRIKE SIDE CLEARANCE, AND PANIC HARDWARE.
- SEE SHEET AS-4, AC5-1 & AC5-2 FOR ADDITIONAL ACCESSIBLE REQUIREMENTS.
- PROVIDE ACCESSIBILITY SIGNAGE (ISA) AT THE PRIMARY PUBLIC ENTRANCE AND DIRECTIONAL SIGNAGE AT MAJOR JUNCTIONS CLARIFYING ACCESSIBLE AND NON-ACCESSIBLE ROUTES.
- CONTRACTOR SHALL VERIFY ALL BARRIERS ON THE INDICATED PATH OF TRAVEL HAVE BEEN REMOVE.

DESIGN PROFESSIONAL IN GENERAL RESPONSIBLE CHARGE STATEMENT:

THE PATH OF TRAVEL (P.O.T.) IDENTIFIED IN THESE CONSTRUCTION DOCUMENTS IS COMPLIANT WITH THE CURRENT APPLICABLE CALIFORNIA BUILDING CODE (CBC) ACCESS PROVISIONS FOR PATH OF TRAVEL REQUIREMENTS FOR ALTERATIONS, ADDITION AND STRUCTURAL REPAIRS. AS PART OF THE DESIGN OF THIS PROJECT, THE P.O.T. WAS EXAMINED AND ANY ELEMENTS, COMPONENTS OR PORTIONS OF THE P.O.T. THAT WERE DETERMINED TO BE NONCOMPLIANT 1) HAVE BEEN IDENTIFIED AND 2) THE CORRECTIVE WORK NECESSARY TO BRING THEM INTO COMPLIANCE HAS BEEN INCLUDED WITHIN THE SCOPE OF WORK OF THIS PROJECT'S WORK THROUGH DETAILS, DRAWINGS AND SPECIFICATIONS INCORPORATED INTO THESE CONSTRUCTION DOCUMENTS. ANY NONCOMPLIANT ELEMENTS, COMPONENTS OR PORTIONS OF THE P.O.T. THAT WILL NOT BE CORRECTED BY THIS PROJECT BASED ON VALUATION THRESHOLD LIMITATIONS OR A FINDING OF UNREASONABLE HARSHNESS ARE SO INDICATED IN THESE CONSTRUCTION DOCUMENTS.


DURING CONSTRUCTION IF P.O.T. ITEMS WITHIN THE SCOPE OF THE PROJECT REPRESENTED AS CODE COMPLIANT ARE FOUND TO BE NONCOMPLYING BEYOND REASONABLE CONST. TOLERANCES, THEY SHALL BE BROUGHT INTO COMPLIANCE WITH THE CBC AS A PART OF THIS PROJECT BY MEANS OF A CONSTRUCTION CHANGE DOCUMENT.

EXISTING

- (E) ASPHALT PAVING, MAX 2% EA. WAY
- (E) CONCRETE WALK, MAX 2% EA. WAY
- (E) STRIPED PAVED PLAY AREA
- (E) FIRE HYDRANT
- (E) LANDSCAPING
- (E) CONCRETE CURB
- (E) CHAIN LINK FENCE
- (E) FIRE ACCESS GATE (20'-0" W x 6'-0" H) W/ KNOX BOX
- (E) CHAIN LINK GATE (8'-0" W x 6'-0" H)
- (E) CURB & GUTTER
- (E) W/ FENCE
- (E) PARKING LOT STRIPING (TYP.)
- (E) CONC. DRIVE
- (E) PLAY FIELD
- (E) CHAIN LINK BACKSTOP
- (E) MECHANICAL ENCLOSURE.
- (E) SHADE STRUCTURE (AP. #02-1071036)
- (E) TREE (TYP.)
- (E) SCHOOL FLAG POLE
- (E) SITE LIGHTING
- (E) SIGN
- (E) BACKFLOW PREVENTOR
- (E) STRIPING
- (E) ACCESSIBLE PARKING STALL PER AP* 02-102121
- (E) PLAYGROUND EQUIPMENT
- (E) ACCESSIBLE STAFF R/R (AP* 02-102121)
- (E) ACCESSIBLE BOYS R/R (AP* 02-102121)
- (E) ACCESSIBLE GIRLS R/R (AP* 02-102121)
- (E) CONCRETE PULL BOX
- (E) TRANSFORMER & CONCRETE PAD

PROPOSED

- NEW TOW AWAY SIGN, SEE DETAIL 9/AC5-2.
- NEW SAFE DISPERSAL AREA SIGN, SEE DETAIL 11/AC5-2



Modesto Fire Department
FIRE PREVENTION DIVISION
409 12th Street
Modesto, California 95354
Tel: (209) 571-5553 Fax: (209) 544-1652

WATERFLOW REPORT
Water Flow Requested By: Joshua Gregoire
Address: 2237 Science Dr.
City: Modesto, CA
Phone: 209-523-8323
FAX: 209-523-8323
E-Mail Results To: jgregoire@skwassociates.com
Project Name: Freedom Elementary School
Project Location: 2101 Fine Ave.
Water Tap Location: FH #J919 on Sharon Ave.
Location of Flow Hydrant: FH #J918 on Sharon Ave.
Main Size: 6"
Tested By: B. Mendenhall J. Ernst
Date Tested: 12/6/2023
Results Are Valid For This Project Only:
Occ. Number: 6142 Building Permit Number: FIR2023-00188

WATERFLOW RESULTS

2.5" pilot reading: static: 58 residual: 60	0 gpm Tested with 2.5" Hose Monster waterflow @ 20 psi
4.5" pilot reading: static: 58 residual: 60	1,623 gpm Tested with 4.5" Hose Monster 3,782 gpm waterflow @ 20 psi

DSA 810

FIRE & LIFE SAFETY SITE CONDITIONS SUBMITTAL

Division of the State Architect (DSA) documents referenced within this publication are available on the DSA Forms or DSA Publications webpage.
To facilitate the Division of the State Architect's (DSA) fire and life safety plan review of project site conditions, DSA requires the design professional to provide the following information at time of project submittal for projects consisting of construction of a new campus, construction of new buildings, additions to existing buildings, and for site alternate design means for fire department emergency vehicle access, and fire suppression water supply. Information associated with compliance items 1 through 3 below is to be provided for all project types indicated above. Information associated with items 4 through 7 is to be completed when an alternate means is utilized. Acknowledgement by the school district and signature from the Local Fire Authority (LFA) is only required when an alternate design means is being requested.

The Project Information and Fire & Life Safety Information sections are to be completed for all projects and imaged onto the fire access site plan. When an alternate design/means is proposed, all sections on pages 1 and 2 are to be completed and imaged on the fire access site plan.
For additional information refer to the instructions at the end of this form and DSA Policy PL 09-01: Fire Flow for Buildings.

PROJECT INFORMATION	
School District/Owner:	SYLVAN UNION SCHOOL DISTRICT
Project Name/School:	FREEDOM ELEMENTARY SCHOOL (2) PORTABLE CLASSROOMS
Project Address:	2101 FINE AVE, MODESTO CA 95355

FIRE & LIFE SAFETY INFORMATION	
1. Has a fire hydrant flow test been performed within the past 12 months? (If yes, provide a copy of the test data.)	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
2. Was the fire hydrant water flow test performed as part of this LFA review?	Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>
3. Is the project located within a designated fire hazard severity zone (FHSZ) as established by Cal-Fire? (If yes, indicate FHSZ classification below.)	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
Refer to the following website for FHSZ locations: http://cal.fire.ca.gov/FHSZ/	Moderate <input type="checkbox"/> High <input type="checkbox"/> Very High <input type="checkbox"/>
Wildland Interface Area (WFA) (If any designations are checked, project design must meet the requirements of CBC Chapter 7A.)	WFA <input type="checkbox"/>

DSG DSA 810 (revised 12/9/20) DIVISION OF THE STATE ARCHITECT DEPARTMENT OF GENERAL SERVICES STATE OF CALIFORNIA Page 1 of 4

DSA 810 FIRE & LIFE SAFETY SITE CONDITIONS SUBMITTAL

CONDITION MEANS AND METHODS RESOLUTION	ALTERNATE ACCEPTED			
	Yes	No	N/A	ADR
4. Emergency vehicle access roadways do not meet CFC requirements.				
4a. Acceptable Alternate: Emergency vehicle and personnel access as proposed by the project architect is acceptable for providing fire suppression and protection of life and property.				<input checked="" type="checkbox"/>
5. Fire Hydrants: Number and spacing does not meet CFC requirements.				<input checked="" type="checkbox"/>
5a. Acceptable Alternate: Number of fire hydrants and spacing as proposed by the project architect is acceptable for fire suppression and protection of life and property.				<input checked="" type="checkbox"/>
6. Fire Hydrants: Water flow and pressure are less than CFC minimum.				<input checked="" type="checkbox"/>
6a. Acceptable Alternate: The available flow and pressure is acceptable for providing fire suppression and protection of life and property.				<input checked="" type="checkbox"/>
7. Location of fire department connection(s) serving the sprinkler systems or standpipe systems does not meet CFC requirements.				<input checked="" type="checkbox"/>
7a. Acceptable Alternate: The location of fire department connection serving the fire sprinkler system and/or standpipe system is acceptable for providing fire suppression and protection of life and property.				<input checked="" type="checkbox"/>

School District Acceptance of Acceptable Design Alternates
By signing this form, the school district acknowledges and accepts the proposed design as an alternative to California Building Code (CBC) and California Fire Code (CFC) minimum requirements as indicated by one or more of the conditions indicated at items 4a, 5a, 6a or 7a, for providing fire and life safety protection of life and property.

Accepted by: _____ Title: _____
Signature: _____ Date: _____

LOCAL FIRE AUTHORITY (LFA) INFORMATION
LFA Agency Name: Modesto Fire Department
LFA Review Official: David Bickle
Title: Fire Chief
Work Email: FirePrevention@modestofire.com
Work Phone: (209) 572-9590

LFA Reviewer's Signature: _____ Date: 2/1/24

DSG DSA 810 (revised 12/9/20) DIVISION OF THE STATE ARCHITECT DEPARTMENT OF GENERAL SERVICES STATE OF CALIFORNIA Page 2 of 4

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR:
SS FLS ACS
DATE: 2/27/2024

skw & associates
architecture • engineering • surveying
2237 Science Drive, Modesto, CA 95355 P: 209-523-8323 F: 209-758-2852

David J. Starck
architect
c.22008

Allan V. Stevenson
civil engineer
roc 61758



PROJECT TITLE:
SYLVAN UNION SCHOOL DISTRICT
FREEDOM ELEMENTARY SCHOOL
(2) PORTABLE CLASSROOMS

2101 Fine Ave
Modesto, CA 95355

SITE PLAN


REVISIONS:

BY: GZ
LIST: FREEDOM
DATE: 2-20-2024
JOB: 23M045
SHEET: AS-1




EXISTING

- ① (E) ASPHALT PAVING, MAX 2% EA. WAY
- ② (E) CONCRETE WALK, MAX 2% EA. WAY
- ③ (E) STRIPED PAVED PLAY AREA
- ④ (E) FIRE HYDRANT
- ⑤ (E) LANDSCAPING
- ⑥ (E) CONCRETE CURB
- ⑦ (E) PARKING LOT STRIPPING (TYP.)
- ⑧ (E) CONCRETE PULL BOX (TYP.)
- ⑨ (E) BASKETBALL HOOP
- ⑩ (E) WHEEL STOP (TYP.)
- ⑪ (E) ACCESSIBLE PARKING STALL SIGN PER AP# 02-102121.
- ⑫ (E) ACCESSIBLE VAN PARKING STALL SIGN 02-102121
- ⑬ (E) ACCESSIBLE PARKING STALL.
- ⑭ (E) CONCRETE CURB PAINTED BLUE (TYP.)



SCALE: 1" = 10'-0"



SCALE: 1/8" = 1'-0"

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

skw & associates
architecture • engineering • surveying
2257 scenic drive, mckleto, ca 95555 p. 209-758-2552

• david | stark
architect
c 22908

• allan v. stevenson
civil engineer
roc 61758




PROJECT TITLE:
SYLVAN UNION SCHOOL DISTRICT
FREEDOM ELEMENTARY SCHOOL
(2) PORTABLE CLASSROOMS
2101 Fine Ave
Mckleto, CA 95555

ENLARGED PARTIAL
SITE PLAN

REVISIONS:


BY : GZ
LIST : FREEDOM
DATE : 2-20-2024
JOB : 23M048

SHEET : AS-2



10 ASSISTIVE LISTENING DEVICES



NTS



12 FLOOR PLAN


SCALE: 1/4" = 1'-0"

9 EXTERIOR ELEVATIONS



FRONT ELEVATION

REAR ELEVATION



LEFT SIDE ELEVATION

VERIFY:

- SUB PANEL LOCATIONS. SEE DRAWINGS BY AMS MODULAR INC.
- MAIN POWER POINT OF CONNECTION (P.O.C.) - SEE ELECTRICAL DRAWINGS.
- SEE MODULAR BUILDING PLANS FOR ALL ADDITIONAL INFORMATION.

NOTE:

SEE SHEET ACS-1 FOR ACCESSIBLE FIXTURES MOUNTING DIMENSIONS.

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC.
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

skw & associates
architecture • engineering • surveying
2257 scenic drive, Modesto, CA 95355 P: 209-528-8525 F: 209-758-2852

• david j stark
architect
c 22908

• allan v. stevenson
civil engineer
no 6758



PROJECT TITLE:
SYLVAN UNION SCHOOL DISTRICT
FREEDOM ELEMENTARY SCHOOL
(2) PORTABLE CLASSROOMS
2101 Fine Ave
Modesto, CA 95355

FLOOR PLAN AND
EXTERIOR ELEVATIONS

REVISIONS:

BY : GZ
LIST : FREEDOM
DATE : 2-20-2024
JOB : 23M048

SHEET : A-1

SCALE: 1/4" = 1'-0"

NOTE: THE CONTRACTOR SHALL CHECK ALL DIMENSIONS AT THE JOB AND SHALL BE RESPONSIBLE FOR ALL DISCREPANCIES BETWEEN DIMENSIONS OF THE ACTUAL WORK AND THOSE SHOWN IN THE DOCUMENTS OR AS INDICATED ON THESE PLANS. THE CONTRACTOR SHALL NOTIFY THE ARCHITECT IMMEDIATELY UPON DISCOVERY OF ANY DISCREPANCY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS PRIOR TO COMMENCING WORK.

9 NOT USED


12 NOT USED

KEY NOTES:

- 01 (E) LAVATORY PER AP* 02-102121
- 02 (E) 36" GRAB BAR PER AP* 02-102121
- 03 (E) 42" GRAB BAR PER AP* 02-102121
- 04 (E) ACC. OR REG. WATER CLOSET PER AP* 02-102121
- 05 (E) ACC. OR REGULAR URINAL PER AP* 02-102121
- 06 (E) TOILET PARTITION (SOLID PLASTIC) PER AP* 02-102121
- 07 (E) SOAP DISPENSER PER AP* 02-102121
- 08 (E) SURFACE MOUNTED TOILET PAPER DISPENSER PER AP* 02-102121
- 09 (E) TOILET SEAT COVER DISPENSER PER AP* 02-102121
- 10 (E) 2'-0" W x 2'-6" H MIRROR +40" AFF. MAX. (BOTT.) PER AP* 02-102121
- 11 (E) SURFACE MOUNTED HAND DRYER PER AP* 02-102121
- 12 (E) URINAL PARTITION (SOLID PLASTIC) WALL 4 TOP RAIL SUPPORTED AT FRONT


DOOR LEGEND:

- (E) INDICATES AN EXISTING 3070 METAL DOOR AND FRAME TO REMAIN.



4 EXISTING ENLARGED RESTROOM PLANS

SCALE: 1/4" = 1'-0"



6 EXISTING ENLARGED RESTROOM PLANS

SCALE: 1/4" = 1'-0"

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

skw & associates
architecture • engineering • surveying
2257 scenic drive, mcklesto, ca 95555 p: 209-758-2852

• david j stark
architect
c 22908

• allan v. stevenson
civil engineer
noe 61758

LICENSED ARCHITECT
DAVID J. STARK
KEN. 22908
STATE OF CALIFORNIA
12.6.23

PROJECT TITLE:
SYLVAN UNION SCHOOL DISTRICT
FREEDOM ELEMENTARY SCHOOL
(2) PORTABLE CLASSROOMS
2101 Fine Ave
Mcklesto, CA 95555

ENLARGED RESTROOM
PLANS


REVISIONS:

BY : GZ
LIST : FREEDOM
DATE : 2-20-2024
JOB : 23M048

SHEET : A-2

DESCRIPTION	PROPOSED	EXISTING
SANITARY SEWER	6"SS	6"SS
STORM SEWER	12"SD	12"SD
GAS LINE	2"GV	2"GV
WATER LINE	8"W	8"W
UNDERGROUND ELECTRICAL	UG-E	UG-E
OVERHEAD UTILITIES	O/H	O/H
ELECTRICAL CONDUIT	E	E
IRRIGATION LINE	12"IR	12"IR
GAS VALVE	GV	GV
WATER VALVE	WV	WV
GRADES/ELEVATIONS	147.00 FG	x147.00
PAD ELEVATION	148.4	
SLOPE/FLOW DIRECTION	SLOPE	SLOPE
CONTOUR LINE		1.48
CENTERLINE		
MANHOLE	●	○
CATCH BASIN	■	□
GAS METER	□	□
WATER METER	□	□
CURB AND GUTTER	▬	▬
SIDEWALK	▬	▬
DRIVEWAY	▬	▬
FIRE HYDRANT	●	●
SIGN	●	●
SANITARY SEWER CLEAN OUT	⊗	⊗
UTILITY POLE	●	●
FENCE	▬	▬
WHEELCHAIR RAMP	▬	▬
ELECTROLIER	●	●

SYMBOLS LEGEND



DEMOLITION PLAN

LEGEND:

KEY NOTES:


- EX. BUILDING TO REMAIN
- EX. CONC. SIDEWALK/FLATWORK TO REMAIN
- EX. SHADE STRUCTURE TO REMAIN
- EX. FENCE TO REMAIN
- EX. UTILITY BOX TO REMAIN
- EX. CATCH-BASIN TO REMAIN
- EX. AC PAVEMENT TO REMAIN

DEMO NOTES:

- SAWCUT/DEMO REMOVE EX. AC PAVEMENT -CONTRACTOR TO VERIFY LOCATION
- REMOVE EX. STORAGE CONTAINER OFF SITE -BY DISTRICT

SCALE: 1" = 50'

SHEET INDEX



VICINITY MAP

SHEET NO.	SHEET TITLE
C1.0	DEMOLITION PLANS
C2.0	GRADING PLAN
C2.1	ENLARGED GRADING PLAN
C3.0	TYPICAL DETAILS

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

skw associates
architecture • engineering • surveying
2227 scenic drive, modesto, ca 95355 p. 209.759.2552


• david j. starrck
architect
c.22008

• allan v. stevenson
civil engineer
rec.61759

LICENSED ARCHITECT
DAVID J. STARRCK
C-22008
JAN 12 2011
STATE OF CALIFORNIA

ABBREV.	DESCRIPTION	ABBREV.	DESCRIPTION
AB	AGGREGATE BASE	LF	LINEAR FEET
AC	ASPHALT CEMENT	LP	LOW POINT
BC	BEGIN CURVE	MATCH	MATCH EXISTING CONDITIONS
BFP	BACKFLOW PREVENTION ASSEMBLY	MAX	MAXIMUM
BOW, BSW, BW	BACK OF SIDEWALK	MH	MANHOLE
BLDG	BUILDING	MIN	MINIMUM
C	CONCRETE	N	NORTH, NEW
CAP	CONCRETE ANGLE POINT	NTS	NOT TO SCALE
CE	CONCRETE EDGE	O/H	OVER-HEAD UTILITIES
CB	CATCH BASIN	P	PAVEMENT
C&G	CURB AND GUTTER	PL	PROPERTY LINE
CIP	CAST IRON PIPE, CAST IN PLACE	PT	POINT, POINT OF TANGENT
CL	CENTERLINE	PNT	POINT
CLF	CHAINLINK FENCE	PVC	POLYVINYL CHLORIDE
CO	CLEAN OUT	RCP	REINFORCED CONCRETE PIPE
CONC	CONCRETE	R	RADIUS, RADIAL BEARING
DEMO	DEMOLISH	REQD	REQUIRED
DET	DETAIL	S	SOUTH, SLOPE
DI	DROP INLET	SD	STORM DRAIN
DIA	DIAMETER	SDMH	STORM DRAIN MANHOLE
DIP	DUCTILE IRON PIPE	SS	SANITARY SEWER
E	EAST, EXISTING	SSMH	SANITARY SEWER MANHOLE
EC	END CURVE	STD	STANDARD
ELEC	ELECTRICAL	SW	SOUTHWEST, SIDEWALK
ELEV	ELEVATION	TBC	TOP BACK OF CURB
EP	EDGE OF PAVEMENT	TC	TOP OF CURB
EX	EXISTING	TEMP	TEMPORARY
FE	FENCE	TFOC	TOP FACE OF CURB
FF	FINISH FLOOR	THRU	THROUGH
FH	FIRE HYDRANT	VERT	VERTICAL
FL	FLOWLINE	W	WEST, WATER
FLW	FACE OF WALK, FRONT OF WALK	WV	WATER VALVE
GB	GRADE BREAK		
CS	GROUND SHOT		
GV	GAS VALVE, GATE VALVE		
INV	INVERT		
IRR	IRRIGATION		

LIST OF ABBREVIATIONS



ENLARGED DEMOLITION PLAN

811
Know what's below.
Call before you dig.

SCALE: 1" = 20'

APPROVAL BLOCK

PROJECT TITLE:
SYLVAN UNION SCHOOL DISTRICT
FREEDOM ELEMENTARY SCHOOL
(2) PORTABLE CLASSROOMS
2101 Fine Ave
Modesto, CA 95355

DEMOLITION PLAN

REVISIONS:

BY	DATE	DESCRIPTION
A.S. R.H.	02-07-2024	FREEDOM
	28MO45	

SHEET: C1.0

NOTE: THE CONTRACTOR SHALL CHECK ALL DIMENSIONS AT THE JOB AND SHALL BE RESPONSIBLE FOR ALL DISCREPANCIES BETWEEN DIMENSIONS OF THE ACTUAL WORK AND THOSE SHOWN ON THE DOCUMENTS. THE CONTRACTOR SHALL ALSO BE RESPONSIBLE FOR ALL QUANTITIES OF MATERIALS TO BE ORDERED TO COMPLETE THE WORK.

C O N C R E T E N O T E S :


- STRUCTURAL CONCRETE SHALL TEST NOT LESS THAN 3000 PSI IN 28 DAYS.
- CEMENT SHALL CONFORM TO A.S.T.M. C-150 TYPE 1.
- CONCRETE AGGREGATES SHALL CONFORM TO A.S.T.M. C-33.
- REINFORCING SHALL CONFORM TO A.S.T.M. A-615 GRADE 40, TYP. #6 OR GREATER, GRADE 60.
- REINFORCING STEEL SHALL BE FABRICATED ACCORDING TO "MANUAL OF STANDARD PRACTICE FOR REINFORCED CONCRETE CONSTRUCTION."
- WIRE FABRIC SHALL NOT BE USED.
- DIMENSIONS SHOWN FOR LOCATION OF REINFORCING ARE TO THE FACE OF MAIN BARS AND DENOTE CLEAR COVERAGE. CONCRETE COVERAGE SHALL BE AS FOLLOWS:

CONCRETE DEPOSITED DIRECTLY AGAINST GROUND (EXCEPT SLAB)	3"
CONCRETE EXPOSED TO GROUND BUT PLACED IN FORMS	2"
TIED COLUMNS (MAIN BARS)	2"
BEAMS (TOP BARS)	1.5"
BEAMS (ALL OTHER MAIN REINFORCING)	2"
PAN JOISTS	1"
SPIRAL COLUMNS (TO FACE OF SPIRAL REINFORCING)	1.5"
WALLS (EXTERIOR FACE)	2"
WALLS (INTERIOR FACE)	0.75"
SLABS (ON FORMS)	0.75"
SLABS (ON GROUND)	POSITION IN CENTER OF SLAB
- SPLICES IN CONTINUOUS REINFORCEMENTS SHALL BE 32 BAR DIAMETERS AND SPLICES IN ADJACENT BARS SHALL BE NOT LESS THAN 5'-0" APART. SPLICE CONTINUOUS BARS IN SPANDRELS, GRADE BEAMS, WALL BEAMS, ETC. AS FOLLOWS: TOP BARS AT CENTER SPAN - BOTTOM BARS AT CENTER SUPPORT.
- CONSTRUCTION JOINTS SHALL BE MADE ROUGH AFTER ALL LAITANCE HAS BEEN REMOVED FROM THE SURFACE. CONCRETE MAY BE ROUGHENED BY CHIPPING THE ENTIRE SURFACE, SAND BLASTING, OR HAVING THE SURFACE 4 TO 6 HOURS AFTER THE POUR WITH A FINE SPRAY. REMOVE ALL DEBRIS FROM THE FORMS BEFORE POURING ANY CONCRETE. DRILL THROUGH STEEL COLUMNS AND BEAMS TO PASS HORIZONTAL REINFORCING.
- REINFORCING, DOWELS, BOLTS, ANCHORS, SLEEVES, ETC. TO BE EMBEDDED IN CONCRETE SHALL BE SECURELY POSITIONED BEFORE PLACING CONCRETE.
- MAXIMUM FREE FALL OF CONCRETE SHALL BE 6'-0".
- WALLS SHALL BE POURED IN HORIZONTAL LAYERS OF 2'-0" MAX. DEPTH.
- CONCRETE IN WALLS, PIERS OR COLUMNS SHALL BE SET AT LEAST 2 HOURS BEFORE PLACING CONCRETE IN BEAMS, SPANDRELS, OR SLABS SUPPORTED THEREON.
- HORIZONTAL WALL BARS IN DOUBLE LAYER WALLS SHALL BE STAGGERED.
- DOWEL ALL VERT. REBARS IN WALLS AND COLUMNS FROM FOUNDATION WITH SAME SIZE BAR.
- MINIMUM WALL REINFORCING SHALL BE:

WALL THICKNESS	SINGLE LAYER	DOUBLE LAYER
7" OR LESS	#4 AT 12" OC EA. WAY	
8"	#4 AT 18" OC EA. WAY	#4 AT 10" OC EA. WAY

T R E N C H I N G A N D R E S U R F A C I N G :

- ALL TRENCHES SHALL BE SHORED OR PROTECTED IN ACCORDANCE WITH OSHA AND OTHER STATE AND FEDERAL SAFETY CODES, REGULATIONS AND ORDINANCES.
- UNSTABLE MATERIAL SHALL BE EXCAVATED AND STABILIZED WITH #3 ROCK (PER ASTM 33 OR APPROVED EQUAL) OR WITH CEMENT SLURRY/CONCRETE AS APPROVED BY THE PROJECT ENGINEER.
 - FOR EXISTING PAVED AREAS, BACKFILL MATERIAL SHALL BE AGGREGATE BASE (95% RELATIVE COMPACTION 2'-0" BELOW THE PAVEMENT SURFACE) AND NATIVE BACKFILL (90% RELATIVE COMPACTION FOR THE REMAINING DEPTH TO THE PIPE BEDDING).
 - PLACEMENT OF AGGREGATE BASE SHALL BE IN 12" LIFTS EVENLY PLACED AND MECHANICALLY COMPACTED TO RELATIVE DENSITY AS SPECIFIED. COMPACTION TESTS SHALL BE REQUIRED AT THE DISCRETION OF THE PROJECT ENGINEER. ALL COSTS RELATED TO THESE TESTS SHALL BE BORNE BY THE OWNER/CONTRACTOR/UTILITY COMPANY WHEN SUCH TESTS ARE REQUIRED. IF RESULTS OF THESE TESTS DO NOT MEET SPECIFIED REQUIREMENTS, BACKFILL SHALL BE EXCAVATED, REPLACED, COMPACTED AND RETESTED. IN CASE OF ONE SACK SLURRY MIX OR CONTROLLED DENSITY FILL, NO COMPACTION TEST WILL BE REQUIRED.
- DROP HAMMER SHALL NOT BE USED TO CUT PAVEMENT.
- ALL TRENCHES SHALL BE BACKFILLED AND TEMPORARILY PAVED AT THE END OF EACH WORKING DAY. THE USE OF STEEL PLATES MUST BE APPROVED BY THE PROJECT ENGINEER AT LEAST 48 HOURS IN ADVANCE.
- INITIAL CUT IN STREET PAVEMENT SHALL BE EQUAL TO THE WIDTH OF THE TRENCH WITH THE OPTION OF BEING JACK HAMMERED OR SAW CUT.
- FINAL CUT IN STREET PAVEMENT SHALL BE 12" WIDER THAN THE TRENCH WIDTH AND SHALL BE MADE BY SAW CUTTING ONLY.
- TEMPORARY BITUMINOUS SURFACING (CUT BACK) SHALL BE PLACED AND COMPACTED IMMEDIATELY ABOVE THE TRENCH FOLLOWING COMPACTION. MINIMUM DEPTH OF CUT BACK SHALL BE 2" OR AS SPECIFIED BY THE PROJECT. CUT BACK SHALL BE MAINTAINED IN GOOD CONDITION UP TO THE TIME THE FINAL PAVING IS PLACED ON TRENCH IN ACCORDANCE WITH NOTE #8.
- FINAL PAVING ABOVE THE TRENCH SECTION SHALL BE PLACED WITHIN 14 DAYS OF ITS BACKFILL AND COMPACTION. EXTENSION MAY BE GRANTED BY THE OWNER DUE TO WEATHER CONDITIONS.
- TEMPORARY CUT BACK SHALL BE REMOVED BEFORE PLACEMENT OF FINAL PAVING. FINAL PAVING SHALL BE PLACED ON UNDISTURBED PREVIOUSLY INSPECTED AND COMPACTED AGGREGATE BASE OR ONE SACK SLURRY MIX/ CONTROLLED DENSITY FILL. RECOMPACTION AND INSPECTION SHALL BE REQUIRED FOR ANY DISTURBED BASE OR SURFACE PRIOR TO PLACEMENT OF FINAL PAVING.
- PROPER TRAFFIC CONTROLS AND COVERING OF TRENCHES SHALL BE MAINTAINED IN ACCORDANCE WITH THE CALTRANS STANDARD SPECIFICATIONS.
- ASPHALT CONCRETE SHALL BE IN ACCORDANCE WITH THE CALTRANS SPECIFICATIONS.
- ALL TRENCHES SHALL HAVE A COMPACTION TEST TO ENSURE PROPER COMPACTION, AS SPECIFIED BY THE GEOTECHNICAL ENGINEER.



KEY NOTES:

- EX. BUILDING TO REMAIN
- EX. CONC. SIDEWALK/FLATWORK TO REMAIN
- EX. SHADE STRUCTURE TO REMAIN
- EX. FENCE TO REMAIN
- EX. UTILITY BOX TO REMAIN
- EX. CATCH-BASIN TO REMAIN
- EX. AC PAVEMENT TO REMAIN

NOTE: THE CONTRACTOR SHALL CHECK ALL DIMENSIONS AT THE JOB AND SHALL BE RESPONSIBLE FOR ALL DISCREPANCIES BETWEEN DIMENSIONS OF THE ACTUAL WORK AND THOSE SHOWN ON THE DRAWINGS. THE CONTRACTOR SHALL ALSO BE RESPONSIBLE FOR ALL DIMENSIONS OF MATERIALS AND DIMENSIONS OF THE WORK. THE CONTRACTOR SHALL ALSO BE RESPONSIBLE FOR ALL DIMENSIONS OF MATERIALS AND DIMENSIONS OF THE WORK.

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

skw associates
 architecture • engineering • surveying
 2237 scenic drive, Modesto, ca 95355 p. 209.525.6833 f. 209.759.2552

• david j. stark
 architect
 c. 22008
 • allan v. stevenson
 civil engineer
 no. 61759




PROJECT TITLE:
 SYLVAN UNION SCHOOL DISTRICT
 FREEDOM ELEMENTARY SCHOOL
 (2) PORTABLE CLASSROOMS
 2101 Fine Ave
 Modesto, CA 95355

GRADING PLAN

REVISIONS:



BY: A.S. R.H.
 LIST: FREEDOM
 DATE: 02-07-2024
 JOB: 28M045

SHEET: C2.0







- EXTERIOR FLATWORK:**
- 1) CONCRETE FLATWORK SHALL BE 4" CONCRETE O/V COMPACTED NATIVE, WITH #3 BARS AT 18". CENTERED IN THE SLAB
 PARKING AREA: 6" CONCRETE O/V 4" A.B. O/V COMPACTED NATIVE, WITH #3 BARS AT 18". CENTERED IN THE SLAB
 - 2) INSTALL CONTINUOUS 1/2" FELT, EXPANSION JOINT WHERE NEW FLATWORK ABUTS EXISTING FLATWORK.
 - 3) **CRACK CONTROL JOINTS:**
 FLATWORK: EVERY 6-FT, WITH A MAXIMUM CONTROLLED AREA OF 30 SQ-FT.
 CONCRETE PAVEMENT: EVERY 14-FT, WITH A MAXIMUM CONTROLLED AREA OF 200 SQ-FT.



NOTE: THE CONTRACTOR SHALL CHECK ALL DIMENSIONS AT THE JOB AND SHALL BE RESPONSIBLE FOR ALL DISCREPANCIES BETWEEN DIMENSIONS OF THE ACTUAL WORK AND THOSE SHOWN IN THE DOCUMENTS. ON ARCHITECT'S APPROVED SHOP DRAWINGS, THE CONTRACTOR SHALL ALSO BE SOLELY RESPONSIBLE FOR ALL QUANTITIES OF MATERIAL OR EQUIPMENT CALLED FOR TO PROPERLY COMPLETE THE WORK.


NOTE: THE CONTRACTOR SHALL CHECK ALL DIMENSIONS AT THE JOB AND SHALL BE RESPONSIBLE FOR ALL DISCREPANCIES BETWEEN DIMENSIONS OF THE ACTUAL WORK AND THOSE SHOWN IN THE DOCUMENTS OR INDICATED BY DIMENSION LINES. THE CONTRACTOR SHALL ALSO BE RESPONSIBLE FOR ALL DIMENSIONS OF MATERIAL OR EQUIPMENT CALLED FOR TO PROPERLY COMPLETE THE WORK.

17	13	9	5	PAVEMENT OVERLAY	1"=1'				
18	14	10	6	PAVEMENT LAP JOINT	N.T.S.	2	TYP. FLAT WORK DET.	1"=1'	
19	15	11	7			3			
20	16	12	8			4			




NOTES:
 1. COLD JOINTS SHALL BE PLACED EVERY 20' (MAX.)
 2. CRACK CONTROL JOINTS SHALL BE PLACED EVERY 5' AT SIDEWALKS.


TYPICAL CONCRETE SLAB



TYPICAL COLD JOINT (CJ)



TYPICAL CRACK CONTROL JOINT (CCJ)



NOTES:
 1) SEE PLAN FOR PAVEMENT SECTIONS.
 2) SOIL COMPACTION SHALL CONFORM TO THE RECOMMENDATIONS SET FORTH IN THE GEOTECHNICAL REPORT.

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

skw & associates
 architecture • engineering • surveying
 2257 scenic drive, Modesto, CA 95355 p: 209-523-8525 f: 209-758-2852

• david j. starck
 architect
 c22908
 • allan v. stevenson
 civil engineer
 noe 61758

PROJECT TITLE:
 SYLVAN UNION SCHOOL DISTRICT
 FREEDOM ELEMENTARY SCHOOL
 (2) PORTABLE CLASSROOMS
 2101 Fine Ave
 Modesto, CA 95355

SECTIONS & DETAILS

REVISIONS:

BY : A.S. R.H.
 LIST : FREEDOM
 DATE : 02-07-2024
 JOB : 25M048

SHEET : **C3.0**

02/16/24 12:00:10 PM F:\A\060 SUSD PORTABLES AT VARIOUS\ENGR\SHEETS\060_E0.2 FIRE ALARM DETAILS.DWG cmeandez


FIRE ALARM INSTALLATION NOTES

- THE FIRE ALARM SYSTEM SHALL CONFORM TO ARTICLE 760 OF THE CALIFORNIA ELECTRICAL CODE.
- UPON COMPLETION OF THE INSTALLATION OF THE FIRE ALARM SYSTEM, A SATISFACTORY TEST OF THE ENTIRE SYSTEM SHALL BE PERFORMED IN THE PRESENCE OF THE DSA INSPECTOR OF RECORD & LOCAL FIRE AUTHORITY.
- ALL DRAWINGS ARE DIAGRAMMATICAL.
- ON FACTORY PROVIDED BACK BOXES, NO ENLARGEMENTS TO THE STANDARD KNOCKOUTS SHALL BE MADE. NOR MAY THE INSTALLER ATTACH CONDUIT TO A NON-FACTORY PROVIDED KNOCKOUT WITHOUT THE EXPRESS WRITTEN CONSENT OF THE MANUFACTURER.
- ALL FIRE ALARM DATA COMMUNICATIONS, AND INITIATING CIRCUITS SHALL BE INSTALLED UTILIZING SOLID COPPER CONDUCTORS OF A SIZE AS PER SPECIFICATIONS OR THE LOCAL ENFORCING AGENCY, WHICHEVER IS MORE STRINGENT SHALL APPLY.
- ALL FIRE ALARM CIRCUITS ARE CONTINUOUS FROM DEVICE TO DEVICE, SPLICES ARE NOT ALLOWED UNLESS IN COVERED JUNCTION BOXES ON APPROVED TERMINAL BLOCKS.
- COLOR CODING SHALL BE AS FOLLOWS:
 - A. INITIATING CIRCUITS (CONVENTIONAL SYSTEMS ONLY) I.E. MANUAL PULL STATIONS, DETECTOR. {+ORANGE
-WHITE
 - B. WATER FLOW SWITCHES, ETC. INDICATING CIRCUITS I.E. BELLS, HORNS, STROBE UNITS, ETC. {+RED
-BLACK
 - C. POWER FOR AUXILIARY DEVICES I.E. DOOR HOLDERS, 4-WIRE SMOKE DETECTORS POWER, REMOTE RELAYS, DAMPERS, EXHAUST FANS, ETC. {+BLUE
-BLACK
 - D. ANNUNCIATION DEVICES I.E. REMOTE LAMPS, ANNUNCIATORS, ETC. {+PURPLE
-BLACK
- CABLING REQUIREMENTS:
 - A. ALL CONDUCTORS SHALL BE TYPE THWN #14 -AMERICAN WIRE GAUGE. THWN INSULATION TYPE (MOISTURE & HEAT RESISTANT THERMOPLASTIC) SUITABLE FOR DRY & WET LOCATIONS
 - B. ALL CONDUCTORS SHALL BE SOLID COPPER; STRANDED CONDUCTORS ARE PROHIBITED.
 - C. ALL CONDUCTORS SHALL BE BRADY OR EQUALLY LABELED.
 - D. ALL CONDUCTORS SHALL BE INSTALLED IN CONDUIT -NO OPEN WIRING.
- IT IS THE RESPONSIBILITY OF THE INSTALLING CONTRACTOR TO MAINTAIN AND UPDATE HIS CONSTRUCTION DRAWINGS WITH A HIGH DEGREE OF ACCURACY. MANUFACTURER/CONTRACTOR WILL PROVIDE RECORD DRAWINGS FOR THE PROJECT BASED ON THE INFORMATION CONTAINED THEREIN.
- FIRE ALARM CONTRACTOR TO VERIFY THAT AUDIBLE FIRE ALARM SOUND LEVEL SHALL BE AT LEAST 15dBA ABOVE AVERAGE AMBIENT SOUND LEVEL IN ALL OCCUPIABLE AREAS NFPA 72 SEC. 18.4.4.1.
- FIRE ALARM CONTRACTOR SHALL PROVIDE A RECORD OF COMPLETION AFTER COMPLETION OF OPERATIONAL ACCEPTANCE TESTS.
- POWER CIRCUITS SHALL BE ON A DEDICATED BRANCH CIRCUIT WITH RED MARKING, WITH LOCK OUT DEVICE, AND IDENTIFIED AS "FIRE ALARM CIRCUIT CONTROL".
- STROBES SHALL FLASH AT A RATE NOT EXCEEDING TWO FLASHES PER SECOND AND NOT LESS THAN ONE FLASH PER SECOND.
- AUDIBLE SIGNALS INTENDED FOR OPERATION IN THE PUBLIC MODE SHALL HAVE A SOUND LEVEL OF NOT LESS THAN 75dBA AT 10 FEET AND NO MORE THAN 110dBA AT THE MINIMUM HEARING DISTANCE FROM THE AUDIBLE APPLIANCE PER CEC 3501.1.
- FINAL FIRE ALARM TESTS SHALL BE CONDUCTED WITH DSA INSPECTOR OF RECORD PRESENT. THE LOCAL FIRE AUTHORITY SHALL BE NOTIFIED OF THE DATE AND TIME OF THE FINAL TESTING AND SHALL ASSIST/WITNESS SUCH TESTING WE ABLE.
- THE AUTOMATIC FIRE ALARM SYSTEM SHALL TRANSMIT ALARM, SUPERVISORY, AND TROUBLE SIGNALS TO AN APPROVED SUPERVISING STATION AS REQUIRED BY NFPA 72, AND AS AMENDED BY ARTICLE 91. THE SUPERVISING STATION SHALL BE LISTED AS EITHER UUFV OR UUVS BY UL OR SHALL MEET THE REQUIREMENTS OF FACTORY MUTUAL RESEARCH APPROVAL STANDARD 3011.
- INSTALLATION OF THE SYSTEMS SHALL NOT BE STARTED UNTIL DETAILED DESIGN DOCUMENTS AND SPECIFICATION, INCLUDING STATE FIRE MARSHAL LISTING NUMBERS FOR EACH COMPONENT OF THE SYSTEM, HAS BEEN APPROVED BY DSA.
- A STAMPED SET OF APPROVED FIRE ALARM DESIGN DOCUMENTS SHALL BE ON THE JOB SITE AND USED FOR INSTALLATION.
- ANY DISCREPANCIES BETWEEN THE DRAWINGS AND THE CODE OR RECOGNIZED STANDARDS SHALL BE BROUGHT TO THE ATTENTION OF DSA AND THE ARCHITECT/ENGINEER OF THE PROJECT.
- DSA, ARCHITECT/ENGINEER AND OWNER SHALL BE NOTIFIED A MINIMUM OF 48 HOURS PRIOR TO THE FINAL INSPECTION AND /OR TESTING.
- ALL PENETRATIONS THROUGH RATED ASSEMBLIES REQUIRING OPENING PROTECTION SHALL BE PROVIDED WITH A PENETRATION FIRE STOP SYSTEM AS IDENTIFIED IN CBC CHAPTER 7, UL OR OTHER APPROVED LAB TESTING CRITERIA. APPROVED TYPES OF MATERIALS SHALL BE IDENTIFIED WITHIN THE PROJECT SPECIFICATIONS WITHIN THE FIRE ALARM SECTION.
- THE ENTIRE LENS OF WALL MOUNTED VISIBLE NOTIFICATION DEVICES SHALL OCCUR BETWEEN +80" MINIMUM AND +96" MAXIMUM FROM FINISHED FLOOR.
- WALL MOUNTED AUDIBLE NOTIFICATION DEVICES SHALL HAVE THEIR TOPS MOUNTED AT 90" MINIMUM AND 100" MAXIMUM FROM FINISHED FLOOR AND NO CLOSER THEN 6" TO A HORIZONTAL STRUCTURE.
- AUDIBLE DEVICES SHALL BE SYNCHRONIZED TEMPORAL CODE 3 PATTERN, EXCEPT CARBON MONOXIDE ALARM, WHICH SHALL BE TEMPORAL CODE 4 PATTERN.
- THE CONTRACTOR SHALL ADJUST/INSTALL ALL DEVICES TO MAXIMIZE PERFORMANCE AND TO MINIMIZE FALSE ALARMS.


FIRE ALARM INSTALLATION NOTES (CONTINUED)

- UNDERGROUND AND EXTERIOR CONDUITS TO HAVE WATER TIGHT FITTINGS AND WIRE TO BE APPROVED FOR WET LOCATIONS.
- ALL FIRE ALARM WIRING SHALL BE FPLOR FPLP (FIRE POWER LIMITED OR FIRE POWER LIMITED PLENUM) AS REQUIRED FOR APPLICATION. WIRING IN CONDUIT ABOVE GROUND MAY BE TYPE THHN OR THWN.
- PER CEC STANDARDS, ALL WIRING IS TO BE PULLED THROUGH EACH JUNCTION BOX AND CONNECTED DIRECTLY TO EACH FIRE DEVICE. DO NOT SPLICE THE WIRE. ALL BOXES TO BE SIZED PER CEC.
- SMOKE DETECTORS SHALL NOT BE ANY CLOSER THAN 1' FROM FIRE SPRINKLERS OR 3' FROM ANY SUPPLY DIFFUSER. IN AREA OF CONSTRUCTION OR POSSIBLE DAMAGE / CONTAMINATION ON NEWLY INSTALLED FIRE ALARM, DEVICES SHALL BE COVERED UNTIL THAT AREA IS READY TO BE TURNED OVER TO THE OWNER.
- ALL FIRE ALARM CIRCUITS SHALL BE IN CONDUIT, SURFACE RACEWAY OR OPEN RUN ABOVE CEILINGS, UNDER FLOORS AND IN WALLS IN A NEAT AND PROTECTED MANNER AS INDICATED ON DESIGN DOCUMENTS. EXPOSED CIRCUITS ARE ONLY PERMITTED WHEN NOTED AS EXPOSED ON DESIGN DOCUMENTS.
- FIRE ALARM PANEL, REMOTES, AND COMPONENTS SHALL BE SECURED TO MOUNTING SURFACES PER MANUFACTURERS SPECIFICATIONS. NO SINGLE DEVICE SHALL EXCEED 20 LBS. WITHOUT SPECIAL MOUNTING DETAILS.
- THE INSTALLING CONTRACTOR SHALL PROVIDE A COMPLETED "SYSTEM RECORD OF COMPLETION" PER NFPA 72, FIGURE 7.8.2(a).
- FIRE ALARM CONTROL PANELS AND REMOTE ANNUNCIATORS SHALL BE INSTALLED WITH THEIR BOTTOMS MOUNTED AT 48" ABOVE THE FINISHED FLOOR.
- MICROPHONES ASSOCIATED WITH EMERGENCY VOICE ALARM COMMUNICATION SYSTEMS (EVAC) SHALL BE ACCESSIBLE FOR USE, INSTALLED IN COMPLIANCE WITH CBC SECTIONS 11B-305 AND 11B-308.
- THE INSTALLING CONTRACTOR SHALL PROVIDE SYSTEM PROGRAMMING FOR SUPERVISORY MONITORING PER CBC SECTION 901.6.2.
- SUPERVISORY MONITORING SHALL BE TESTED AND VERIFIED AS SENDING CORRECT SIGNALS IN CONJUNCTION WITH FINAL ACCEPTANCE TEST.
- OWNER SHALL BE RESPONSIBLE FOR ESTABLISHING A FIRE SYSTEM MONITORING CONTRACT OR PROVISIONS.

PROPER MOUNTING FOR SMOKE DETECTORS




DEVICE ELEVATION DETAIL




SYSTEM OPERATIONAL MATRIX

DEVICE	ACTIVATE COMMON ALARM SIGNAL INDICATOR LED	ACTIVATE AUDIBLE ALARM SIGNAL PIEZO SOUNDER	ACTIVATE COMMON SUPERVISORY SIGNAL INDICATOR LED	ACTIVATE AUDIBLE SUPERVISORY SIGNAL PIEZO SOUNDER	ACTIVATE COMMON TROUBLE SIGNAL INDICATOR LED	ACTIVATE AUDIBLE TROUBLE SIGNAL PIEZO SOUNDER	TRANSMIT FIRE ALARM SIGNAL TO SUPERVISING STATION	TRANSMIT SUPERVISORY SIGNAL TO SUPERVISING STATION	TRANSMIT TROUBLE SIGNAL TO SUPERVISING STATION	ACTIVATE AUDIBLE/VISUAL SIGNAL	SHUTDOWN DOWN HVAC WITHIN AREA	ACTIVATE ANNUNCIATOR ALARM SIGNAL	ACTIVATE ANNUNCIATOR SUPERVISORY SIGNAL INDICATOR	ACTIVATE ANNUNCIATOR TROUBLE SIGNAL	SOUND TEMPORAL CODE 4, & SOUNDER AS DETECTOR BASE.
AREA HEAT DETECTOR	X	X					X			X		X			
AREA SMOKE DETECTOR	X	X					X			X		X			
FIRE ALARM SYSTEM AC POWER FAILURE					X	X			X						X
FIRE ALARM SYSTEM LOW BATTERY					X	X			X						X
OPEN CIRCUIT					X	X			X						X
GROUND FAULT					X	X			X						X
NOTIFICATION APPLIANCE CIRCUIT SHORT					X	X			X						X

WIRING DIAG. & SYSTEM MATRIX



PROPER MOUNTING FOR HEAT DETECTORS



PEZZONI ENGINEERING, INC.
CONSULTING ELECTRICAL ENGINEERS
1150 9th Street, Suite #1415 Modesto, CA 95354
PHONE: 209-554-4602
HTTP://WWW.PEZZONI.COM
PEZZONI ENGINEERING, INC. © Copyrighted 2024

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

skw & associates
architecture • engineering • surveying
2257 scenic drive, Modesto, CA 95355 P: 209-759-2852

David J. Starck
architect
c.22908
Allan V. Stevenson
civil engineer
roc 67798



PROJECT TITLE:
SYLVAN UNION SCHOOL DISTRICT
**FREEDOM ELEMENTARY SCHOOL
(2) PORTABLE CLASSROOMS**
2101 Fine Ave
Modesto, CA 95355

FIRE ALARM DETAILS

SHEET TITLE:
REVISIONS:

BY: CCM/KP
LIST: FREEDOM
DATE: 02/16/2024
JOB: 23MO045


SHEET: **E0.2**

F:\A\060 SUSD PORTABLES AT VARIOUS\ENGR\SHEETS\060_E0.2 FIRE ALARM DETAILS.DWG cmeandez 02/16/24 12:00:10 PM

02/16/24 12:00:22 PM F:\24\060 SUSO PORTABLES AT VARIOUS\ENGR\SHEETS\060_E1.0 OVERALL SITE PLAN - FREEDOM.DWG cmenendez

SHAKUN AVENUE


FINE AVENUE



PLAN NOTES:

1. BOGEN MC2000 HEADEND -CONNECT (N) SPEAKERS WITHIN (N) PORTABLES.
2. REPLACE INTERNAL COMPONENTS AT (E) FACP LOCATION -SEE FIRE ALARM RISER DIAGRAM FOR SCOPE OF WORK.
3. REPLACE (E) REMOTE ANNUNCIATOR AT MAIN OFFICE AREA TO BE COMPATIBLES W/(N) FACP MAINBOARD & W/MICROPHONE.
4. APPROXIMATE ROUTING OF COMMUNICATION PATHWAYS -INSTALL (N) CABLES AS REQD.
5. REPLACE (E) NAC PANEL W/(N) ADDRESS SLC NOTIFICATION MODULE -RECONNECT (E) NAC CKTS IN KIND -SEE FIRE ALARM RISER DIAGRAM FOR ADDITIONAL REQMTS.

1 OVERALL SITE PLAN - ELECTRICAL
SCALE: 1"=30'-0"



PEZZONI ENGINEERING, INC.
CONSULTING ELECTRICAL ENGINEERS
1150 9th Street, Suite #1415 Modesto, CA 95354
PHONE: 209-554-4602
HTTP://WWW.PEZZONI.COM
PEZZONI ENGINEERING, INC. © Copyrighted 2024

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

skw & associates
architecture • engineering • surveying
2257 scenic drive, modesto, ca 95355 p: 209-759-2852

• david j. starck
architect
c 22905

• allan v. stevenson
civil engineer
roc 67758





PROJECT TITLE:
SYLVAN UNION SCHOOL DISTRICT
**FREEDOM ELEMENTARY SCHOOL
(2) PORTABLE CLASSROOMS**
2101 Fine Ave
Modesto, CA 95355

SHEET TITLE:
OVERALL SITE PLAN - ELECTRICAL


REVISIONS:

BY : CCM/KP
LIST : FREEDOM
DATE : 02/16/2024
JOB : 25M045
SHEET : **E1.0**


02/16/24 12:00:22 PM F:\24\060 SUSO PORTABLES AT VARIOUS\ENGR\SHEETS\060_E1.0 OVERALL SITE PLAN - FREEDOM.DWG cmenendez



1 PORTABLES FLOOR PLAN - FIRE ALARM
SCALE: 1/8"=1'-0"




3 FIRE ALARM RISER DIAGRAM
SCALE: NTS



2 PORTABLES FLOOR PLAN - POWER
SCALE: 1/8"=1'-0"

- ## PLAN NOTES:
- (E) PULLBOX.
 - (E) 2-1 1/2" W/PORT FEEDERS PER SINGLE LINE DIAGRAM.
 - (N) 1 1/2" W/PORTABLE FEEDER PER SINGLE LINE DIAGRAM.
 - (E) PANEL W/BLDG -INSTALL (N) 20A-1P BREAKER FOR (N) PROJECTOR CIRCUIT AS SHOWN.
 - (N) WIRELESS ACCESS POINT W/CAT-6 DATA CABLES AS SHOWN BACK TO (E) BLDG 'C1' -PROVIDE WET LISTED CABLE THROUGHOUT
 - (N) TEACHER WORKSTATION W/CAT-6 DATA & TELE CABLES AS SHOWN BACK TO (E) BLDG 'C1' -PROVIDE WET LISTED CABLE THROUGHOUT
 - (N) 8SURFACE MOUNTED SPEAKER W/XFMR W/2C/16AWG STP CABLE TO (E) PORTABLE #11
 - (N) PROJECTOR LOCATION (FIELD VERIFY LOCATION) W/DISTRICT W/(N) DUPLEX RECEPTACLE & CAT-6 DATA CABLES AS SHOWN BACK TO (E) BUILDING 'A' -INSTALL WITHIN 2900 SERIES WIREMOLD (WHITE) -PROVIDE WET LISTED CABLE THROUGHOUT
 - (N) PROVIDE 2" LFMC FLEX CONNECTION BETWEEN BUILDINGS.
 - (E) PANEL 'P' W/(E) SPARE 100A-2P. BREAKERS.
 - (E) IDF CABINET -INSTALL (N) PATCH PANEL AS REQUIRED TO TERMINATE (N) CAT-6 CABLES SHOWN.

4 PARTIAL SINGLE LINE DIAGRAM
SCALE: NTS



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

skw & associates
architecture • engineering • surveying
2257 scenic drive, modesto, ca 95355 p. 209-524-8525 f. 209-758-2852

• david j. starck
architect
c.22905
• allan v. stevenson
civil engineer
roc 67798



PROJECT TITLE:
SYLVAN UNION SCHOOL DISTRICT
FREEDOM ELEMENTARY SCHOOL
(2) PORTABLE CLASSROOMS
2101 Fine Ave
Modesto, CA 95355


PORTABLE FLOOR PLAN - ELECTRICAL
SHEET TITLE:
REVISIONS:

BY : CCM/KP
LIST : FREEDOM
DATE : 02/16/2024
JOB : 25MO45
SHEET : E2.0


PEZZONI ENGINEERING, INC.
CONSULTING ELECTRICAL ENGINEERS
1150 9th Street, Suite #1415 Modesto, CA 95354
PHONE: 209-554-4602
HTTP://WWW.PEZZONI.COM
PEZZONI ENGINEERING, INC. © Copyrighted 2024

02/16/24 12:00:28 PM F:\A\060 SUBD PORTABLES AT VARIOUS\ENGR\SHEETS\060_E2.0 FLOOR PLAN - FREEDOM.DWG cmendez


02/16/24 12:00:28 PM F:\A\060 SUBD PORTABLES AT VARIOUS\ENGR\SHEETS\060_E2.0 FLOOR PLAN - FREEDOM.DWG cmendez




1 COMMUNICATION CONNECTION AT BLDG.
SCALE: N.T.S.




2 PORTABLE BUILDING GROUND (TYP.)
SCALE: N.T.S.




3 UNDERGROUND CONNECTION AT PORTABLE
SCALE: N.T.S.



4 SEISMIC CONDUIT BETWEEN BLDGS.
SCALE: N.T.S.



5 ELECTRICAL TRENCH SECTION (TYP.)
SCALE: N.T.S.



6 CABLE SUPPORT DETAILS
SCALE: N.T.S.

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC.
REVIEWED FOR:
SS FLS ACS
DATE: 2/27/2024

skw & associates
architecture • engineering • surveying
2257 scenic drive, modesto, ca 95355 p. 209-759-2852 f. 209-759-2852

• david j. starck
architect
c.22908

• allan v. stevenson
civil engineer
roc 67798



PROJECT TITLE:
SYLVAN UNION SCHOOL DISTRICT
FREEDOM ELEMENTARY SCHOOL
(2) PORTABLE CLASSROOMS
2101 Fine Ave
Modesto, CA 95355

ELECTRICAL DETAILS

SHEET TITLE:
REVISIONS:

BY: CCM/KP
LIST: FREEDOM
DATE: 02/16/2024
JOB: 25MO45
SHEET: E3.1

02/16/24 12:00:36 PM F:\24\060 SUSD PORTABLES AT VARIOUS\ENGR\SHEETS\060_E3.1 ELECTRICAL DETAILS.DWG cmenendez

02/16/24 12:00:36 PM F:\24\060 SUSD PORTABLES AT VARIOUS\ENGR\SHEETS\060_E3.1 ELECTRICAL DETAILS.DWG cmenendez

MODULAR CLASSROOM BUILDINGS (WITH OPTIONAL RESTROOM MODULES)

BUILDING SIZE: 24' X 40' EXPANDABLE TO 120' X 40' PC 04-121999

BY
SILVER CREEK MODULAR, INC.
2830 BARRETT AVE, PERRIS, CALIFORNIA 92571
PHONE : (951) 943-5393 FAX : (951) 943-2211

SYLVAN UNION SCHOOL DISTRICT FREEDOM ELEMENTARY SCHOOL (2) 24' X 40' CLASSROOM


SHEET INDEX - PROJECT SPECIFIC

SHEET	ARCHITECTURAL
A-0N	COVER SHEET
A-1.01N	FLOOR PLAN 24' x 40' PROJECT SPECIFIC

SHEET	ELECTRICAL
E-1.01N	ELECTRICAL PLAN AND SCHEDULE - 24' x 40'

SHEET INDEX - PC 04-12199

SHEET	ARCHITECTURAL
A-0	COVER SHEET
A-0A	T & I FORMS
A-0B	T & I FORMS
A-0.1	SYMBOLS LEGEND, ABBREVIATION, AND ADA SIGNAGE
A-0.2	SCHEDULES
A-0.3	TYPICAL KEY PLANS - 24' TO 120' x 40'
A-0.33	DESIGN ENERGY VALUES - WOOD FLOOR - WALL HVAC
A-0.34	PRF FORMS - ZONE 24x40 - 14 WORST CASE
A-0.6A	CERTIFICATE OF COMPLIANCE FORMS
A-0.6B	CERTIFICATE OF COMPLIANCE FORMS
A-0.6C	CERTIFICATE OF COMPLIANCE FORMS
A-0.7	PV SYSTEM REQ'S, ENERGY MANDATORY MEASURES & CALGREEN SPEC'S
A-1.01	FLOOR PLAN - 24' x 40'
A-2.01	REFLECTED CEILING PLAN - 24' x 40'
A-2.20	CEILING DETAILS - T-GRID
A-3.01	ROOF PLAN - 24' x 40' - METAL DECK - MONO OR DUAL SLOPE
A-3.50	ROOF DETAILS - STANDING SEAM ROOF DECK
A-4.01	EXTERIOR ELEVATIONS - 24' x 40' - MONO OR DUAL SLOPE
A-5.01	CROSS SECT. - MONO SLOPE
A-5.05	CROSS SECTION
A-5.50	ARCHITECTURAL DETAILS - WOOD STUD - SHTG
A-5.70	ARCHITECTURAL DETAILS - FLOOR
A-5.80	ARCHITECTURAL DETAILS - MISCELLANEOUS/OPTIONS
A-5.81	ARCHITECTURAL DETAILS - MISCELLANEOUS/OPTIONS
A-6.01	INTERIOR ELEVATIONS - 24' x 40'



PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC. (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.

ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
COVER SHEET

REVISIONS

- 1
- 2
- 3
- 4
- 5

PRE-CHECK (PC) DOCUMENT CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

PC STATE AGENCY APPROVAL

Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO: 11478

DRAWN BY:

SCALE: AS NOTED

DATE: 02-27-2023

P.C. SHEET NUMBER

A-0N

- #### GENERAL NOTES
1. FIRE ALARM IS NOT PART OF THIS APPROVAL.
 2. ALLOWABLE AREA IS BASED ON 10' SET BACK FROM IMAGINARY ASSUMED LINE PER 2022 CBC 705.3.
 3. THIS PC IS DESIGNED STRUCTURALLY TO SUPPORT THE WEIGHT OF A FIRE SPRINKLER SYSTEM.
 4. PC IS DESIGNED AS A SINGLE STORY MODULAR BUILDING.
 5. FOR SOILS TYPES / DESIGN BEARING STRENGTH, SEE STRUCTURAL SPECIFICATIONS.
 6. ALL WORK SHALL CONFORM TO TITLE 24, CALIFORNIA CODE OF REGULATIONS (CCR).
 7. THIS PC IS NOT APPROVED FOR "A" OCCUPANCY USES.
 8. EXTERIOR WALL OPENINGS TO COMPLY W/ 705.8, 2022 CBC. THE USE OF UNPROTECTED OPENINGS SHALL BE VERIFIED IN THE PROJECT SPECIFIC APPLICATIONS.
 9. EXTERIOR PROJECTIONS ARE TO BE FIRE PROTECTED WHERE REQUIRED BY SECTIONS 705.2 & 1406.
 10. SEE SHEETS A-0.7 FOR REQUIRED BUILDING ENVELOPE ASSEMBLIES AND HVAC SYSTEM.
 11. PURSUANT TO D.S.A. APPROVAL ALL PRODUCTS CAN BE SUBSTITUTED BY AN "EQUAL".
 12. BUILDING(S) TO BE LOCATED IN ANY FIRE HAZARD SEVERITY ZONE OR ANY WILDLAND - URBAN INTERFACE FIRE AREA SHALL COMPLY WITH CBC CHAPTER 7A.
 13. WHEN THE PRE-CHECKED BUILDING IS SITE ADAPTED, THE BUILDING AND SITE FEATURES NEED TO COMPLY WITH CALGREEN CODE, SECTION 5.507.4 FOR THE SITE SPECIFIC LOCATION.
 14. IN THE EVENT THAT A PC CLASSROOM IS DESIGNED TO CONNECT TO THE SAME PC CLASSROOM, INTERIOR SOUND TRANSMISSION IN THE INTERIOR ADJOINING WALL AND FLOOR-CEILING SHALL MEET THE MINIMUM REQUIREMENTS OF THE STC RATING OF 40 PER CALGREEN CODE, SECTION 5.507.4.3.
 15. FOR THE CONCRETE BELOW GRADE (AMM*) FOUNDATION OPTION THIS PC USES A DSA APPROVED ALTERNATE MEANS OF COMPLIANCE WITH THE FOUNDATION DURABILITY REQUIREMENTS OF CBC 1402.2 + 1403.2 (WEATHER-RESISTANT EXTERIOR WALL ENVELOPE AND CONTINUOUS WATER-RESISTIVE BARRIER ON WALLS TO FOUNDATION) + 2304.12.1.2 (PROTECTION AGAINST DECAY AND TERMITES). DETAILS ARE PROVIDED ON SHEETS A-5.71 - A-5.78 AS APPLICABLE.
 16. THE BUILDING PAD ELEVATION SHALL ABOVE THE DESIGN FLOOD ELEVATION.
 17. WHEN THE SITE-SPECIFIC PROJECT IS LOCATED IN A FLOOD ZONE OTHER THAN ZONE X, A SEALED LETTER FROM A GEOTECHNICAL ENGINEER SHALL BE PROVIDED TO VALIDATE THE APPLICABILITY OF THE ALLOWABLE SOIL BEARING PRESSURES INDICATED ON THE PC DRAWINGS. EXCEPTION: THIS LETTER IS NOT REQUIRED FOR PROJECTS LOCATED IN FLOOD ZONE D WHEN A GEOTECHNICAL REPORT IS AVAILABLE FOR IMPROVEMENTS ON THE SAME PROJECT SITE, AND IN ACCORDANCE WITH THE CURRENT CBC, WHICH CONFIRMS THAT THE SITE IS NOT IN A FLOOD HAZARD ZONE OR CONFIRMS THAT THE FLOOD HAZARD DOES NOT RESULT IN A REDUCTION OF SOIL CAPACITY VALUES.



BUILDING DATA	
NUMBER OF STORIES:	1 - STORY
OCCUPANCY:	E or B
TYPE OF CONSTRUCTION:	V-B
FLOOR LIVE LOAD:	50-15 PSF PARTITION LOAD
ROOF LIVE LOAD:	20 PSF
FLOOR DEAD LOAD:	WOOD FLOOR - 11 PSF
ROOF DEAD LOAD:	18 PSF (INCLUDING SPRINKLER LOAD AND SOLAR ALLOWANCE)
SOLAR ALLOWANCE:	0.6 PSF OVER ENTIRE ROOF AREA
RAMP LIVE LOAD:	100 PSF
BUILDING AREA:	24'x40' BLDG 960 S.F.
ALLOWABLE AREA:	9,000 S.F.
(ALL W/O OVERHANGS)	
FOUNDATION:	WOOD (CONDITIONAL)
CEC CLIMATE ZONE:	ALL ZONES
ALLOWABLE SOIL PRESSURE	
WOOD FOOTING (DL & DL+LL & DL+LL+SEISMIC)	1,000 psf
CONCRETE FOOTING (DL & DL+LL & DL+LL+SEISMIC)	1,500 psf
ROOF SNOW LOAD	
GROUND SNOW LOAD, P _g FROM COUNTY	0
ROOF SNOW LOAD: FLAT P _g	
SNOW EXPOSURE FACTOR C _e	-
SNOW IMPORTANCE FACTOR I _s	1.0
THERMAL FACTOR C _t	-
FLOOD DESIGN (SEE GENERAL NOTE #16 + 17)	
FLOOD HAZARD AREA	NO
WIND DESIGN	
BASIC WIND SPEED (3 SECOND GUST) V _{ult}	120
RISK CATEGORY	II
WIND EXPOSURE CATEGORY	C
TOPOGRAPHIC FACTOR K _{zt}	1

SEISMIC DESIGN FOR SITE SPECIFIC PROJECTS	
SELECT ONE	<input checked="" type="checkbox"/> DESIGN BASED ON SITE CLASS D _{detrad}
NO GEOTECHNICAL INVESTIGATION REQUIRED	
S _s = 0.625	F _a = 1.2
<input type="checkbox"/> DESIGN BASED ON SITE CLASS DETERMINED PER CHAPTER 20 OF ASCE 7-16	
GEOTECHNICAL INVESTIGATION PROVIDED	
SITE CLASS:	<input type="checkbox"/> C <input type="checkbox"/> D
S _s = _____	F _a = _____ PER ASCE 7-16 SUPPL 3, TABLE 11.4-1
<input type="checkbox"/> DESIGN BASED ON SITE SPECIFIC GROUND MOTION HAZARD ANALYSIS PER CHAPTER 21 OF ASCE 7-16	
SHORT-PERIOD DESIGN SPECTRAL RESPONSE PARAMETER, S _{0.5} , SHALL BE AS SPECIFIED IN GEOTECHNICAL INVESTIGATION	
CGS APPROVAL REQUIRED	
NOT ELIGIBLE FOR OTC REVIEW	
SITE CLASS:	<input type="checkbox"/> C <input type="checkbox"/> D
S _{0.5} = 1/2 F _a S _s = 0.541	
<input checked="" type="checkbox"/> SITE CLASS C or D: 0.7 x S _{0.5} * = 0.7 x 0.541 = 0.3737 ≤ 1.56	
C _g = 0.45 USED IN DESIGN	
SEISMIC DESIGN CATEGORY: <input checked="" type="checkbox"/> D <input type="checkbox"/> E	
* SITE SPECIFIC S _{0.5} VALUE BEFORE APPLYING REDUCTION ALLOWED BY ASCE 7 SECTION 12.8.1.3	



- #### APPLICABLE STANDARDS
- | | |
|---|--------------|
| NFPA 13 AUTOMATIC SPRINKLER SYSTEMS (A, AMENDED) | 2022 EDITION |
| NFPA 72 NATIONAL FIRE ALARM CODE (CALIFORNIA AMENDED) | 2022 EDITION |
| (NOTE: SEE UL STANDARD 1971 FOR "VISUAL DEVICES") | |
| ACI 318 BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE | 2019 EDITION |
| ASME A17.1 (W/A17.1A CSA B44A-2019 ADDENDA) SAFETY CODE FOR ELEVATORS & ESCALATORS. | 2019 EDITION |
- #### APPLICABLE CODES
- LIST OF 2022 CALIFORNIA CODE OF REGULATIONS
- 2022 BUILDING ADMINISTRATIVE CODE (CAC), PART 1, TITLE 24 C.C.R.
 - 2022 CALIFORNIA BUILDING CODE (CBC), PART 2, TITLE 24 C.C.R.
 - 2022 CALIFORNIA ELECTRICAL CODE (CEC), PART 3, TITLE 24 C.C.R.
 - 2022 CALIFORNIA MECHANICAL CODE (CMC), PART 4, TITLE 24 C.C.R.
 - 2022 CALIFORNIA PLUMBING CODE (CPC), PART 5, TITLE 24 C.C.R.
 - 2022 CALIFORNIA ENERGY CODE, PART 6, TITLE 24 C.C.R.
 - 2022 CALIFORNIA FIRE CODE (FC), PART 9, TITLE 24 C.C.R.
 - 2022 CALIFORNIA GREEN BUILDING STANDARDS CODE (CALGREEN), PART 11, TITLE 24 C.C.R.
 - 2022 CALIFORNIA REFERENCED STANDARDS CODE, PART 12, TITLE 24 C.C.R.
 - TITLE 19 C.C.R., PUBLIC SAFETY, STATE FIRE MARSHAL REGULATIONS.
- APPLICABLE STANDARDS:
- FOR A LIST OF APPLICABLE STANDARDS, INCLUDING CALIFORNIA AMENDMENTS TO THE NFPA STANDARDS, REFER TO CBC CHAPTER 35 AND CFC CHAPTER 80.

SEISMIC DESIGN	
LATERAL FORCE-RESISTING SYSTEM	OMF
ANALYSIS PROCEDURE	EQUIV. LATERAL FORCE
SEISMIC DESIGN CATEGORY (SDC)	III
SEISMIC IMPORTANCE FACTOR I _e	1.0
SEISMIC RESPONSE COEFFICIENT C _s	0.45
RESPONSE MODIFICATION COEFFICIENT R	3.5
SITE CLASS	D
MAPPED SPECTRAL RESPONSE ACCELERATION AT SHORT PERIOD S _{0.5}	2.8
SHORT PERIOD SITE COEFFICIENT F _p	1.2
DESIGN SPECTRAL RESPONSE ACCELERATION AT SHORT PERIOD S _{0.5}	2.23 ***
MAPPED SPECTRAL RESPONSE ACCELERATION AT 1-SECOND PERIOD S ₁	1.064
LONG PERIOD SITE COEFFICIENT, F _p	1.7
DESIGN SPECTRAL RESPONSE ACCELERATION AT 1-SECOND PERIOD S _{0.1}	1.2
HORIZONTAL OR VERTICAL IRREGULARITY TYPES	NONE
REDUNDANCY FACTOR R _{ho}	1.0
FUNDAMENTAL PERIOD T	< 0.5s
*** PER SUPPLEMENT 3 OF ASCE 7-16, STRUCTURES SITUATED IN SITE CLASS D WITH S1 VALUES THAT ARE EQUAL TO OR GREATER THAN 0.2 ARE EXEMPTED FROM THE GROUND MOTION HAZARD ANALYSIS. THIS EXEMPTION APPLIES WHEN THE PARAMETER SM1, DETERMINED THROUGH THE USE OF EQ. 11.4-2, IS ELEVATED BY 50% FOR ALL APPLICATIONS OF SM1	
*** FOR THE PURPOSES OF CALCULATING C _g (PER ASCE 7-16 12.8.1.3) S _{0.5} = 1.56 ACTUAL PERIOD T = 0.34 SEC.	

NOTE:
CHANGES TO THE APPROVED DRAWINGS AND SPECIFICATIONS SHALL BE MADE BY AN ADDENDUM OR A CONSTRUCTION CHANGE DOCUMENT (CCD) APPROVED BY THE DIVISION OF THE STATE ARCHITECT, AS REQUIRED BY SECTION 4-338, PART 1, TITLE 24, CCR.



- NOTES:
- SIZE OF CONDUCTORS SHALL COMPLY WITH CEC TABLE 250.66
 - ELEC. TRADE SHALL CHECK AREA FOR EXISTING CONDUITS, SEWER, GAS & WATER PIPING BEFORE DRIVING GROUND RODS.
 - BOND SEPARATE CONDUCTORS FROM GROUND ROD TO ELECTR. PANEL & TO METAL BUILDING FRAME (CEC 250.52) IN ADDITION TO THE DETAIL SHOWN ABOVE, BOND THE ELECTRICAL GROUND TO METAL UNDERGROUND WATER PIPE IN DIRECT CONTACT WITH THE EARTH FOR 10 FT. OR MORE, IF AVAILABLE (CEC 250.52)
 - ALL MODULES OF METAL FRAME BLDGS. SHALL BE ELECTRICALLY BONDED TOGETHER (BOLTING ONLY IS NOT ACCEPTABLE BONDING). BONDING SHALL INCLUDE METAL RAMP.
 - CHECK RESISTANT TO GROUND ROD, IF RESISTANCE EXCEEDS 25 OHMS, INSTALL ADDITIONAL GROUND RODS WITH CONDUCTORS AS SHOWN SEPARATED AT LEAST 6'-0" UNTIL RESISTANCE IS REDUCED TO 25 OHMS OR LESS (CEC 250.56)



GROUND JUMPER AT MODLINE

EACH BUILDING SHALL BE SEPARATELY GROUNDED WITH A 3/4" RD. X 8' COPPER/CLAD STEEL GROUND ROD. WHERE ROCK BOTTOM IS ENCOUNTERED, ROD SHALL BE DRIVEN AT AN ANGLE NOT TO EXCEED 45 DEGREES FROM THE VERTICAL OR SHALL BE BURIED IN A TRENCH THAT IS AT LEAST 30" DEEP (BY SITE ELECTRICAL).

TESTING: TEST FOR RESISTANCE TO GROUND, IF RESISTANCE EXCEEDS 25 OHMS, INSTALL ADDITIONAL GROUND RODS SEPARATED AT LEAST 6'-0" UNTIL RESISTANCE IS REDUCED TO 25 OHMS OR LESS. (BY SITE ELECTRICAL).

APPROVAL OF THIS PLAN DOES NOT CONSTITUTE APPROVAL OF THIS FIRE ALARM FOR ALL SITES. THE FIRE ALARM SYSTEM AND/OR COMPONENTS MAY BE REQUIRED TO BE CHANGED DUE TO SITE LOCATION EXISTING CONDITIONS OR INCOMPATIBLE COMPONENTS.

GROUND MG TEST SHALL BE DONE IN THE PRESENCE OF THE PROJECT INSPECTOR, ALL GROUNDING SHALL BE IN ACCORDANCE WITH CEC ARTICLE 250.

FIRE ALARM NOTES

- SMOKE AND HEAT DETECTOR CONDUIT AND DEVICES PROVIDED AND INTERCONNECTED BY OTHERS TO FIRE ALARM SYSTEM
- PROVIDE DEDICATED FIRE ALARM 120 VOLT CIRCUIT CONNECTED TO LOCKED-ON BREAKER. THE CIRCUIT BREAKER SHALL BE LOCKED-ON WITH APPROVED LOCKING DEVICE, MARKED RED AND IDENTIFIED AS "FIRE ALARM CONTROL CIRCUIT". NFPA 72 SECTION 10.6.5.2

MEP COMPONENT ANCHORAGE NOTE

ALL MECHANICAL, PLUMBING AND ELECTRICAL COMPONENTS SHALL BE ANCHORED AND INSTALLED PER THE DETAILS ON THE DSA APPROVED CONSTRUCTION DOCUMENTS. THE FOLLOWING COMPONENTS SHALL BE ANCHORED OR BRACED TO MEET THE FORCE AND DISPLACEMENT REQUIREMENTS PRESCRIBED IN THE 2022 CBC SECTIONS 1617A.1.18 THROUGH 1617A.1.26 AND ASCE 7-16 CHAPTERS 13, 26, AND 30:

- ALL PERMANENT EQUIPMENT AND COMPONENTS.
- TEMPORARY OR MOVABLE EQUIPMENT THAT IS PERMANENTLY ATTACHED (E.G. HARD WIRED) TO THE BUILDING UTILITY SERVICES SUCH AS ELECTRICITY, GAS OR WATER. "PERMANENTLY ATTACHED" SHALL INCLUDE ALL ELECTRICAL CONNECTIONS EXCEPT PLUGS FOR 110/220 VOLT RECEPTACLES HAVING A FLEXIBLE CABLE.
- TEMPORARY, MOVABLE OR MOBILE EQUIPMENT WHICH IS HEAVIER THAN 400 POUNDS OR HAS A CENTER OF MASS LOCATED 4 FEET OR MORE ABOVE THE ADJACENT FLOOR OR ROOF LEVEL THAT DIRECTLY SUPPORT THE COMPONENT IS REQUIRED TO BE RESTRAINED IN A MANNER APPROVED BY DSA.

THE FOLLOWING MECHANICAL AND ELECTRICAL COMPONENTS SHALL BE POSITIVELY ATTACHED TO THE STRUCTURE, BUT NEED NOT DEMONSTRATE DESIGN COMPLIANCE WITH THE REQUIREMENTS NOTED ABOVE. THESE COMPONENTS SHALL HAVE FLEXIBLE CONNECTIONS PROVIDED BETWEEN THE COMPONENT AND ASSOCIATED DUCTWORK, PIPING, AND CONDUIT. FLEXIBLE CONNECTIONS MUST ALLOW MOVEMENT IN BOTH TRANSVERSE AND LONGITUDINAL DIRECTIONS:

- COMPONENTS WEIGHING LESS THAN 400 POUNDS AND HAVE A CENTER OF MASS LOCATED 4 FEET OR LESS ABOVE THE ADJACENT FLOOR OR ROOF LEVEL THAT DIRECTLY SUPPORT THE COMPONENT.
- COMPONENTS WEIGHING LESS THAN 20 POUNDS, OR IN THE CASE OF DISTRIBUTED SYSTEMS, LESS THAN 5 POUNDS PER FOOT, WHICH ARE SUSPENDED FROM A ROOF OR FLOOR OR HUNG FROM A WALL.

THE ANCHORAGE OF ALL MECHANICAL, ELECTRICAL AND PLUMBING COMPONENTS SHALL BE SUBJECT TO THE APPROVAL OF THE DESIGN PROFESSIONAL IN GENERAL RESPONSIBLE CHARGE OR STRUCTURAL ENGINEER DELEGATED RESPONSIBILITY AND ACCEPTANCE BY DSA. THE PROJECT INSPECTOR WILL VERIFY THAT ALL COMPONENTS AND EQUIPMENT HAVE BEEN ANCHORED IN ACCORDANCE WITH THE ABOVE REQUIREMENTS.

THE ANCHORAGE OF ALL MECHANICAL, ELECTRICAL AND PLUMBING COMPONENTS SHALL BE SUBJECT TO THE APPROVAL OF THE DESIGN PROFESSIONAL IN GENERAL RESPONSIBLE CHARGE OR STRUCTURAL ENGINEER DELEGATED RESPONSIBILITY AND ACCEPTANCE BY DSA. THE PROJECT INSPECTOR WILL VERIFY THAT ALL COMPONENTS AND EQUIPMENT HAVE BEEN ANCHORED IN ACCORDANCE WITH THE ABOVE REQUIREMENTS.

TYPICAL GROUNDING DETAIL 1

PIPING, DUCTWORK AND ELECTRICAL DISTRIBUTION SYSTEM BRACING NOTE

PIPING, DUCTWORK AND ELECTRICAL DISTRIBUTION SYSTEMS SHALL BE BRACED TO COMPLY WITH THE FORCES AND DISPLACEMENTS PRESCRIBED IN ASCE 7-16 SECTION 13.3 AS DEFINED IN ASCE 7-16 SECTION 13.6.5, 13.6.6, 13.6.7, 13.6.8 AND 2022 CBC SECTIONS 1617A.1.24, 1617A.1.25 & 1617A.1.26.

THE METHOD OF SHOWING BRACING AND ATTACHMENTS TO THE STRUCTURE FOR THE IDENTIFIED DISTRIBUTION SYSTEM ARE AS NOTED BELOW. WHEN BRACING AND ATTACHMENTS ARE BASED ON A PREAPPROVED INSTALLATION GUIDE (E.G., OSHPD OPA FOR 2013 CBC OR LATER), COPIES OF THE BRACING SYSTEM INSTALLATION GUIDE OR MANUAL SHALL BE AVAILABLE ON THE JOBSITE PRIOR TO THE START OF AND DURING THE HANGING AND BRACING OF THE DISTRIBUTION SYSTEMS. THE STRUCTURAL ENGINEER OF RECORD SHALL VERIFY THE ADEQUACY OF THE STRUCTURE TO SUPPORT THE HANGER AND BRACE LOADS.

MECHANICAL PIPING (MP), MECHANICAL DUCTS (MD), PLUMBING PIPING (PP), ELECTRICAL DISTRIBUTION SYSTEM (E):

MP MD PP E OPTION 1: DETAILED ON THE APPROVED DRAWINGS WITH PROJECT SPECIFIC NOTES AND DETAILS.

LIGHTING CONTROL SYSTEM SEQUENCE OF OPERATIONS

THE LIGHTING CONTROL SYSTEM BASIS OF DESIGN SHALL BE THE LUTRON VIVE WIRELESS LIGHTING CONTROL SYSTEM. THE SYSTEM SHALL BE CAPABLE OF PROVIDING MANUAL CONTROL, OCCUPANCY SENSING CONTROL AND DAYLIGHT HARVESTING CONTROL.

SEQUENCE:

OCCUPANT ENTERS:
ALL LIGHTS AUTOMATICALLY TURN ON TO 50% LIGHT LEVEL. OCCUPANT MAY INCREASE LIGHTS TO MAXIMUM LEVEL MANUALLY WITH WALL CONTROL.
WHEN OCCUPIED:
LIGHTING IN DAYLIT ZONES AUTOMATICALLY DIMBRIGHTEN BASED ON DAYLIGHT AVAILABILITY.
OCCUPANT MAY MANUALLY DIMBRIGHTEN THE LIGHTS WITH WALL CONTROL.
OCCUPANT EXITS:
ALL LIGHTS AUTOMATICALLY TURN OFF 15 MINUTES AFTER VACANCY.

CONDUIT FILL AND CONDUCTOR CAPACITY TABLE

(ALL CONDUCTORS SHALL BE TYPE THHN/THWN 90°C. COPPER)

WIRE SIZE	CAPACITY	NO. OF CONDUCTOR PERMITTED			
		1/2" C	3/4" C	1" C	1 1/4" C
#12	20A	9	16	25	45
#10	30A	5	10	16	28
#8	45A	2	5	8	14
#6	65A	1	3	5	10
#4	85A	1	2	4	7

JUNCTION BOX SIZE TABLE

BOX SIZE	CU. IN.	MAX NO. OF CONDUCTORS			
		#12	#10	#8	#6
4SS 1 1/4" x 4" SQ	18.0	8	7	6	0
4S 1 1/2" x 4" SQ	21.0	9	8	7	0
4SD 2 1/8" x 4" SQ	30.3	13	12	10	6
4SX 2 7/8" x 4" SQ	43.5	23	21	17	10
5SD 2 1/8" x 4-11/16" SQ	42.0	18	16	14	6
5SX 3 7/8" x 4-11/16" SQ	66.0	38	34	28	17
6SA 4" x 6" SQ	144.0	64	57	48	28

* DEDUCT ONE CONDUCTOR FOR (1) OR MORE GROUNDING CONDUCTORS ENTERING THE BOX

LEGEND

- 2x4 CEILING RECESSED LIGHT, LED LIGHT FIXTURE WITH DIMMING WATTAGE: 51 WATTS (MAX), 5000L (MIN)
- WALL MOUNTED HVAC UNIT. SEE MECHANICAL DWGS
- ROOF MOUNTED HVAC UNIT-SEE MECHANICAL DWGS
- ELECTRICAL PANEL AT +60" AFF TO TOP OF ELECTRICAL PANEL WITH 1 1/2" DIA POWER STUB UP (U.N.O.)
- CEILING MOUNTED OCCUPANCY SENSOR
- CEILING MOUNTED PHOTOCELL
- ULTRASONIC CEILING OCCUPANCY SENSOR. SENSOR TO BE CONNECTED TO KEYED LIGHT SWITCHES FOR MANUAL OVERRIDE AND USE FOR RESTROOM W/ PARTITIONS.
- SINGLE SWITCH WALL OCCUPANCY SENSOR. WATTSTOPPER PW-100 OR EQUAL. SENSOR TO BE MOUNTED AT +44" AFF
- DIMMER SWITCH, AT +48" AFF. TO TOP OF OUTLET BOX
- LIGHT SWITCH. MOUNT AT +48" AFF TO TOP OF OUTLET BOX
- 3-WAY LIGHT SWITCH. MOUNT AT +48" AFF TO TOP OF OUTLET BOX
- KEYED SWITCH MOUNT AT +48" AFF TO TOP OF OUTLET BOX
- DUPLEX (WALL MOUNTED) RECEPTACLE 15A - 125V - 3 WIRE. MOUNT AT +18" AFF U.O.N. TO CENTERLINE OF DEVICE
- EXTERIOR WEATHER PROOF GFI RECEPTACLE AT +24" AFF FOR A/C SERVICES (MAX 255-0" FROM UNITS)
- GROUND FAULT CIRCUIT INTERRUPT RECEPTACLE WITHIN 6'-0" OF ALL SINKS
- ROOF MOUNTED WEATHER PROOF GFI RECEPTACLE
- EXTERIOR LED LIGHT FIXTURE W/ 90 MIN. EMERGENCY BATTERY BACKUP WHEN 'EM' IS DESIGNATED NEXT TO FIXTURE W/ PHOTOCELL W/ 30w MAX. MOUNT AT +93" AFF
- CLOCK OUTLET AT +90" AFF TO CENTERLINE OF DEVICE
- EXIT SIGN REQUIRED FOR CLASSROOMS WITH TWO OR MORE EXTERIOR DOORS. CLASSROOMS WITH ONE EXTERIOR DOOR - OPTIONAL)
- 4SD J-BOX FOR FIRE ALARM PULL STATION (DEVICE BY OTHERS). MOUNT AT +48" AFF TO TOP OF OUTLET BOX WITH 3/4" CONDUIT TO FIRE ALARM STROBE WITH PULL STRING
- 4SD J-BOX FOR FIRE ALARM STROBE OR VOICE EVAC SPEAKER/STROBE (DEVICE BY OTHERS). BOTTOM OF LENS SHALL BE BETWEEN 80" AND 96" AFF AND WITH 3/4" CONDUIT TO EXTERIOR FIRE ALARM SPEAKER/HORN WITH PULL STRING
- 4SD J-BOX FOR EXTERIOR FIRE ALARM SPEAKER (DEVICE BY OTHERS). MOUNT AT +90" AFF TO TOP OF DEVICE WITH 3/4" CONDUIT STUBBED TO ATTIC WITH PULL STRING
- RECESSED 4SD J-BOX W/ COVER PLATE FOR FUTURE FIRE ALARM SYSTEM BY OTHERS. MOUNT AT +18" AFF U.O.N. TO CENTERLINE OF BOX AND PROVIDE 1" CO STUB TO ATTIC SPACE WITH PULL STRING
- 4SD J-BOX IN ATTIC FOR CEILING MOUNTED SMOKE DETECTOR (DEVICE BY OTHERS). MAXIMUM 21'-0" FROM ANY POINT IN ROOM AND 30'-0" BETWEEN THEM. PROVIDE A 6'-0" CONDUIT FROM EACH J-BOX TO SMOKE DETECTOR LOCATION. CONDUIT & CONNECTION TO CEILING DEVICE & DEVICE BY OTHERS (ALARM NOTE #1)
- 4SD J-BOX IN ATTIC FOR ATTIC MOUNTED HEAT DETECTOR (DEVICE BY OTHERS). MAXIMUM 35'-0" FROM ANY POINT IN ATTIC AND 50'-0" BETWEEN THEM. PROVIDE A 6'-0" CONDUIT FROM EACH J-BOX TO HEAT DETECTOR LOCATION. CONDUIT & CONNECTION TO CEILING DEVICE & DEVICE BY OTHERS (ALARM NOTE #1)
- 4SD J-BOX FOR WATER HEATER LOCATE ABOVE CEILING W/ COVER PLATE, HARD WIRE TO UNIT
- 100 CFM CEILING MOUNTED EXHAUST FAN. INTERLOCKED WITH LIGHT SWITCH
- 300 CFM CEILING MOUNTED EXHAUST FAN. INTERLOCKED WITH LIGHT SWITCH
- 2x4 CEILING RECESSED LIGHT, LED LIGHT FIXTURE WITH DIMMING WATTAGE: 51 WATTS (MAX), 5000L (MIN) EACH LIGHT FIXTURE WHICH IS INDICATED AS BEING AN EMERGENCY LIGHT SHALL HAVE A BALLAST BATTERY PACK INSTALLED ON THE FIXTURE. THE BATTERY PACK SHALL PROVIDE POWER TO A SINGLE LAMP WITHIN THE FIXTURE FOR NO LESS THAN 90 MINUTES. ANY LIGHT FIXTURE EQUIPPED WITH A BATTERY PACK SHALL BE WIRED IN SUCH A MANNER THAT THE BATTERY WILL BE ACTIVATED IMMEDIATELY UPON LOSS OF POWER TO THE FIXTURE. ADDITIONALLY THE BATTERY PACK SHALL BE OPERATED USING BATTERY POWER LIGHTING CONTROL SWITCHES AND SENSORS SHALL NOT BE ABLE TO SHUT THE FIXTURE OFF.
- WALL MOUNTED LIGHT FIXTURE, 30 WATTS
- 4SD J-BOX FOR FUTURE DATA W/ SINGLE GANG RING W/ 1" CO STUB INTO ATTIC AND PULL STRING
- DEDICATED CIRCUIT w/ LOCK ON DEVICE FOR FIRE SPRINKLER FLOW SWITCH.
- DEDICATED CIRCUIT w/ LOCK ON DEVICE FOR FIRE SPRINKLER TAMPER SWITCH.
- DEDICATED CIRCUIT w/ LOCK ON DEVICE FOR FIRE SPRINKLER BELL.

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR:
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
SYLVAN USD FREEDOM E.S. (2) 24' x 40' CLASSROOM BUILDINGS

SHEET TITLE:
ELECTRICAL PLAN AND SCHEDULE 24' x 40' PROJECT SPECIFIC

REVISIONS

1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

PC STATE AGENCY APPROVAL

Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

REGISTERED PROFESSIONAL ENGINEER
JOSH W. STARBUCK
STRUCTURAL
STATE OF CALIFORNIA

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO: 11478
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023

P.C. SHEET NUMBER
E-1.01N

ELECTRICAL PLAN

SCALE: 1/4" = 1'-0"

ELECTRICAL PANEL

VOLTS: 120/208 V
MAIN: 100 A
PANEL: WALL MOUNTED HVAC
LOCATION: INTERIOR ACCESS
FEED: REAR
MOUNTING: FLUSH

LOAD	QTY	WATTS		BREAKER	Circuit	WATTS		QTY	LOAD
		Aφ	Bφ			Aφ	Bφ		
RECEPTACLES	4	720		20	1	720		1	HVAC - WALL MOUNT
RECEPTACLES/CLOCK	5		900	20	1		900		
INTERIOR LIGHTING	8	960		20	1	960			
EXTERIOR LIGHTING	1		40	20	1		40		
WALL RECEPTACLE (GFI)	1	180		20	1	180			
DED - SOLAR READY									
DED - SOLAR READY									
A =	6690	WATTS / PHASE	1860	940				4830	4870
TOTAL =	12,500	WATTS	61	AMPS				3	WIRE

NOTE: PROVIDE A MINIMUM OF 72 SF SOLAR READY AREA PER MODULE. AREA TO BE A MINIMUM OF 5' IN ANY DIRECTION WITH A MINIMUM SPACE OF 80 SF PER BUILDING.

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. Additional tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports.

KEY TO COLUMNS

1 TYPE

Continuance - Indicates that a continuous special inspection is required.

Periodic - Indicates that a periodic special inspection is required.

Test - Indicates that a test is required.

2 PERFORMED BY

GE (Geotechnical Engineer) - Indicates that the special inspection shall be performed by a registered geotechnical engineer or his or her authorized representative.

CE (Civil Engineer) - Indicates that the special inspection shall be performed by a registered civil engineer or his or her authorized representative.

LE (Licensed Engineer) - Indicates that the special inspection shall be performed by a licensed engineer or his or her authorized representative.

LS (Licensed Structural Engineer) - Indicates that the special inspection shall be performed by a licensed structural engineer or his or her authorized representative.

PE (Professional Engineer) - Indicates that the special inspection shall be performed by a professional engineer or his or her authorized representative.

SI (Special Inspector) - Indicates that the special inspection shall be performed by a special inspector who is qualified in accordance with the requirements and limitations in this section.

3

Code Reference and Notes

DA 103-22 List of Required Verified Reports, CBC 2022

Application Number: [Blank]

Subcontract Number: [Blank]

DSA File Number: [Blank]

DSA Form Number: [Blank]

1. Structural Testing and Inspection Laboratory Verified Report Form DSA 291

2. Concrete Batch Plant Inspection Laboratory Verified Report Form DSA 281

3. Shop Welding Inspection Laboratory Verified Report Form DSA 281, or for independently contracting, Special Inspection Verified Report Form DSA 282

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. Additional tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports.

KEY TO COLUMNS

1 TYPE

Continuance - Indicates that a continuous special inspection is required.

Periodic - Indicates that a periodic special inspection is required.

Test - Indicates that a test is required.

2 PERFORMED BY

GE (Geotechnical Engineer) - Indicates that the special inspection shall be performed by a registered geotechnical engineer or his or her authorized representative.

CE (Civil Engineer) - Indicates that the special inspection shall be performed by a registered civil engineer or his or her authorized representative.

LE (Licensed Engineer) - Indicates that the special inspection shall be performed by a licensed engineer or his or her authorized representative.

LS (Licensed Structural Engineer) - Indicates that the special inspection shall be performed by a licensed structural engineer or his or her authorized representative.

PE (Professional Engineer) - Indicates that the special inspection shall be performed by a professional engineer or his or her authorized representative.

SI (Special Inspector) - Indicates that the special inspection shall be performed by a special inspector who is qualified in accordance with the requirements and limitations in this section.

3

Code Reference and Notes

DA 103-22 List of Required Verified Reports, CBC 2022

Application Number: [Blank]

Subcontract Number: [Blank]

DSA File Number: [Blank]

DSA Form Number: [Blank]

1. Structural Testing and Inspection Laboratory Verified Report Form DSA 291

2. Concrete Batch Plant Inspection Laboratory Verified Report Form DSA 281

3. Shop Welding Inspection Laboratory Verified Report Form DSA 281, or for independently contracting, Special Inspection Verified Report Form DSA 282

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. Additional tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports.

KEY TO COLUMNS

1 TYPE

Continuance - Indicates that a continuous special inspection is required.

Periodic - Indicates that a periodic special inspection is required.

Test - Indicates that a test is required.

2 PERFORMED BY

GE (Geotechnical Engineer) - Indicates that the special inspection shall be performed by a registered geotechnical engineer or his or her authorized representative.

CE (Civil Engineer) - Indicates that the special inspection shall be performed by a registered civil engineer or his or her authorized representative.

LE (Licensed Engineer) - Indicates that the special inspection shall be performed by a licensed engineer or his or her authorized representative.

LS (Licensed Structural Engineer) - Indicates that the special inspection shall be performed by a licensed structural engineer or his or her authorized representative.

PE (Professional Engineer) - Indicates that the special inspection shall be performed by a professional engineer or his or her authorized representative.

SI (Special Inspector) - Indicates that the special inspection shall be performed by a special inspector who is qualified in accordance with the requirements and limitations in this section.

3

Code Reference and Notes

DA 103-22 List of Required Verified Reports, CBC 2022

Application Number: [Blank]

Subcontract Number: [Blank]

DSA File Number: [Blank]

DSA Form Number: [Blank]

1. Structural Testing and Inspection Laboratory Verified Report Form DSA 291

2. Concrete Batch Plant Inspection Laboratory Verified Report Form DSA 281

3. Shop Welding Inspection Laboratory Verified Report Form DSA 281, or for independently contracting, Special Inspection Verified Report Form DSA 282

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. Additional tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports.

KEY TO COLUMNS

1 TYPE

Continuance - Indicates that a continuous special inspection is required.

Periodic - Indicates that a periodic special inspection is required.

Test - Indicates that a test is required.

2 PERFORMED BY

GE (Geotechnical Engineer) - Indicates that the special inspection shall be performed by a registered geotechnical engineer or his or her authorized representative.

CE (Civil Engineer) - Indicates that the special inspection shall be performed by a registered civil engineer or his or her authorized representative.

LE (Licensed Engineer) - Indicates that the special inspection shall be performed by a licensed engineer or his or her authorized representative.

LS (Licensed Structural Engineer) - Indicates that the special inspection shall be performed by a licensed structural engineer or his or her authorized representative.

PE (Professional Engineer) - Indicates that the special inspection shall be performed by a professional engineer or his or her authorized representative.

SI (Special Inspector) - Indicates that the special inspection shall be performed by a special inspector who is qualified in accordance with the requirements and limitations in this section.

3

Code Reference and Notes

DA 103-22 List of Required Verified Reports, CBC 2022

Application Number: [Blank]

Subcontract Number: [Blank]

DSA File Number: [Blank]

DSA Form Number: [Blank]

1. Structural Testing and Inspection Laboratory Verified Report Form DSA 291

2. Concrete Batch Plant Inspection Laboratory Verified Report Form DSA 281

3. Shop Welding Inspection Laboratory Verified Report Form DSA 281, or for independently contracting, Special Inspection Verified Report Form DSA 282

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. Additional tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports.

KEY TO COLUMNS

1 TYPE

Continuance - Indicates that a continuous special inspection is required.

Periodic - Indicates that a periodic special inspection is required.

Test - Indicates that a test is required.

2 PERFORMED BY

GE (Geotechnical Engineer) - Indicates that the special inspection shall be performed by a registered geotechnical engineer or his or her authorized representative.

CE (Civil Engineer) - Indicates that the special inspection shall be performed by a registered civil engineer or his or her authorized representative.

LE (Licensed Engineer) - Indicates that the special inspection shall be performed by a licensed engineer or his or her authorized representative.

LS (Licensed Structural Engineer) - Indicates that the special inspection shall be performed by a licensed structural engineer or his or her authorized representative.

PE (Professional Engineer) - Indicates that the special inspection shall be performed by a professional engineer or his or her authorized representative.

SI (Special Inspector) - Indicates that the special inspection shall be performed by a special inspector who is qualified in accordance with the requirements and limitations in this section.

3

Code Reference and Notes

DA 103-22 List of Required Verified Reports, CBC 2022

Application Number: [Blank]

Subcontract Number: [Blank]

DSA File Number: [Blank]

DSA Form Number: [Blank]

1. Structural Testing and Inspection Laboratory Verified Report Form DSA 291

2. Concrete Batch Plant Inspection Laboratory Verified Report Form DSA 281

3. Shop Welding Inspection Laboratory Verified Report Form DSA 281, or for independently contracting, Special Inspection Verified Report Form DSA 282

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. Additional tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports. The project inspector is responsible for providing the Geotechnical Engineer of Record with the test results and special inspection reports.

KEY TO COLUMNS

1 TYPE

Continuance - Indicates that a continuous special inspection is required.

Periodic - Indicates that a periodic special inspection is required.

Test - Indicates that a test is required.

2 PERFORMED BY

GE (Geotechnical Engineer) - Indicates that the special inspection shall be performed by a registered geotechnical engineer or his or her authorized representative.

CE (Civil Engineer) - Indicates that the special inspection shall be performed by a registered civil engineer or his or her authorized representative.

LE (Licensed Engineer) - Indicates that the special inspection shall be performed by a licensed engineer or his or her authorized representative.

LS (Licensed Structural Engineer) - Indicates that the special inspection shall be performed by a licensed structural engineer or his or her authorized representative.

PE (Professional Engineer) - Indicates that the special inspection shall be performed by a professional engineer or his or her authorized representative.

SI (Special Inspector) - Indicates that the special inspection shall be performed by a special inspector who is qualified in accordance with the requirements and limitations in this section.

3

Code Reference and Notes

DA 103-22 List of Required Verified Reports, CBC 2022

Application Number: [Blank]

Subcontract Number: [Blank]

DSA File Number: [Blank]

DSA Form Number: [Blank]

1. Structural Testing and Inspection Laboratory Verified Report Form DSA 291

2. Concrete Batch Plant Inspection Laboratory Verified Report Form DSA 281

3. Shop Welding Inspection Laboratory Verified Report Form DSA 281, or for independently contracting, Special Inspection Verified Report Form DSA 282

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT

APP: 02-12160 INC:
REVIEWED FOR:
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM) INC AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM INC.

ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM INC SHALL BE THE PROPERTY OF SCM INC

PROJECT NAME: **SILVAN USD FREEDOM E.S. (2) 24' x 40' CLASSROOM BUILDINGS**

SHEET TITLE: **T & I FORMS**

REVISIONS

PRE-CHECK (PC) DOCUMENT CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT

APP: 04-121999 INC:
REVIEWED FOR:
DATE: 08/31/2023

PC STATE AGENCY APPROVAL

Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023

P.C. SHEET NUMBER

A-0A

The example form DSA 103 sections shown on this sheet are for illustration purposes only. A form DSA 103 is to be completed for each application that this PC is being incorporated into and the example sections shown on this drawing are to be crossed out.

- UT TESTING SHALL BE PERFORMED ON 100% OF CJP GROOVE WELDS COLUMN SPLICES OR BEAM SPLICES WHERE THE MATERIAL THICKNESS BEING WELDED IS 5/16" OR GREATER.
- UT TEST SHALL NOT BE REQUIRED TO BE PERFORMED ON CJP GROOVE WELDS WHERE THE MATERIAL THICKNESS BEING WELDED IS 1/4" OR LESS.
- MAGNETIC PARTICLE TESTING SHALL BE PERFORMED ON 25% OF ALL BEAM TO COLUMN OR TRUSS CHORD TO COLUMN CJP GROOVE WELDS.

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record, Laboratory of Record, or Special Inspector. The actual complete test and inspection program must be performed as detailed on the DSA approved documents. The appendix at the bottom of this form identifies work NOT subject to DSA requirements for special inspection or structural testing. The project inspector is responsible for providing inspection of all fields of construction, including but not limited to, special inspections not listed on this form such as structural wood framing, high-load wood diaphragms, cold-formed steel framing, anchorage of non-structural components, etc. per Title 24, Part 2, Chapter 17A (2022 CBC).

****NOTE:** Underlined section and table references found in this document are from the CBC, or California Building Code.

KEY TO COLUMNS	1. TYPE	2. PERFORMED BY	Code Reference and Notes
Continuum - Indicates that a continuous special inspection is required.		SE (Structural Engineer) - Indicates that the special inspection shall be performed by a registered professional engineer or his or her authorized representative.	
Periodic - Indicates that a periodic special inspection is required.		LR (Laboratory of Record) - Indicates that the test or special inspection shall be performed by a laboratory registered in the State of California and approved by the Department of Industrial Relations (DIR) under the provisions of the Labor Code, Chapter 350, Section 4355.	
Test - Indicates that a test is required.		SI (Special Inspector) - Indicates that the special inspection may be performed by a registered professional engineer or his or her authorized representative, or by a Special Inspector who is specifically approved by DSA.	
		SI (Special Inspector) - Indicates that the special inspection shall be performed by an appropriately qualified/registered special inspector.	

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record, Laboratory of Record, or Special Inspector. The actual complete test and inspection program must be performed as detailed on the DSA approved documents. The appendix at the bottom of this form identifies work NOT subject to DSA requirements for special inspection or structural testing. The project inspector is responsible for providing inspection of all fields of construction, including but not limited to, special inspections not listed on this form such as structural wood framing, high-load wood diaphragms, cold-formed steel framing, anchorage of non-structural components, etc. per Title 24, Part 2, Chapter 17A (2022 CBC).

****NOTE:** Underlined section and table references found in this document are from the CBC, or California Building Code.

KEY TO COLUMNS	1. TYPE	2. PERFORMED BY	Code Reference and Notes
Continuum - Indicates that a continuous special inspection is required.		SE (Structural Engineer) - Indicates that the special inspection shall be performed by a registered professional engineer or his or her authorized representative.	
Periodic - Indicates that a periodic special inspection is required.		LR (Laboratory of Record) - Indicates that the test or special inspection shall be performed by a laboratory registered in the State of California and approved by the Department of Industrial Relations (DIR) under the provisions of the Labor Code, Chapter 350, Section 4355.	
Test - Indicates that a test is required.		SI (Special Inspector) - Indicates that the special inspection may be performed by a registered professional engineer or his or her authorized representative, or by a Special Inspector who is specifically approved by DSA.	
		SI (Special Inspector) - Indicates that the special inspection shall be performed by an appropriately qualified/registered special inspector.	

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record, Laboratory of Record, or Special Inspector. The actual complete test and inspection program must be performed as detailed on the DSA approved documents. The appendix at the bottom of this form identifies work NOT subject to DSA requirements for special inspection or structural testing. The project inspector is responsible for providing inspection of all fields of construction, including but not limited to, special inspections not listed on this form such as structural wood framing, high-load wood diaphragms, cold-formed steel framing, anchorage of non-structural components, etc. per Title 24, Part 2, Chapter 17A (2022 CBC).

****NOTE:** Underlined section and table references found in this document are from the CBC, or California Building Code.

KEY TO COLUMNS	1. TYPE	2. PERFORMED BY	Code Reference and Notes
Continuum - Indicates that a continuous special inspection is required.		SE (Structural Engineer) - Indicates that the special inspection shall be performed by a registered professional engineer or his or her authorized representative.	
Periodic - Indicates that a periodic special inspection is required.		LR (Laboratory of Record) - Indicates that the test or special inspection shall be performed by a laboratory registered in the State of California and approved by the Department of Industrial Relations (DIR) under the provisions of the Labor Code, Chapter 350, Section 4355.	
Test - Indicates that a test is required.		SI (Special Inspector) - Indicates that the special inspection may be performed by a registered professional engineer or his or her authorized representative, or by a Special Inspector who is specifically approved by DSA.	
		SI (Special Inspector) - Indicates that the special inspection shall be performed by an appropriately qualified/registered special inspector.	

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record, Laboratory of Record, or Special Inspector. The actual complete test and inspection program must be performed as detailed on the DSA approved documents. The appendix at the bottom of this form identifies work NOT subject to DSA requirements for special inspection or structural testing. The project inspector is responsible for providing inspection of all fields of construction, including but not limited to, special inspections not listed on this form such as structural wood framing, high-load wood diaphragms, cold-formed steel framing, anchorage of non-structural components, etc. per Title 24, Part 2, Chapter 17A (2022 CBC).

****NOTE:** Underlined section and table references found in this document are from the CBC, or California Building Code.


KEY TO COLUMNS	1. TYPE	2. PERFORMED BY	Code Reference and Notes
Continuum - Indicates that a continuous special inspection is required.		SE (Structural Engineer) - Indicates that the special inspection shall be performed by a registered professional engineer or his or her authorized representative.	
Periodic - Indicates that a periodic special inspection is required.		LR (Laboratory of Record) - Indicates that the test or special inspection shall be performed by a laboratory registered in the State of California and approved by the Department of Industrial Relations (DIR) under the provisions of the Labor Code, Chapter 350, Section 4355.	
Test - Indicates that a test is required.		SI (Special Inspector) - Indicates that the special inspection may be performed by a registered professional engineer or his or her authorized representative, or by a Special Inspector who is specifically approved by DSA.	
		SI (Special Inspector) - Indicates that the special inspection shall be performed by an appropriately qualified/registered special inspector.	

2022 CBC

IMPORTANT: This form is only a summary list of structural tests and some of the special inspections required for the project. Generally, the structural tests and special inspections noted on this form are those that will be performed by the Geotechnical Engineer of Record, Laboratory of Record, or Special Inspector. The actual complete test and inspection program must be performed as detailed on the DSA approved documents. The appendix at the bottom of this form identifies work NOT subject to DSA requirements for special inspection or structural testing. The project inspector is responsible for providing inspection of all fields of construction, including but not limited to, special inspections not listed on this form such as structural wood framing, high-load wood diaphragms, cold-formed steel framing, anchorage of non-structural components, etc. per Title 24, Part 2, Chapter 17A (2022 CBC).

****NOTE:** Underlined section and table references found in this document are from the CBC, or California Building Code.

KEY TO COLUMNS	1. TYPE	2. PERFORMED BY	Code Reference and Notes
Continuum - Indicates that a continuous special inspection is required.		SE (Structural Engineer) - Indicates that the special inspection shall be performed by a registered professional engineer or his or her authorized representative.	
Periodic - Indicates that a periodic special inspection is required.		LR (Laboratory of Record) - Indicates that the test or special inspection shall be performed by a laboratory registered in the State of California and approved by the Department of Industrial Relations (DIR) under the provisions of the Labor Code, Chapter 350, Section 4355.	
Test - Indicates that a test is required.		SI (Special Inspector) - Indicates that the special inspection may be performed by a registered professional engineer or his or her authorized representative, or by a Special Inspector who is specifically approved by DSA.	
		SI (Special Inspector) - Indicates that the special inspection shall be performed by an appropriately qualified/registered special inspector.	



PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM INC) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM INC.

ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM INC SHALL BE THE PROPERTY OF SCM INC.

PROJECT NAME:

**SILVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**


SHEET TITLE:

T & I FORMS

REVISIONS

NO.	DESCRIPTION
1	
2	
3	
4	

PRE-CHECK (PC) DOCUMENT CODE: 2022 CBC A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED



PC STATE AGENCY APPROVAL



MODULAR BUILDING DESIGN PROFESSIONAL



SILVER CREEK INDUSTRIES 24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER

A-0B

RELO CONCRETE FOUNDATION

4

RELO WOOD FOUNDATION

3

GENERAL 103-22 NOTES

2

PERMANENT WOOD / CONC. FLRS - CONC. FOUNDATION

1

PERMANENT WOOD / CONC. FLRS - CONC. FOUNDATION

1

PERMANENT WOOD / CONC. FLRS - CONC. FOUNDATION

1

The example form DSA 103 sections shown on this sheet are for illustration purposes only. A form DSA 103 is to be completed for each application that this PC is being incorporated into and the example sections shown on this drawing are to be crossed out.

- UT TESTING SHALL BE PERFORMED ON 100% OF CJP GROOVE WELDS COLUMN SPLICES OR BEAM SPLICES WHERE THE MATERIAL THICKNESS BEING WELDED IS 5/16" OR GREATER.
- UT TEST SHALL NOT BE REQUIRED TO BE PERFORMED ON CJP GROOVE WELDS WHERE THE MATERIAL THICKNESS BEING WELDED IS 1/4" OR LESS.
- MAGNETIC PARTICLE TESTING SHALL BE PERFORMED ON 25% OF ALL BEAM TO COLUMN OR TRUSS CHORD TO COLUMN CJP GROOVE WELDS.

REFLECTED CEILING NOTES

1. CEILING SYSTEM GENERAL NOTES

- 1.01 Ceiling system components shall comply with ASTM C635 and Section 5.1 of ASTM E580.
1.02 The ceiling grid system must be rated heavy duty as defined by ASTM C635.
1.03 Ceiling systems: The following ceiling system(s) is/are part of the scope of this project:

Manufacturer: Armstrong ICC ESR-1308
Main Runner Part, Model, or Catalog Number: 7321 XL7328
Cross Runner Part, Model, or Catalog Number:

1.04 Seismic Wall Clip:

Manufacturer's Model: BERCE-2

- 1.05 Ceiling panels shall not support any luminaires, air terminals or devices.
1.06 For ceiling installations utilizing acoustic tile panels of mineral or glass fiber, it is not mandatory to provide 1/2" clearance between the acoustic tile panels and the wall on the sides of the ceiling which are free to slip. For all other ceiling panel types, provide 1/2" clearance between the ceiling panel and the wall on the sides of the ceiling free to slip. Clearance between ceiling grid runners/members and walls shall comply with the details on these drawings regardless of ceiling tile material.

2. MATERIALS

- 2.01 Ceiling wire shall be Class 1 zinc coated (galvanized) carbon steel conforming to ASTM A641. Wire shall be #12 gauge (0.106" diameter) with soft temper and minimum ultimate tensile strength = 70 ksi.
2.02 Galvanized sheet steel (including that used for metal stud and track compression struts/post) shall conform to ASTM A653, or other equivalent sheet steel listed in Section A3.1 of the North American Specification for the Design of Cold-Formed Steel Structural Members, (AISI S100). Material 43 mil (18 gauge) and lighter shall have minimum yield strength of 33 ksi. Material 54 mil (16 gauge) and heavier shall have a minimum yield strength of 50ksi.
2.03 Electrical metallic tube (EMT) shall be ANSI C80.3/UL 797 carbon steel with G90 galvanizing. EMT shall have minimum yield strength (FY) of 30 ksi and minimum ultimate strength (FU) of 46 ksi.

3. ATTACHMENT OF HANGER AND BRACING WIRES

- 3.01 Separate all ceiling hanger and bracing wires at least 6 inches from all unbraced ducts, pipes, conduit, etc.
3.02 Hanger and bracing wires shall not attach to or bend around obstructions including but not limited to piping, ductwork, conduit and equipment.
3.03 Hanger wires that are more than one (horizontal) in six (vertical) out of plumb shall have counter-sloping wires.
3.04 Slack safety wires shall be considered hanger wires for installation and testing requirements.
3.05 Hanger and bracing wire anchorage to the structure shall be installed in such a manner that the direction of the anchorage aligns closely with the direction of the wire (e.g., bracing wire ceiling clips must be bent as shown in the details and rotated as required to align closely with the direction of the wire, screw eyes in wood must be installed so they align closely with the direction of the wire, etc.).

4. FASTENERS AND WELDING

- 4.01 Sheet metal screws shall comply with ASTM C1513 and ASME B18.6.3. Penetration of screws through joined material shall not be less than three times the diameter.
4.02 Expansion anchors shall be: [RDP to indicate manufacturer, product, evaluation report number and test load for each size specified per CBC 1910A.5.4.]
4.03 Power-Activated Fasteners shall be: [RDP to indicate manufacturer, product, evaluation report number.]
4.04 If not otherwise specified in the evaluation report, power-actuated fasteners installed in steel shall be installed so the entire pointed end of the fastener is driven through the steel member
4.05 Power-actuated fasteners in concrete or masonry are not permitted for bracing wires.
4.06 Concrete reinforcement and prestressing tendons shall be located by non-destructive means prior to installing post-installed anchors.
4.07 Welding shall be in accordance with AWS D1.3 using E60XX series electrodes.

5. TESTING

- 5.01 All field testing must be performed in the presence of the project inspector.
5.02 Post-installed anchors in concrete used to support hanger wires shall be tested at a frequency of 10 percent. Power-actuated fasteners in concrete shall be field tested for 200 pounds in tension. All other post-installed anchors in concrete shall be tested in accordance with CBC Section 1910A.5.
5.03 Post-installed anchors in concrete used to attach bracing wires shall be tested at a frequency of 50 percent in accordance with CBC Section 1910A.5.

6. LUMINAIRES

- 6.01 All luminaires shall be positively attached to the ceiling suspension systems by mechanical means to resist a horizontal force equal to the weight of the luminaire. A minimum of two screws or approved fasteners are required at each luminaire, per ASTM E580 Section 5.3.1.
6.02 Surface-mounted luminaires shall be attached to the main runner with at least two positive clamping devices. The clamping device shall completely surround the supporting ceiling runner and be made of steel with a minimum thickness of #14 gauge. Rotational spring catches do not count. A #12 gauge slack safety wire shall be connected from each clamping device to the structure above. Provide additional supports when a luminaire is 8 feet or longer or exceeds 56 pounds. Maximum spacing between supports shall not exceed 8 feet.
6.03 Luminaires weighing less than or equal to 10 pounds may be supported directly on the ceiling runners, shall have a minimum of one #12 gauge slack safety wire connected from the fixture housing to the structure above.
6.04 Luminaires weighing greater than 10 pounds but less than or equal to 56 pounds may be supported directly on the ceiling runners, but they shall have a minimum of two #12 gauge slack safety wires connected from the fixture housing at diagonal corners to the structure above.
Exception: All luminaires greater than two by four feet weighing less than 56 pounds shall have a #12 gauge slack safety wire in each corner.
6.05 All luminaires weighing greater than 56 pounds shall be independently supported by not less than four #12 gauge hanger wires (one at each corner) attached from the fixture housing to the structure above or other approved hangers. The four #12 gauge wires or other approved hangers, including their attachment to the structure above, shall be capable of supporting four times the weight of the fixture.

7. SERVICES WITHIN THE CEILING


- 7.01 All flexible sprinkler hose fitting mounting brackets, ceiling-mounted air terminals or other services shall be positively attached to the ceiling suspension systems by mechanical means. Screws or approved fasteners are required. A minimum of two attachments are required at each component.
7.02 Ceiling-mounted air terminals or other services weighing less than or equal to 20 pounds shall have one #12 gauge slack safety wire attached from the terminal or service to the structure above.
7.03 Flexible sprinkler hose fittings, ceiling-mounted air terminals or other services weighing more than 20 pounds but less than or equal to 56 pounds shall have two #12 gauge slack safety wires (at diagonal corners) connected from the terminal or service to the structure above.
7.04 Flexible sprinkler hose fittings, ceiling-mounted air terminals or other services weighing more than 56 pounds shall be supported directly from the structure above by not less than four #12 gauge hanger wires attached from the terminal or service to the structure above or other approved hangers.

8. OTHER DEVICES WITHIN THE CEILING


- 8.01 All lightweight miscellaneous devices, such as strobe lights, occupancy sensors, speakers, exit signs, etc., shall be attached to the ceiling grid. In addition, devices weighing more than 10 pounds shall have a #12 gauge slack safety wire anchored to the structure above. Devices weighing more than 20 pounds shall be supported independently from the structure above.

NOTE: ACOUSTICAL PANELS SHALL BE 5/8" MINIMUM THICK, MINERAL FIBERBOARD OR VINYL FACED FIBERGLASS LAY-IN PANELS SQUARE EDGE AND CBC CLASS C FLAME-SPREAD 76-200; SMOKE-DEVELOPED 0-450.


NOTE: PER CBC SECTION 718.2.1. FIRE BLOCKS MAY BE OF GYPSUM BOARD, CEMENT FIBER BOARD, BATTS OR MINERAL OR GLASS FIBER, OR OTHER APPROVED MATERIALS INSTALLED IN SUCH A MANNER AS TO BE SECURELY RETAINED IN PLACE. LOOSE-FILL INSULATION MATERIAL SHALL NOT BE USED AS A FIRE BLOCK UNLESS SPECIFICALLY TESTED IN THE FORM AND MANNER INTENDED FOR USE TO DEMONSTRATE ITS ABILITY TO REMAIN IN PLACE AND TO RETARD THE SPREAD OF FIRE AND HOT GASES. (SECTION 718.2.1). FLAME SPREAD - 25 SMOKE DEVELOPMENT - 50 MAX FIRE BLOCKING IS NOT REQUIRED WITHIN CONCEALED SPACES CONSTRUCTED OF NON-COMBUSTIBLE MATERIALS



NOTE: ALL SIGN EDGES SHALL BE EASED OR ROUNDED 1/16" (MIN) OR CHAMFERED 1/8" (MAX)



MOUNTING HEIGHT NOTE: 48" MIN AFF TO BASELINE OF LOWEST BRAILLE 60" MAX AFF TO BASELINE OF HIGHEST RAISED CHARACTER





NOTE: TACTILE SIGNS TO BE PROVIDED AND INSTALLED ON SITE BY OTHERS, NOT SCM. AND SHALL COMPLY W/ CBC 1013.4

SIGNAGE NOTES

- 1. CHARACTER TYPE: CHARACTERS ON TACTILE SIGNS SHALL BE RAISED 1/32" (0.794 mm) MINIMUM ABOVE THEIR BACKGROUND AND SHALL BE SANS SERIF UPPERCASE CHARACTERS ACCOMPANIED BY GRADE 2 BRAILLE. (SEE NOTE 5 BELOW) 11B-703.2.1 & 11B-703.2.2 & 11B-703.2.3.
2. RAISED CHARACTER HEIGHT: CHARACTER HEIGHT MEASURED VERTICALLY FROM THE BASELINE OF THE CHARACTER SHALL BE 5/8" (15.9 mm) MINIMUM AND 2 INCH (51 mm) MAXIMUM BASED ON THE HEIGHT OF THE UPPERCASE LETTER "T". 11B-703.2.5
3. FINISH AND CONTRAST: SYMBOLS OF ACCESSIBILITY AND THEIR BACKGROUND SHALL HAVE A NON-GLARE FINISH SYMBOLS. SYMBOLS OF ACCESSIBILITY SHALL CONTRAST WITH THEIR BACKGROUND WITH EITHER A LIGHT SYMBOL ON A DARK BACKGROUND OR A DARK SYMBOL ON A LIGHT BACKGROUND. 11B-703.7.1.
4. PROPORTIONS: RAISED CHARACTERS ON SIGNS SHALL BE SELECTED FROM FONTS WHERE THE WIDTH OF THE UPPERCASE LETTER "O" IS 60% MIN AND 110% MAX OF THE HEIGHT OF THE UPPERCASE LETTER "I". STROKE THICKNESS OF THE UPPERCASE "I" SHALL BE 15% MAX OF THE HEIGHT OF THE CHARACTER. 11B-703.2.4 + 11B-703.2.6
VISUAL CHARACTERS ON SIGNS SHALL BE SELECTED FROM FONTS WHERE THE WIDTH OF THE UPPERCASE LETTER "O" IS 60% MIN AND 110% MAX OF THE HEIGHT OF THE UPPERCASE LETTER "I". STROKE THICKNESS OF THE UPPER CASE "I" SHALL BE 10% MIN. AND 20% MAX OF THE HEIGHT OF THE CHARACTER.
TEMPLATE FOR CHECKING CHARACTER AND STROKE WIDTH TO HEIGHT PROPORTIONS:
TACTILE - VISUAL CHARACTER WIDTH: 1.1:1 (110%), 3.5 (60%)
TACTILE STROKE WIDTH: 3:20 (15%), 1.5 (20%), 1:10 (10%)
VISUAL STROKE WIDTH
5. CHARACTER SPACING: CHARACTER SPACING SHALL BE MEASURED BETWEEN THE TWO CLOSEST POINTS OF ADJACENT RAISED CHARACTERS WITHIN A MESSAGE, EXCLUDING WORD SPACES. WHERE CHARACTERS HAVE RECTANGULAR CROSS SECTIONS, SPACING BETWEEN INDIVIDUAL RAISED CHARACTERS SHALL BE 1/8" (MIN) AND 4 TIMES THE RAISED CHARACTER STROKE WIDTH (MAX), WHERE CHARACTERS HAVE OTHER CROSS SECTIONS, SPACING BETWEEN INDIVIDUAL RAISED CHARACTERS SHALL BE 1/16" (MIN) AND 4 TIMES THE RAISED CHARACTER STROKE WIDTH (MAX) AT THE BASE OF THE CROSS SECTIONS, AND 1/8" (MIN) AND 4 TIMES THE RAISED CHARACTER STROKE WIDTH (MAX) AT THE TOP OF THE CROSS SECTIONS. CHARACTERS SHALL BE SEPARATED FROM RAISED BORDERS AND DECORATIVE ELEMENTS 3/8" (MIN). 11B-703.2.7
6. LINE SPACING: SPACING BETWEEN THE BASELINES OF SEPARATE LINES OF RAISED CHARACTERS WITHIN A MESSAGE SHALL BE 135% (MIN) AND 170% (MAX) OF THE RAISED CHARACTER HEIGHT. 11B-703.2.8
7. BRAILLE: BRAILLE SHALL BE CONTRACTED (GRADE 2) AND SHALL COMPLY WITH SECTIONS 11B-703.3 AND 11B-703.4. DIMENSIONS AND CAPITALIZATION: BRAILLE DOTS SHALL HAVE A DOMED OR ROUNDED SHAPE AND SHALL COMPLY WITH TABLE 11B-703.3.1. THE INDICATION OF AN UPPERCASE LETTER OR LETTERS SHALL ONLY BE USED BEFORE THE FIRST WORD OF SENTENCES, PROPER NOUNS, INDIVIDUAL LETTERS OF THE ALPHABET, INITIALS, AND ACRONYMS. 11B-703.3.1.

Table with 2 columns: MEASUREMENT RANGE and MINIMUM IN INCHES MAXIMUM IN INCHES. Rows include dot base diameter, distance between two dots, distance between adjacent cells, dot height, and distance between corresponding dots.




NOTE: SIGN MATERIAL TO BE 1/8" THK. E.S. PLASTIC W/1/32" RAISED GRAPHICS AND LETTERS. PROVIDE MECHANICAL MOUNTING W/ VANDAL RESISTANT FASTENERS. CBC SECTION 11B-703. WHERE RAISED BORDERS OCCUR, PROVIDE 1/2" MIN. CLEARANCE BETWEEN TOP OF BOARDER AND LOWEST LEVEL OF BRAILLE TEXT.

A ROOM IDENTIFICATION ROOM SIGNAGE (BY DISTRICT) FOR SITE SPECIFIC LOCATIONS ARCHITECT TO PROVIDE BUILDING / ROOM IDENTIFICATION SIGNS. DETAILS AND LOCATIONS OF SIGNAGE TO BE INDICATED. COORDINATE WITH SIGNAGE NOTES 1 THROUGH 7 ON THIS SHEET.

THIS DETAIL FOR REFERENCE ONLY

SYMBOLS LEGEND



ABBREVIATIONS

Table listing abbreviations for various materials and construction terms such as ABS, ABSOLUTE, ABOVE, ACCESS, ADDL, ADJ, AFF, etc.

SPECIFICATIONS

- DIVISION 5 - METALS
• ALL WELDED JOINTS AND SURFACES SHALL BE GROUNDED SMOOTH, NO SHARP OR ABRASIVES CORNERS. EDGES OR SURFACES. WALL SURFACES ADJACENT TO HANDRILLS SHALL BE SMOOTH,
• ALL HANDRILLS SHALL BE ROUND OR SHALL HAVE RADIUSSED EDGES (R = 1/8" MIN)
DIVISION 6 - WOOD AND PLASTICS
• ALL CABINET AND DRAWERS WILL HAVE U-SHAPED WIRE PULLS
DIVISION 9 - FINISHES
• CEILING INSTALLATION SHALL BE PER THE NOTES PROVIDED ON THIS SHEET.
DIVISION 10 - SPECIALITIES
• ALL TOILET ACCESSORIES SHALL BE INSTALLED AT THE HEIGHT AND CLEARANCES SHOWN ON SHEET P-1.01
DIVISION 22 - PLUMBING
• FAUCETS SHALL BE LEVER OPERATED (4" MIN BLADE) OR SHALL BE PUSH TYPE OR AUTOMATIC ELECTRONICALLY CONTROLLED. CONTROLS TO BE OPERABLE WITH ONE HAND AND SHALL NOT REQUIRE TIGHT GRASPING, PINCHING OR TWISTING OF THE WRIST TO OPERATE.
• FORCE TO ACTIVATE CONTROLS SHALL NOT BE GREATER THAN 5 LBS
• FORCE TO REMAIN OPEN FOR A MINIMUM OF 10 SECONDS WHEN SELF CLOSING VALVES ARE USED
• PIPE COVERS SHALL BE PROVIDED FOR WATER LINES AND DRAIN PIPES UNDER ACCESSIBLE SINKS AND LAVATORIES
• ACCESSIBLE SINKS SHALL NOT BE DEEPER THAN 6 1/2"

ASSISTIVE LISTENING SYSTEM



NOTES:
1. ASSISTIVE-LISTENING SYSTEM SHALL BE PROVIDED IN ACCORDANCE WITH CBC SECTIONS 11B-216.10 AND 11B-219 AND SHALL COMPLY WITH CBC SECTION 11B-706.
2. THE MINIMUM NUMBER OF RECEIVERS TO BE PROVIDED SHALL BE EQUAL TO 4% OF THE TOTAL NUMBER OF SEATS, BUT IN NO CASE LESS THAN TWO. 25% (MIN) OF RECEIVERS PROVIDED, BUT NO FEWER THAN TWO, SHALL BE HEARING AID COMPATIBLE IN ACCORDANCE WITH CBC SECTION 11B-706.3
3. SIGNAGE SHALL BE POSTED IN A PROMINENT PLACE INDICATING THE AVAILABILITY OF ASSISTIVE LISTENING DEVICES.
4. OWNER/SCHOOL DISTRICT SHALL PROVIDE A PERMANENT OR PORTABLE ASSISTIVE LISTENING SYSTEM.

ASSISTIVE LISTENING SYSTEM SIGN (SYMBOL PROPORTIONS SHALL MATCH CBC FIGURE 11B-703.7.2.4)

IDENTIFICATION STAMP DIV. OF THE STATE ARCHITECT APP: 02-122160 INC: REVIEWED FOR DATE: 2/27/2024. PROJECT SPECIFIC STATE AGENCY APPROVAL. THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM INC) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM INC. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM INC SHALL BE THE PROPERTY OF SCM INC. PROJECT NAME: SYLVAN USD FREEDOM E.S. (2) 24' x 40' CLASSROOM BUILDINGS. SHEET TITLE: SYMBOLS LEGEND, ABBREVIATIONS & ADA SIGNAGE. REVISIONS. PRE-CHECK (PC) DOCUMENT CODE: 2022 CBC A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED. IDENTIFICATION STAMP DIV. OF THE STATE ARCHITECT APP: 04-121999 INC: REVIEWED FOR DATE: 08/31/2023. PC STATE AGENCY APPROVAL.

Silver Creek logo with address: 2830 BARRETT AVE PERRIS, CALIFORNIA 92571 PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

REGISTERED PROFESSIONAL ENGINEER JOHN W. STARBUCK ARCHITECTURAL ENGINEER OF CALIFORNIA

SILVER CREEK INDUSTRIES 24' x 40' PC PROJECT NO: DRAWN BY: SCALE: AS NOTED DATE: 02-27-2023 P.C. SHEET NUMBER: A-0.1

WILDLAND URBAN INTERFACE REQUIREMENTS

WHEN THIS BUILDING IS TO BE INSTALLED WHERE THE REQUIREMENTS OF CHAPTER 7A OF THE 2022 CBC ARE APPLICABLE COMPLIANCE WITH THE APPLICABLE REQUIREMENTS SHALL BE AS OUTLINED BELOW.

CHAPTER 7A REQUIREMENTS:

705A ROOFING
705A.1 - ROOF SHALL BE CLASS "A".
705A.2 - NOT APPLICABLE. NO VOIDS OCCUR, ROOF IS APPLIED DIRECTLY.
705A.3 - NOT APPLICABLE. NO VALLEYS OCCUR.
705A.4 - LEAF GUARDS/COVERS SHALL BE PROVIDED AT ALL GUTTERS.

706A VENTS
706A.2 - THE UNDER-FLOOR ACCESS AND VENT OPENINGS SHALL BE COVERED WITH CORROSION RESISTANT WIRE MESH WITH A CLEAR OPENING NOT EXCEEDING 1/8".
706A.3 - THE SOFFIT VENTS SHALL BE VULCAN TECHNOLOGIES MODEL #VF OR VSC SOFFIT VENT COVERS (PER CASFM LISTING 8165-2192-0100).

707A EXTERIOR COVERINGS
707A.3 - EXTERIOR WALL FINISH SHALL BE PLASTER (NON-COMBUSTIBLE) OVER 1/2" OSB OVER STUDS OR 19/32" DURATEMP SIDING OVER STUDS (PER SFM LISTING# 8140-2031-0004).
707A.4 - NOT APPLICABLE. NO OPEN ROOF EAVES OCCUR.
707A.5 - SOFFIT FINISH SHALL BE PLASTER (NON-COMBUSTIBLE) OVER FRAMING OR ADURA FIBER-CEMENT PANELS (NON-COMBUSTIBLE) (PER ESR-1688).
707A.6 - NOT APPLICABLE. DOES NOT OCCUR.
707A.7 - NOT APPLICABLE. DOES NOT OCCUR.
707A.8 - NOT APPLICABLE. DOES NOT OCCUR.
707A.9 - NOT APPLICABLE. DOES NOT OCCUR.

708A EXTERIOR DOORS AND WINDOWS
708A.2 - NOT APPLICABLE. DOES NOT OCCUR.
708A.3 - EXTERIOR DOORS AND FRAMES ARE NON-COMBUSTIBLE (HOLLOW METAL).
708A.4 - NOT APPLICABLE.

709A DECKING - THE EXTERIOR DECKING (WHERE APPLICABLE) IS A NON-COMBUSTIBLE STEEL FRAME AND DECK. SKIRTING MATERIAL (WHERE APPLICABLE) SHALL BE 19/32" DURATEMP SIDING (PER SFM LISTING# 8140-2031-0004).

710A - NOT APPLICABLE.


WINDOW SCHEDULE

WINDOW NO.	TYPE	SIZE		FRAME MAT.	OPERABLE	MAX U-FACTOR	REQUIRED SHGC	MIN VT	NFRC RATED	GLASS SPECS	NOTES
		WIDTH	HEIGHT								
A	1	8'-0"	4'-0"	ANOD	YES	0.520	0.350	0.610	YES	DP	

WINDOW FINISH

ANOD: CLEAR ANODIZED ALUMINUM FRAME
DP: 3/16" MINIMUM DUAL PANE TEMPERED GLASS OF SOLAR GRAY - 3/16" EMERGESHIELD
T: TEMPERED GLASS

NOTES:
1. ALL OPERABLE SASH SHALL HAVE SCREENS.
2. TEMPORARY NFRC LABELS SHALL STAY ON WINDOWS UNTIL PROJECT INSPECTOR HAS VERIFIED INSTALLED FENESTRATION MATCHES WINDOW SCHEDULE ON PLAN.




DOOR SCHEDULE

DOOR NO.	WIDTH	HEIGHT	DOOR TYPE	QTY	DOOR MAT/FIN	FRAME MAT/FIN	HARDWARE SET	LOCKABLE FROM INT.	NOTES*
1	3'-0"	7'-0"	A		HM	KD	HW-1	YES	
2	3'-0"	7'-0"	A1		HM	KD	HW-2	YES	
3	3'-0"	7'-0"	A		SCL	KD	HW-3	NO	
4	3'-0"	7'-0"	B		HM	KD	HW-4	NO	
5	3'-0"	7'-0"	B		HM	KD	HW-5	NO	NO CLOSER REQ'D.
6	2'-0"	7'-0"	C		HM	KD	HW-6	NO	

DOOR MATERIAL AND FINISH ABBREVIATIONS

HM:	18GA HOLLOW METAL	KD:	KNOCK DOWN FRAME	EXTERIOR DOORS TO BE UNINSULATED SINGLE LAYER DOORS W/ U-FACTOR OF 1.450 MAX
WF:	16GA WELDED FRAME	SCL:	SOLID CORE WOOD LEGACY	
AL:	ALUMINUM	HC:	HOLLOW CORE WOOD	
SST:	STAINLESS STEEL	PT:	PAINTED	



FINISH SCHEDULE

ROOM NAME	FLOORING	WALL FINISH				CEILING		NOTES	
		FLOOR	BASE	FRONT	LEFT	REAR	RIGHT		CEILING
CLASSROOM 101	CARP	4" TS	TACK	TACK	TACK	TACK	CP	8'-6"	
CLASSROOM 102	CARP	4" TS	TACK	TACK	TACK	TACK	CP	8'-6"	
TOILET 106	OV	6" TS	FRP	FRP	FRP	FRP	OB	8'-0"	SEE 10A-5.70
TOILET 108	OV	6" TS	FRP	FRP	FRP	FRP	OB	8'-0"	SEE 10A-5.70
TOILET 109	OV	6" TS	FRP	FRP	FRP	FRP	OB	8'-0"	SEE 10A-5.70
TOILET 110	OV	6" TS	FRP	FRP	FRP	FRP	OB	8'-0"	SEE 10A-5.70
PLUMBING CHASE	---	---	---	---	---	---	---	---	---

FLOOR, WALL, CEILING MATERIALS

FLOORING
CARP: CARPET PER STATE OF CALIFORNIA SPECIFICATIONS COMPLYING WITH GROUP 1; TYPE "A" OR TYPE "B"; CLASS 2; DENSITY 4600; DIRECT GLUE DOWN
SV: SHEET VINYL FLOORING W/ FULLY SEALED JOINTS
VCT: VINYL COMPOSITION TILE

BASE
4" TS: 4" TOP SET BASE
6" TS: 6" TOP SET BASE
SC: 6" SELF-GOUGE BASE, CONTINUE FLOOR MATERIAL UP THE WALL PER 10A-5.70

WALLS
TACK: 1/2" VINYL TACKBOARD CLASS 1 OVER 1/2" GYPSUM BOARD BACKING
FRP: 1/8" FIBER REINFORCED PANEL OVER 1/2" WATER RESISTANT GYPSUM BOARD
GYP: 1/2" GYPSUM BOARD; TAPE; TEXTURE: PAINTED FINISH
PLY: 1/2" PLYWOOD FINISH
NF: NO FINISH

CEILING
CP: ACOUSTICAL LAY IN GRID CEILING PANELS (SEE SPECIFICATION NOTES ON REFLECTED CEILING PLAN)
HC: 5/8" GYPSUM BOARD; TAPE; TEXTURE: PAINTED FINISH (HARD LID CEILING)
GBP: 1/2" GYPSUM BOARD WASHABLE PANELS (PAINTED)

- ### FINISH NOTES
- ALL FINISHES SHALL COMPLY WITH CBC, CFC AND TITLE 19 CCR.
 - PREPARATION FOR SUB-FLOOR TO ACCEPT FINISH FLOORING IS BY FLOORING CONTRACTOR. PLYWOOD SUB-FLOOR IS 2.4.1 PLYWOOD. OUTER PLYWOOD IS PLUGGED AND TOUCH SANDED. ANY DEFORMITIES DUE TO STANDARD CONSTRUCTION PRACTICES SHALL BE FILLED AND SANDED BY FLOORING CONTRACTOR. THE JOINT AT THE MODLINE SHALL NOT BE LARGER THAN 1/8" AND SHALL BE FILLED AND SANDED BY FLOORING CONTRACTOR.
 - RESILIENT FLOORING DEMONSTRATING A COEFFICIENT OF FRICTION OF AT LEAST 0.6 PER ASTM D2047, WILL BE ACCEPTED AS MEETING THE INTENT OF SLIP RESISTANCE.
 - CARPET SHALL HAVE A LEVEL LOOP, TEXTURED LOOP, LEVEL CUT, OR LEVEL CUT / UN CUT PILE TEXTURE AND MAXIMUM PILE HEIGHT OF 1/2" PER THE 2022 CBC. CARPET EDGED SHALL COMPLY WITH THE 2022 CBC

DOOR HARDWARE

CLASSROOM -		EXTERIOR DOOR HW-1
LOCKSET	TAL LHV75-LFIC SAT	Finish 626 or equal
I/C CORE	SCHLAGE 23-030 C123	Finish 626 or equal
BUTTS	TAL BB179 4 1/2" x 4 1/2" NRP	Finish 626 or equal
CLOSER	TAL DC851 DA	Finish 689 or equal
WEATHER STRIP	COLUMBIA 3340S 3684 (ON DR FRAME)	Finish Alum or equal
THRESHOLD	COLUMBIA 4920 36"	Finish Alum or equal
DOOR BOTTOM	COLUMBIA 2590 36"	Finish Alum or equal

BOYS & GIRLS RESTROOM -		EXTERIOR DOOR HW-4
LOCKSET	TAL LHV70-LFIC SAT	Finish 626 or equal
I/C CORE	SCHLAGE 23-030 C123	Finish 626 or equal
BUTTS	TAL BB179 4 1/2" x 4 1/2" NRP	Finish 626 or equal
CLOSER	TAL DC851 DA	Finish 689 or equal
WEATHER STRIP	COLUMBIA 3340S 3684 (ON DR FRAME)	Finish Alum or equal
THRESHOLD	COLUMBIA 4920 36"	Finish Alum or equal
DOOR BOTTOM	COLUMBIA 2590 36"	Finish Alum or equal
LOUVER	ANEMO 24 x 12	Finish Bronze or equal

STAFF RESTROOM / SINGLE-OCCUPANCY -		INTERIOR DOOR HW-3
LOCKSET	TAL LHV40 SAT	Finish 626 or equal
BUTTS	TAL BB179 4 1/2" x 4 1/2" NRP	Finish 626 or equal

CHASIS EXTERIOR DOOR -		INTERIOR DOOR HW-6
LOCKSET	TAL LHV70 LFIC SAT	Finish 626 or equal
I/C CORE	SCHLAGE 23-030 C123	Finish 626 or equal
BUTTS	TAL BB179 4 1/2" x 4 1/2" NRP	Finish 626 or equal

INSULATION SPECIFICATIONS

MOISTURE PROTECTION INSULATION:
DESCRIPTION OF WORK: THE FURNISHING AND INSTALLING OF ALL INSULATION FOR ALL CEILING, FLOOR AREAS, PIPES AND EXTERIOR WALLS. (CLASS A = 0.25 FLAME SPREAD); SMOKE DEVELOPMENT DENSITY LESS THAN 450.

MATERIAL:
INSULATING MATERIAL FOR WALLS SHALL BE FIBERGLASS BATTS (UNFACED) AND SHALL COMPLY WITH CBC 720.1, 720.2, 720.3, 720.5 AND 720.7. INSULATION SHALL BE AS MANUFACTURED BY OWENS-CORNING, JOHNS-MANVILLE, OR EQUAL.

INSULATING MATERIAL FOR ROOFS SHALL BE CLOSED CELL SPRAY FOAM AND SHALL COMPLY WITH CBC 720.1, 720.2, 720.3, 720.5 AND 720.7. INSULATION SHALL HAVE A MINIMUM R-VALUE OF R-6 PER EACH INCH OF THICKNESS, AN AIR PERMEANCE RATE OF NOT MORE THAN 0.02 L/s AT 75 Pa, AND A WATER VAPOR TRANSMISSION RATE OF NOT MORE THAN 0.9 PERMS. THE FOAM SHALL BE APPLIED TO FILL ALL VOIDS IN THE ROOF FRAMING MEMBERS.

MIN INSULATION VALUES:
WOOD STUD EXTERIOR WALL INSULATION (MIN.)
 R-13 (4" WALL @ UNCONDITIONED RESTROOM MODULE ONLY)
 R-19 (6" WALL)
 R-30 (8" WALL)

STEEL STUD EXTERIOR WALL INSULATION (MIN.)
 R-13 (4" WALL @ UNCONDITIONED RESTROOM MODULE ONLY)
 R-19 BATT + R-6 (MIN) CONTINUOUS RIGID FOAM INSULATION ON THE INTERIOR SIDE OF THE WALL (6" WALL)
 R-30 BATT + R-8.8 (MIN) CONTINUOUS RIGID FOAM INSULATION ON THE INTERIOR SIDE OF THE WALL (8" WALL)

INTERIOR WALL INSULATION (MIN.)
R-13

FLOOR INSULATION
 NONE (CONCRETE MASS)
 R-11 (MIN) + CONCRETE MASS
 R-19 (MIN)

ROOF INSULATION (MIN.)
R-30 (5" MIN. DEPTH) CLOSED CELL SPRAY FOAM

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC.
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
SCHEDULES

REVISIONS

PRE-CHECK (PC) DOCUMENT CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 121999 INC.
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023










PC STATE AGENCY APPROVAL

Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO.
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER
A-0.2



IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc
 ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
**TYPICAL KEY PLANS
 24' - 120' x 40'**

REVISIONS

1	
2	
3	
4	

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION
 FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 14-121999 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 08/31/2023

PC STATE AGENCY APPROVAL

Silver Creek
 2830 BARRETT AVE PERRIS, CALIFORNIA 92571
 PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
 24' x 40' PC

PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023

P.C. SHEET NUMBER
A-0.3

Zone	Zip Code (Weather Station)	Rotation
Zone 14 92301 (PALMDALE)		30
		75
		120
		165
		210
		255
Zone 15 92225 (PALM SPRINGS)		300
		345
		30
		75
Zone 16 96006 (BLUE CANYON)		120
		165
		210
		255
		300
		345

24x40 (1) 5-ton unit							
TDV Eff.	%	TDV Total	%	Source EN	%	Result	
75.68	18.0%	75.68	18.0%	6.98	19.3%	0.0%	
78.22	18.3%	78.22	18.3%	7.26	19.8%	0.0%	
78.82	18.5%	78.82	18.5%	7.27	19.8%	0.0%	
69.06	16.8%	69.06	16.8%	6.39	17.9%	0.0%	
72.38	17.4%	72.38	17.4%	6.65	18.5%	0.0%	
74.24	17.7%	74.24	17.7%	6.87	19.0%	0.0%	
75.17	17.9%	75.17	17.9%	6.93	19.2%	0.0%	
68.01	16.6%	68.01	16.6%	6.32	17.9%	0.0%	
72.14	16.8%	72.14	16.8%	6.79	20.9%	0.0%	
76.94	17.6%	76.94	17.6%	7.22	21.9%	0.0%	
78.02	17.8%	78.02	17.8%	7.34	22.2%	0.0%	
67.89	16.1%	67.89	16.1%	6.41	20.1%	0.0%	
68.26	16.1%	68.26	16.1%	6.53	20.3%	0.0%	
70.52	16.4%	70.52	16.4%	6.80	20.9%	0.0%	
67.87	15.9%	67.87	15.9%	6.61	20.5%	0.0%	
65.76	15.6%	65.76	15.6%	6.27	19.7%	0.0%	
53.58	15.0%	53.58	15.0%	19.96	33.1%	0.0%	
56.56	15.7%	56.56	15.7%	20.06	33.2%	0.0%	
54.70	15.2%	54.70	15.2%	19.96	33.0%	0.0%	
43.85	12.6%	43.85	12.6%	19.58	32.7%	0.0%	
57.00	15.8%	57.00	15.8%	20.16	33.3%	0.0%	
60.18	16.5%	60.18	16.5%	20.16	33.3%	0.0%	
56.39	15.6%	56.39	15.6%	19.88	33.0%	0.0%	
46.54	13.3%	46.54	13.3%	19.52	32.7%	0.0%	

36x40 (1) 5-ton unit							
TDV Eff.	%	TDV Total	%	Source EN	%	Result	
95.31	26.2%	95.31	26.2%	8.77	28.3%	PASS	
98.31	26.5%	98.31	26.5%	9.05	28.8%	PASS	
97.91	26.5%	97.91	26.5%	8.99	28.7%	PASS	
88.70	25.0%	88.70	25.0%	8.13	26.9%	PASS	
95.51	26.3%	95.51	26.3%	8.75	28.3%	PASS	
98.80	26.7%	98.80	26.7%	9.07	28.9%	PASS	
98.08	26.6%	98.08	26.6%	8.98	28.7%	PASS	
87.68	24.8%	87.68	24.8%	8.04	26.7%	PASS	
7.51	2.6%	7.51	2.6%	0.51	2.5%	PASS	
6.59	2.2%	6.59	2.2%	0.52	2.6%	PASS	
7.89	2.7%	7.89	2.7%	0.55	2.7%	PASS	
16.78	5.6%	16.78	5.6%	0.56	2.8%	PASS	
15.35	5.2%	15.35	5.2%	0.46	2.3%	PASS	
8.56	2.9%	8.56	2.9%	0.66	3.3%	PASS	
8.02	2.7%	8.02	2.7%	0.56	2.8%	PASS	
8.18	2.8%	8.18	2.8%	0.43	2.2%	PASS	
70.82	22.8%	70.82	22.8%	19.50	38.6%	PASS	
74.47	23.6%	74.47	23.6%	19.55	38.6%	PASS	
70.44	22.6%	70.44	22.6%	19.31	38.2%	PASS	
63.49	21.0%	63.49	21.0%	19.05	38.0%	PASS	
71.64	23.0%	71.64	23.0%	19.51	38.6%	PASS	
74.64	23.7%	74.64	23.7%	19.54	38.6%	PASS	
70.14	22.5%	70.14	22.5%	19.32	38.3%	PASS	
63.68	21.0%	63.68	21.0%	19.10	38.1%	PASS	

□ 48x40
(2) 5-ton units

(2) 24x40 CLASSROOMS

□ 60x40
(2) 5-ton units

(1) 24x40 CLASSROOM +
(1) 36x40 CLASSROOM

□ 72x40
(3) 5-ton units

(3) 24x40 CLASSROOMS

□ 84x40
(3) 5-ton units

(2) 24x40 CLASSROOMS +
(1) 36x40 CLASSROOM

□ 96x40
(4) 5-ton units


(4) 24x40 CLASSROOMS

□ 108x40
(4) 5-ton units

(3) 24x40 CLASSROOMS +
(1) 36x40 CLASSROOM

□ 120x40
(5) 5-ton units

(5) 24x40 CLASSROOMS



PROJECT SPECIFIC STATE AGENCY APPROVAL


THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**DESIGN ENERGY VALUES
WOOD FLOOR - WALL HVAC**

REVISIONS

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED



MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER
A-0.53

Envelope Min Design - Zone: 1-16 Buildings: All		
Assembly	U-Value	Insulation R-Value
Walls:	0.062	R-19 batt
Floor:	0.054	R-19 batt
Roof:	0.055	R-30 Foam

HVAC Min Design - Zone: 1-16 Building: 24 x 40	
Tonnage	5
Min. EER / COP	11.0/3.3
Outside Air	See Ventilation Calcs on Mechanical Plans
Occupancy Sensor	Yes
DCV/ Economizer	Yes
Cooling Stages (Min.)	1
Allowable Mechanical Unit (See Equipment Schedule)	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> STANDARD </div> <div style="text-align: center;"> OPTIONAL </div> </div>

HVAC Min Design - Zone: 1-16 Buildings: 36 x 40	
Tonnage	5
Min. EER / COP	11.0/3.3
Outside Air	See Ventilation Calcs on Mechanical Plans
Occupancy Sensor	Yes
DCV/ Economizer	Yes
Cooling Stages (Min.)	2
Allowable Mechanical Unit (See Equipment Schedule)	<div style="text-align: center;"> STANDARD </div>

LEGEND
Occupancy Sensor: Ceiling mounted occupancy sensor with dimming controls. Automatic on for low level lighting only, full by manual activation.
DCV: Demand Control Ventilation

NOTES:
- Interior lights shall be dimmable LED fixtures, 51 Watts Max per fixtures, 4 fixtures per module per floor
- Windows shall be NFRC #INT-A-73-00213-00011 or equal, U-Factor = 0.520 (Max), SHGC = 0.350 (Max), Visual Transmittance = 0.610 (Min)
- Doors shall be hollow metal, uninsulated single layer doors (Min), U-Factor = 1.450 (Max)
- Refer to sheet A-0.2 For windows specifications
- Refer to sheet A-0.2 For insulation specifications
- Refer to sheets A-0.3 for mechanical layout per classroom
- Refer to Mechanical plans for more info
- Where Steel stud walls are used the exterior wall assembly shall be as follows:
U-Value 0.062 (max) - provide 6" (Nominal) studs @ 24" oc with R-19 batt cavity insulation and continuous 1.5" rigid foam insulation (R=8.8 min) on the interior side of the wall.

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD
Nonresidential Performance Compliance Method
Project Name: 04-121999 - 2640 - CONC FLS - RP HVAC

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

4. PROJECT SUMMARY
Table 4 shows which building components are included in the performance calculation. If indicated as not included, the project must show compliance prescriptively if within the general application.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

C1. COMPLIANCE SUMMARY
Table showing compliance margins for various energy components like Space Heating, Space Cooling, and Indoor Fans.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

C2. TUV ENERGY COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Annual TUV Energy Use, kWh/m² · yr)
Table with columns for Energy Component, Standard Design (TDV), Proposed Design (TDV), and Compliance Margin (TDV).

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

C3. TUV ENERGY RESULTS FOR NON-REGULATED COMPONENTS
Table showing compliance margins for components like Recreators, Process, and Other Lig.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD
Nonresidential Performance Compliance Method
Table with columns for Energy Component, Standard Design (SOURCE), Proposed Design (SOURCE), and Compliance Margin (SOURCE).

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

C4. SOURCE ENERGY RESULTS FOR NON-REGULATED COMPONENTS
Table showing compliance margins for components like Recreators, Process, and Other Lig.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

C5. ENERGY USE SUMMARY
Table with columns for Energy Component, Standard Design Site (MWh), Proposed Design Site (MWh), Margin (MWh), and Margin Percentage.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

C6. ENERGY USE INTENSITY (EUI)
Table with columns for Energy Component, Standard Design (kBtu/m² · yr), Proposed Design (kBtu/m² · yr), Margin (kBtu/m² · yr), and Margin Percentage.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

E1. ENVELOPE GENERAL INFORMATION (conditioned spaces only)
Table with columns for Energy Component, Standard Design (kBtu/m² · yr), Proposed Design (kBtu/m² · yr), Margin (kBtu/m² · yr), and Margin Percentage.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD
Nonresidential Performance Compliance Method
Table with columns for Surface Name, Construction Type, Area (ft²), Framing Type, Cavity B-Ratio, and Compliance Margin (SOURCE).

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

E2A. FENESTRATION ASSEMBLY SUMMARY (NONRESIDENTIAL)
Table with columns for Fenestration Assembly Name, Fenestration Type/Product Type/Framing Type, Certification Method, Assembly Method, Area (ft²), Overall U-factor, Overall SHGC, Overall VT, and Status.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

H4. INDOOR ENVIRONMENTAL AND THERMAL UTILITY SUMMARY
Table with columns for System ID, System Type, Heating Capacity (kBtu/h), Cooling Capacity (kBtu/h), Airflow (ft³/min), and other metrics.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

E3. INDOOR ENVIRONMENTAL AND THERMAL UTILITY SUMMARY
Table with columns for System ID, System Type, Heating Capacity (kBtu/h), Cooling Capacity (kBtu/h), Airflow (ft³/min), and other metrics.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

E4. INDOOR ENVIRONMENTAL AND THERMAL UTILITY SUMMARY
Table with columns for System ID, System Type, Heating Capacity (kBtu/h), Cooling Capacity (kBtu/h), Airflow (ft³/min), and other metrics.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

CERTIFICATE OF COMPLIANCE - NONRESIDENTIAL PERFORMANCE COMPLIANCE METHOD
Nonresidential Performance Compliance Method
Table with columns for Building Component, Name, and Compliance Margin (SOURCE).

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

E4A. FENESTRATION ASSEMBLY SUMMARY (NONRESIDENTIAL)
Table with columns for Fenestration Assembly Name, Fenestration Type/Product Type/Framing Type, Certification Method, Assembly Method, Area (ft²), Overall U-factor, Overall SHGC, Overall VT, and Status.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

H4. INDOOR ENVIRONMENTAL AND THERMAL UTILITY SUMMARY
Table with columns for System ID, System Type, Heating Capacity (kBtu/h), Cooling Capacity (kBtu/h), Airflow (ft³/min), and other metrics.


CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

E3. INDOOR ENVIRONMENTAL AND THERMAL UTILITY SUMMARY
Table with columns for System ID, System Type, Heating Capacity (kBtu/h), Cooling Capacity (kBtu/h), Airflow (ft³/min), and other metrics.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601

E4. INDOOR ENVIRONMENTAL AND THERMAL UTILITY SUMMARY
Table with columns for System ID, System Type, Heating Capacity (kBtu/h), Cooling Capacity (kBtu/h), Airflow (ft³/min), and other metrics.

CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance
Report Version: 2022.0.000
Schema Version: rev 20220601



PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM INC) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY...

PROJECT NAME:

SYLVAN USD FREEDOM E.S. (2) 24' x 40' CLASSROOM BUILDINGS


SHEET TITLE:

PRF FORMS 24x40 - ZONE 14 WORST CASE

REVISIONS

- Revision list with symbols 1 through 5.

PRE-CHECK (PC) DOCUMENT CODE: 2022 CBC A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED



PC STATE AGENCY APPROVAL



Silver Creek 2830 BARRETT AVE PERRIS, CALIFORNIA 92571 PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL



SILVER CREEK INDUSTRIES 24' x 40' PC

PROJECT NO:

DRAWN BY: SCALE: AS NOTED

DATE: 02-27-2023

P.C. SHEET NUMBER

A-0.54

Nonresidential Building Commissioning CERTIFICATE OF COMPLIANCE. Project Name: SILVER CREEK PC - TYPICAL CLASSROOM. Report Page: (Page 1 of 6). Project Address: 2023-01-31T18:53:26-05:00.

Table with 3 columns: Item, Description, and Details. Includes sections for GENERAL INFORMATION, PROJECT SCOPE, and COMMISSIONING REQUIREMENTS PER 120.8.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance. Report Version: 2022.0.000. Compliance ID: 86563-0123-0005.

Table with 10 columns: Design Kickoff Review, Owner's Project Requirements, Basis of Design, Design Review, Commissioning Plan, Functional Performance Testing, Documentation and Training, Commissioning Report, Compliance Results.

D. EXCEPTIONAL CONDITIONS. This table is auto-filled with uneditable comments because of selections made or data entered in tables throughout the form.

F. ADDITIONAL REMARKS. This table includes remarks made by the permit applicant to the Authority Having Jurisdiction.

Nonresidential Building Commissioning CERTIFICATE OF COMPLIANCE. Project Name: SILVER CREEK PC - TYPICAL CLASSROOM. Report Page: (Page 3 of 6). Project Address: 2023-01-31T18:53:26-05:00.

Table with 3 columns: Item, Description, and Details. Includes sections for DESIGN REVIEW KICKOFF MEETING and PRELIMINARY CONSTRUCTION SCHEDULE.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance. Report Version: 2022.0.000. Compliance ID: 86563-0123-0005.

Table with 2 columns: Item and Description. Includes sections for DESIGN REVIEW KICKOFF MEETING, OWNER'S PROJECT REQUIREMENTS (OPR), BASIS OF DESIGN (BOD), and CONSTRUCTION DOCUMENT DESIGN REVIEW CHECKLIST.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance. Report Version: 2022.0.000. Compliance ID: 86563-0123-0005.

Nonresidential Building Commissioning CERTIFICATE OF COMPLIANCE. Project Name: SILVER CREEK PC - TYPICAL CLASSROOM. Report Page: (Page 2 of 6). Project Address: 2023-01-31T18:53:26-05:00.

Table with 3 columns: Item, Description, and Details. Includes sections for CONSTRUCTION DOCUMENT DESIGN REVIEW CHECKLIST, COMMISSIONING PLAN, FUNCTIONAL PERFORMANCE TESTING, DOCUMENTATION AND TRAINING, COMMISSIONING REPORT, REQUIRED CERTIFICATES OF INSTALLATION, and REQUIRED CERTIFICATES OF ACCEPTANCE.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance. Report Version: 2022.0.000. Compliance ID: 86563-0123-0005.

Documentation Author's Declaration Statement. I certify that this Certificate of Compliance documentation is accurate and complete.

Documentation Author Name: Ryan McIntosh. Signature Date: 02-20-2023. Address: 2830 Barnett Ave, Perris, CA 92571. Phone: (951) 943-5303.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance. Report Version: 2022.0.000. Compliance ID: 86563-0123-0005.

Table with 3 columns: Item, Description, and Details. Includes sections for DESIGN REVIEW KICKOFF MEETING, PRELIMINARY CONSTRUCTION SCHEDULE, PROJECT GOALS RELATED TO ENERGY EFFICIENCY, and OPERATIONAL GOALS.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance. Report Version: 2022.0.000. Compliance ID: 86563-0123-0005.

Table with 2 columns: Item and Description. Includes sections for DESIGN REVIEW KICKOFF MEETING, OWNER'S PROJECT REQUIREMENTS (OPR), BASIS OF DESIGN (BOD), and CONSTRUCTION DOCUMENT DESIGN REVIEW CHECKLIST.

Electrical Power Distribution CERTIFICATE OF COMPLIANCE. Project Name: SILVER CREEK PC - TYPICAL CLASSROOM. Report Page: (Page 1 of 4). Project Address: 2023-01-31T18:53:26-05:00.

Table with 7 columns: Item, Description, and Details. Includes sections for GENERAL INFORMATION, PROJECT SCOPE, COMPLIANCE RESULTS, EXCEPTIONAL CONDITIONS, REMARKS, VOLTAGE DROP, and ADDITIONAL REMARKS.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance. Report Version: 2022.0.000. Compliance ID: 86563-0123-0006.

Electrical Power Distribution CERTIFICATE OF COMPLIANCE. Project Name: SILVER CREEK PC - TYPICAL CLASSROOM. Report Page: (Page 2 of 4). Project Address: 2023-01-31T18:53:26-05:00.

Table with 6 columns: Item, Description, and Details. Includes sections for COMPLIANCE RESULTS and EXCEPTIONAL CONDITIONS.

Table with 5 columns: Item, Description, and Details. Includes sections for VOLTAGE DROP and ADDITIONAL REMARKS.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance. Report Version: 2022.0.000. Compliance ID: 86563-0123-0006.


Electrical Power Distribution CERTIFICATE OF COMPLIANCE. Project Name: SILVER CREEK PC - TYPICAL CLASSROOM. Report Page: (Page 3 of 4). Project Address: 2023-01-31T18:53:26-05:00.

Table with 5 columns: Item, Description, and Details. Includes sections for DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION and DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE.

Registration Number: CA Building Energy Efficiency Standards - 2022 Nonresidential Compliance. Report Version: 2022.0.000. Compliance ID: 86563-0123-0006.

Documentation Author's Declaration Statement. I certify that this Certificate of Compliance documentation is accurate and complete.

Documentation Author Name: Ryan McIntosh. Signature Date: 02-20-2023. Address: 2830 Barnett Ave, Perris, CA 92571. Phone: (951) 943-5303.




PROJECT SPECIFIC STATE AGENCY APPROVAL. THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC. (SCM Inc.)

PROJECT NAME: SYLVAN USD FREEDOM E.S. (2) 24' x 40' CLASSROOM BUILDINGS

CERTIFICATE OF COMPLIANCE FORMS

REVISIONS table with 5 rows and 2 columns.


PRE-CHECK (PC) DOCUMENT CODE: 2022 CBC. A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED.



PC STATE AGENCY APPROVAL. Silver Creek logo and address: 2830 BARRETT AVE PERRIS, CALIFORNIA 92571. PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL. SILVER CREEK INDUSTRIES 24' x 40' PC.

PROJECT NO., DRAWN BY, SCALE: AS NOTED, DATE: 02-27-2023, P.C. SHEET NUMBER, A-0.6A



NOTES

- PLACE (2) PERMANENT METAL IDENTIFICATION LABELS ON EACH MODULE. PER IR 16-1 (4.1)
(1) LABEL AT REAR EXTERIOR AND (1) LABEL ABOVE FINISH LINE AT INTERIOR FRAME. LABELS WILL BE MECHANICALLY FASTENED AND SHOW THE DSA APPLICATION NUMBER, MANUFACTURER'S NAME AND SERIAL NUMBER, DESIGN LIVE LOAD FOR ROOF AND FLOOR FRAMING, REQUIRED PV SYSTEM CAPACITY (kW), WIND SPEED, EXPOSURE CATEGORY, AND Kz1 = 1.0 2022 CBC, DESIGN CLIMATE ZONE, SEISMIC PARAMETER = S_s
- VINYL TACKBOARD INTERIOR FINISH SHALL COMPLY WITH CBC SECTION 803.7
- LOCATIONS OF DOORS AND WINDOWS MAY VARY PER JOB. (IF THE NUMBER OF WINDOWS INCREASE, A NEW TITLE 24 SHALL BE SUBMITTED TO DSA)
- POSTERS OF OCCUPANCY LOAD SIGNS SHALL COMPLY WITH CALIFORNIA CODE OF REGULATIONS (CCR) TITLES 19 ART. 3.30 (NOT IN MODULAR MANUFACTURER'S SCOPE OF WORK)
- IF BUILDING IS TO BE RELOCATED, SEE RELOCATION SHEETS
- FOR BUILDINGS THAT ARE MANUFACTURED IN-PLANT, THE IN-PLANT INSPECTOR IS TO ATTACH A VERIFIED REPORT INSIDE EACH BUILDING, WHICH SHALL INDICATE THE MANUFACTURER'S NAME AND THE SERIAL NUMBER FOR EACH BUILDING MODULE AS WELL AS THE DSA FILE AND APPLICATION NUMBERS, PER IR 16-1.13 (2.1)
- ALL FIXTURE HEIGHTS TO BE VERIFIED PRIOR TO CONSTRUCTION
- INTERIOR WALLS MAY BE ADDED TO FLOOR PLAN. SEE STRUCTURAL
- FOR CASEWORK, TEACHER WALL, OR TV BLOCKING OPTIONS, SEE SHEET A-5.80
- INTERIOR WALLS BETWEEN CLASSROOMS AND ADJACENT SPACES (WHERE OCCURS) SHALL BE FULL HEIGHT TO THE UNDERSIDE OF THE STRUCTURE ABOVE AND SHALL HAVE A STC RATING OF NOT LESS THAN 40. SEE SHEET A-0.7 FOR WALL ASSEMBLY
- TOILET ROOM FLOORING AND BASE SHALL BE INSTALLED PER 10/A-5.70 IN LIEU OF PROVIDING A CURB (IR 23-2)
- DOORS SHALL PROVIDED WITH MINIMUM 4' CANOPY OR ROOF OVERHANG

DETAIL SCHEDULE

FINISH:	SHEET #:
<input type="checkbox"/> SIDING OVER WOOD STUDS	A-5.50
<input type="checkbox"/> PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH WOOD STUDS	A-5.51
<input type="checkbox"/> SIDING OVER STEEL STUDS	A-5.60
<input type="checkbox"/> PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH STEEL STUDS	A-5.61

FIRE RATED DETAIL SCHEDULE

FIRE PROTECTION:	SHEET #:
<input type="checkbox"/> 1 HOUR - SIDING OVER WOOD STUDS	A-5.52
<input type="checkbox"/> 1 HOUR - PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH WOOD STUDS	A-5.53
<input type="checkbox"/> 1 HOUR - SIDING OVER STEEL STUDS	A-5.62
<input type="checkbox"/> 1 HOUR - PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH STEEL STUDS	A-5.63

WALL LEGEND


	NOMINAL 4" WALL STUD	<input type="checkbox"/>
	NOMINAL 6" WALL STUD	<input type="checkbox"/>
	NOMINAL 8" WALL STUD	<input type="checkbox"/>
	WINDOW PER SCHEDULE SHEET A-0.2	
	DOOR PER SCHEDULE SHEET A-0.2	

NOTES:
ALL EXTERIOR WALL FRAMING SHALL BE 2x6 (OR 6" NOMINAL STEEL STUD) (MIN). EXCEPTION: AT UNCONDITIONED RESTROOM MODULES.
2x4 (OR 4" NOMINAL STEEL STUD) WALL FRAMING NOT ALLOWED WITH PLASTER WALL FINISH AT UNCONDITIONED RESTROOM MODULES WITH WALLS OVER 9'-0" IN HEIGHT.
THIS PLAN MAY INCLUDE THE VARIOUS EXERCISABLE OPTIONS APPLICABLE TO THE PC SUCH AS PARTITION WALLS, PLUMBING, ETC. FOR REFERENCE PURPOSES, OPTIONS CAN BE APPLIED AS REQUIRED TO THE PC'S BUILDING SIZES.

SYMBOLS LEGEND

	60" CIRCLE CLEAR SPACE
	30"x48" CLEAR SPACE

MARKING & IDENTIFICATION OF FIRE RATED CONSTRUCTION. (CBC 703.5)
FIRE WALLS, FIRE BARRIERS, FIRE PARTITIONS, SMOKE BARRIERS AND SMOKE PARTITIONS OR ANY OTHER WALL REQUIRED TO HAVE PROTECTED OPENINGS OR PENETRATIONS SHALL BE EFFECTIVELY AND PERMANENTLY IDENTIFIED WITH SIGNS OR STENCILING. SUCH IDENTIFICATION SHALL:
1. BE LOCATED IN ACCESSIBLE CONCEALED FLOOR, FLOOR-CEILING OR ATTIC SPACES;
2. BE LOCATED WITHIN 15 FEET OF THE END OF EACH WALL AND AT INTERVALS NOT EXCEEDING 30 FEET MEASURED HORIZONTALLY ALONG THE WALL OR PARTITION; AND
3. INCLUDE LETTERING NOT LESS THAN 3" IN HEIGHT AND A MIN. 3/8" STROKE IN A CONTRASTING COLOR INCORPORATING THE SUGGESTED WORDING. "FIRE AND/OR SMOKE BARRIER - PROTECT ALL OPENINGS" OR OTHER SIMILAR WORDING.



PROJECT SPECIFIC STATE AGENCY APPROVAL


THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC. (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**FLOOR PLAN
24' x 40'**

REVISIONS

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED




PC STATE AGENCY APPROVAL

Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER
A-1.01




HARDLID CEILING (OPTIONAL) SCALE: 1/4" = 1'-0"

LEGEND

	T-BAR CEILING
	FIELD INSTALLED PANEL AT MODULE LINE
	2' x 4' RECESSED LIGHT FIXTURE, HATCHING DENOTES EMERGENCY LIGHT FIXTURE (SEE ELECTRICAL PLAN)
	"OPTIONAL" 1' x 4' RECESSED LIGHT FIXTURE
	SPLAY WIRE
	RETURN AIR REGISTER
	SUPPLY AIR REGISTER
	CEILING EXHAUST FAN
	CEILING MOUNTED OCCUPANCY SENSOR
	CEILING MOUNTED PHOTOCELL
	CEILING MOUNTED SMOKE DETECTOR
	ATTIC MOUNTED HEAT DETECTOR

NOTE:
FOR ALL REFLECTED CEILING NOTES
SEE SHEET A-0.1



REFLECTED CEILING PLAN SCALE: 1/4" = 1'-0" 1

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.

ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**REFLECTED CEILING
PLAN
24' x 40'**

REVISIONS

1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL

Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023

T-BAR SCHEDULE

ARMSTRONG PART NUMBERS ICC-ES ESR-1308
MAIN RUNNER: 7301
4" CROSS TEE: XL7341
2" CROSS TEE: XL7328
STANDARD 7/8" WALL ANGLE WITH BERG-2 CLIP (ICC #ESR-1308) 2"
WALL ANGLE: 7810 (OPTIONAL)

P.C. SHEET NUMBER
A-2.01

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
 ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
**CEILING DETAILS
 T-GRID**

REVISIONS

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION
 FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-121999 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 08/31/2023

PC STATE AGENCY APPROVAL



Silver Creek
 2830 BARRETT AVE PERRIS, CALIFORNIA 92571
 PHONE: 951-943-5393 FAX: 951-943-2211


MODULAR BUILDING DESIGN PROFESSIONAL




SILVER CREEK INDUSTRIES
 24' x 40' PC

PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023
 P.C. SHEET NUMBER


A-2.20




GRID AT MODLINE SCALE: 3"=1'-0" 1




SPLAY BRACING WIRE SCALE: 3"=1'-0" 6




HANGER WIRE DETAIL SCALE: 3"=1'-0" 11




TRAPEZE DETAIL SCALE: NTS 17




HVAC REGISTER MOUNTING SCALE: NTS 12




LIGHT FIXTURE MOUNTING SCALE: NTS 7




4' CROSS TEE AT LIGHTS SCALE: 3/8"=1'-0" 2




FIXED SIDE SCALE: NTS 18




HANGER WIRE - FIXED SIDE (ENDWALL) SCALE: 3"=1'-0" 13




HANGER WIRE - FIXED SIDE (SIDEWALL) SCALE: 3"=1'-0" 8




SEISMIC SPLAY - 4 WAY SCALE: NTS 3




FREE SIDE SCALE: NTS 19




HANGER WIRE - FREE SIDE (ENDWALL) SCALE: 3"=1'-0" 14




HANGER WIRE - FREE SIDE (SIDEWALL) SCALE: 3"=1'-0" 9




COMPRESSION STRUT SCALE: 3"=1'-0" 4




GRID SEISMIC SEPARATION JOINT SCALE: 3"=1'-0" 20




ATTIC DRAFT STOP SCALE: 3"=1'-0" 15



HVAC DUCTWORK MOUNTING SCALE: NTS 10




COMPRESSION STRUT SCALE: 3"=1'-0" 5



ROOF PLAN - METAL DECK - DUAL SLOPE

SCALE: 1/4" = 1' - 0"




ROOF PLAN - METAL DECK - MONO SLOPE

SCALE: 1/4" = 1' - 0"

NOTES

- BUILDINGS SHALL HAVE ROOF COVERINGS AS SPECIFIED IN CBC TABLE 1505.1 - CLASS A.
- LOCATIONS OF DRAFTSTOP AND/OR FULL HEIGHT PARTITIONS AS REQUIRED PER CBC-718.4.3 SHALL BE SHOWN ON PROJECT SPECIFIC PLANS LOCATED AT MODULE LINES.
- ALL ROOFTOP EQUIPMENT THAT REQUIRES SERVICE & ROOF ACCESS HATCHES MUST BE A MIN. OF 10'-0" AWAY FROM ALL ROOF EDGES TO OPENING EDGES. OR A GUARDRAIL SHALL BE PROVIDED PER 7/S-2.60
- SEE DETAIL "A" (THIS SHEET) FOR ROOF SYSTEM UPLIFT CAPACITY

SOLAR ZONE




KEYPLAN

BUILDING SIZE	REQUIRED SOLAR ZONE	PROVIDED SOLAR ZONE
24'-0" x 40'-0"	172 SF	178 SF
24'-0" x 40'-0"	250 SF	267 SF
24'-0" x 40'-0"	344 SF	360 SF
24'-0" x 40'-0"	430 SF	445 SF
24'-0" x 40'-0"	510 SF	524 SF
24'-0" x 40'-0"	590 SF	600 SF
24'-0" x 40'-0"	670 SF	674 SF
24'-0" x 40'-0"	754 SF	764 SF
24'-0" x 40'-0"	830 SF	830 SF

ROOF AREA PER MODULE = 567 SF
 REQUIRED SOLAR ZONE = 86 SF
 PROVIDED SOLAR ZONE = 89 SF

NOTE: ACTUAL SOLAR ZONE LOCATION AND SIZE MAY VARY. MINIMUM ZONE AREA SHALL BE PER THE TABLE ABOVE.



NOTES:

- THE ALLOWABLE UPLIFT VALUES PROVIDED ABOVE ARE BASED ON TESTING PERFORMED IN ACCORDANCE WITH UL STANDARD 1897 (UPLIFT TEST FOR ROOF COVERING SYSTEM).
- THE ULTIMATE LOAD DETERMINED BY TESTING = 135 PSF. A SAFETY FACTOR OF 2.0 HAS BEEN USED IN CALCULATING THE ALLOWABLE VALUES.
- PV PANEL ATTACHMENT OPTION IS NOT INCLUDED WITHIN THIS PC.
- THE CLIP SLIDING CAPACITY HAS NOT BEEN TESTED. IF PV PANELS ARE INSTALLED THE SLIDING CAPACITY OF THE ROOF PANEL SYSTEM MUST BE DETERMINED BY FIELD TESTING FOR ROOF SLOPES OF NOT LESS THAN 7 DEGREES. EXCEPTION: WHERE THE SLIDING LOAD FOR SEISMIC AND WIND FORCES ON THE PV PANEL SYSTEM IS LESS THAN THE DISPLACED DESIGN LIVE LOAD SLIDING COMPONENT PER DSA IN 16-8 (SECTION 5.1.1.2).
- CONVERSION FROM ALLOWABLE UPLIFT (ASD) TO UPLIFT CAPACITY (LRFD) IS BASED ON ASD WIND PRESSURE = 0.6 x (LFRD WIND PRESSURE).

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc.) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**


SHEET TITLE:
**ROOF PLAN
24'x40' - METAL DECK
MONO OR DUAL SLOPE**

REVISIONS


PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL


Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL



SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023

P.C. SHEET NUMBER
A-3.01

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
 ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
**ROOF DETAILS
 STANDING SEAM
 ROOF DECK**

REVISIONS

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION
 FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-121999 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 08/31/2023

PC STATE AGENCY APPROVAL



Silver Creek
 2830 BARRETT AVE PERRIS, CALIFORNIA 92571
 PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL




SILVER CREEK INDUSTRIES
 24' x 40' PC


PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023

P.C. SHEET NUMBER


A-3.50




REF: A3.01, A3.02, A3.03, A3.04
ROOF FLASHING AT SIDEWALL SCALE: 6"=1'-0" 16




REF: A3.50
ROOF CLIP ZONES NTS 17




REF: A3.50
ROOF DECK PROFILE SCALE: NTS 18




REF: A3.50
END ROOF PAN CONDITION SCALE: 6"=1'-0" 19




REF: A3.01, A3.02, A3.03, A3.04
DOWNSPOUT ATTACHMENT SCALE: 3"=1'-0" 20




REF: A3.01, A3.02, A3.03, A3.04
GUTTER AT ROOF FASCIA BEAM SCALE: 3"=1'-0" 11




REF: A3.01, A3.02, A3.03, A3.04
GUTTER AT ROOF FASCIA BEAM SCALE: 3"=1'-0" 12




REF: A3.01, A3.02, A3.03, A3.04
ROOF FLASHING AT HIGH SIDE SCALE: 6"=1'-0" 13




REF: A3.50
ROOF CLIP SCALE: 1'-0"=1'-0" 14




REF: A3.03, A3.04
ROOF CAP AT SEPARATION SCALE: 3"=1'-0" 15




REF: A3.50
STANDING SEAM PANEL AT ENDS SCALE: NTS 6




REF: A3.01, A3.02, A3.03, A3.04
STARTER ROOF PAN CONNECTION SCALE: 6"=1'-0" 7




REF: A3.01, A3.02, A3.03, A3.04
ROOF FLASHING AT SIDEWALL SCALE: 6"=1'-0" 8




REF: A3.01, A3.02, A3.03, A3.04
ROOF CLIP @ STANDING SEAM SCALE: NTS 9




REF: A3.01, A3.02, A3.03, A3.04
MODULE LINE ROOF CAP SCALE: 3"=1'-0" 10




REF: A3.50
FLASHING AT MODULE LINE WALL SCALE: 6"=1'-0" 1a




REF: A3.50
0.018" ROOF CAP AT MODULE LINE SCALE: 6"=1'-0" 1b




REF: A3.50
FLASHING AT ROOF LOW SIDE(S) SCALE: 6"=1'-0" 3a




REF: A3.01, A3.02, A3.03
FLASHING AT ROOF HIGH SIDE SCALE: 6"=1'-0" 3b




REF: A3.50
GUTTER AND STRAP & DOWNSPOUT SCALE: 3"=1'-0" 5




EXTERIOR ELEVATIONS - FRONT - DUAL SLOPE SCALE: 1/4" = 1'-0" 5




EXTERIOR ELEVATIONS - FRONT - MONO SLOPE SCALE: 1/4" = 1'-0" 1




EXTERIOR ELEVATIONS - REAR - DUAL SLOPE SCALE: 1/4" = 1'-0" 6




EXTERIOR ELEVATIONS - REAR - MONO SLOPE SCALE: 1/4" = 1'-0" 2




EXTERIOR ELEVATIONS - LEFT - DUAL SLOPE SCALE: 1/4" = 1'-0" 7



EXTERIOR ELEVATIONS - LEFT - MONO SLOPE SCALE: 1/4" = 1'-0" 3



EXTERIOR ELEVATIONS - RIGHT - DUAL SLOPE SCALE: 1/4" = 1'-0" 8



EXTERIOR ELEVATIONS - RIGHT - MONO SLOPE SCALE: 1/4" = 1'-0" 4

- NOTES (EXTERIOR ELEVATION)**
- PROVIDE PROTECTION RAIL AROUND HVAC UNIT(S) IF LOCATED IN A PEDESTRIAN WAY IF THE HEIGHT FROM GRADE TO BOTTOM OF UNIT EXCEEDS 27" (NIC). REFERENCE TO DET. # 2/A5.81 FOR WOOD STUDS, # 17/A5.81 FOR STEEL STUDS
 - RAMP (WHERE OCCURS), NOT SHOWN FOR CLARITY.
 - WALL BEYOND HANDRAIL SHALL NOT HAVE ANY SHARP OR ABRASIVE SURFACE ADJACENT TO HANDRAILS. (GRIND SMOOTH ALL METAL RAILING CONNECTIONS - SMOOTH SURFACE TO EXTEND 18" ABOVE HANDRAIL)
 - ~~FOR REAR ONLY PROVIDE CONTROL JOINT AT EACH MODULE LINE AND BELOW OPENING WHERE FIRE RATED WALLS ARE REQUIRED MATERIALS AND METHOD OF CONSTRUCTION USED TO PROTECT JOINTS WILL COMPLY WITH CBC SECTION 708.2 AND 709.~~
 - EXTERIOR PROJECTIONS SHALL COMPLY W/ SECTION 705 AND 1406, 2022 CBC
 - PROVIDE AN OFFSET RAMP (PER SHEET R-1.02) WHEN A RAMP IS REQUIRED ADJACENT TO A STUCCO WALL AND/OR FIRE RESISTANCE RATED EXTERIOR WALL.

DETAIL SCHEDULE

FINISH:	SHEET #:
<input checked="" type="checkbox"/> SIDING OVER WOOD STUDS	A-5.50
<input type="checkbox"/> PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH WOOD STUDS	A-5.61
<input type="checkbox"/> SIDING OVER STEEL STUDS	A-5.60
<input type="checkbox"/> PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH STEEL STUDS	A-5.61

FIRE RATED DETAIL SCHEDULE

FIRE PROTECTION:	SHEET #:
<input type="checkbox"/> 1 HOUR - SIDING OVER WOOD STUDS	A-5.53
<input type="checkbox"/> 1 HOUR - PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH WOOD STUDS	A-5.53
<input type="checkbox"/> 1 HOUR - SIDING OVER STEEL STUDS	A-5.62
<input type="checkbox"/> 1 HOUR - PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH STEEL STUDS	A-5.63

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**


SHEET TITLE:
**EXTERIOR ELEVATION
24' X 40'
MONO / DUAL SLOPE**

REVISIONS


PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL


Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL



SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER

A-4.01

DETAIL SCHEDULE

FINISH:	SHEET #:
<input checked="" type="checkbox"/> SIDING OVER WOOD STUDS	A-5.50
<input type="checkbox"/> PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH WOOD STUDS	A-5.51
<input type="checkbox"/> SIDING OVER STEEL STUDS	A-5.60
<input type="checkbox"/> PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH STEEL STUDS	A-5.61

FIRE RATED DETAIL SCHEDULE


FINISH:	SHEET #:
<input type="checkbox"/> 1 HOUR - SIDING OVER WOOD STUDS	A-5.50
<input type="checkbox"/> 1 HOUR - PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH WOOD STUDS	A-5.53
<input type="checkbox"/> 1 HOUR - SIDING OVER STEEL STUDS	A-5.62
<input type="checkbox"/> 1 HOUR - PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH STEEL STUDS	A-5.63

FLOOR OPTION

<input checked="" type="checkbox"/> WOOD FLOOR
<input type="checkbox"/> CONCRETE FLOOR

NOTES

SEALANTS AND CAULKING:
GENERAL: FURNISH AND INSTALL ALL SEALANTS AND CAULKING AS REQUIRED TO PROVIDE A WEATHERTIGHT BUILDING AND TO LIMIT AIR LEAKAGE.
MATERIALS: SEALANT SHALL BE AN ACRYLIC LATEX OR SILICONE CAULKING.
APPLICATIONS: AT JOINTS WHERE SHOWN, APPLY SEALANT AS FOLLOWS - JOINTS SHALL BE CLEAN, DRY, AND FREE FROM DUST, WAX, AND FOREIGN MATERIALS. SEALANT SHALL BE APPLIED WITH A GUN IN A STRICT COMPLIANCE WITH MANUFACTURER'S DIRECTIONS. COMPLETELY FILL THE JOINT AND FIRMLY TOOL AGAINST THE BACKING, MAKING A SMOOTH CONVEX BEAD.
COLOR: COLOR OF MATERIAL SHALL MATCH THAT OF ADJACENT FINISHED SURFACES.
ALL EXTERIOR JOINTS, PENETRATIONS AND OTHER OPENINGS SHALL BE CAULKED, GASKETED, WEATHER-STRIPPED OR OTHERWISE SEALED.



PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc


PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**CROSS SECTION
MONO SLOPE**

REVISIONS

NO.	DESCRIPTION
1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED



PC STATE AGENCY APPROVAL





MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER

A-5.01



BUILDING SECTION

SCALE: 1" = 1' - 0" 1

DETAIL SCHEDULE

FINISH:	SHEET #:
<input checked="" type="checkbox"/> SIDING OVER WOOD STUDS	A-5.50
<input type="checkbox"/> PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH WOOD STUDS	A-5.51
<input type="checkbox"/> SIDING OVER STEEL STUDS	A-5.60
<input type="checkbox"/> PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH STEEL STUDS	A-5.61

FIRE RATED DETAIL SCHEDULE


FINISH:	SHEET #:
<input type="checkbox"/> 1 HOUR - SIDING OVER WOOD STUDS	A-5.50
<input type="checkbox"/> 1 HOUR - PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH WOOD STUDS	A-5.53
<input type="checkbox"/> 1 HOUR - SIDING OVER STEEL STUDS	A-5.62
<input type="checkbox"/> 1 HOUR - PLASTER OVER 1/2" OSB OR 1/2" CDX PLY WITH STEEL STUDS	A-5.63

FLOOR OPTION

<input checked="" type="checkbox"/> WOOD FLOOR
<input type="checkbox"/> CONCRETE FLOOR

NOTES

SEALANTS AND CAULKING:
 GENERAL: FURNISH AND INSTALL ALL SEALANTS AND CAULKING AS REQUIRED TO PROVIDE A WEATHERTIGHT BUILDING AND TO LIMIT AIR LEAKAGE.
 MATERIALS: SEALANT SHALL BE AN ACRYLIC LATEX OR SILICONE CAULKING.
 APPLICATIONS: AT JOINTS WHERE SHOWN, APPLY SEALANT AS FOLLOWS - JOINTS SHALL BE CLEAN, DRY, AND FREE FROM DUST, WAX, AND FOREIGN MATERIALS. SEALANT SHALL BE APPLIED WITH A GUN IN A STRICT COMPLIANCE WITH MANUFACTURER'S DIRECTIONS. COMPLETELY FILL THE JOINT AND FIRMLY TOOL AGAINST THE BACKING, MAKING A SMOOTH CONVEX BEAD.
 COLOR: COLOR OF MATERIAL SHALL MATCH THAT OF ADJACENT FINISHED SURFACES.
 ALL EXTERIOR JOINTS, PENETRATIONS AND OTHER OPENINGS SHALL BE CAULKED, GASKETED, WEATHER-STRIPPED OR OTHERWISE SEALED.



PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
 ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc


PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
CROSS SECTION

REVISIONS

1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED



PC STATE AGENCY APPROVAL




Silver Creek
 2830 BARRETT AVE PERRIS, CALIFORNIA 92571
 PHONE: 951-943-5393 FAX: 951-943-2211


MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
 24' x 40' PC


PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023

P.C. SHEET NUMBER
A-5.05







HVAC MOUNT AT JAMBS SCALE: 3"=1'-0" 16




WINDOW SECTION AT JAMBS SCALE: 3"=1'-0" 11




EXTERIOR DOOR HEADER SCALE: 3"=1'-0" 6




CLOSURE BETWEEN BUILDINGS SCALE: 3"=1'-0" 1




HVAC UNIT AT BOTTOM SCALE: 3"=1'-0" 17




WINDOW HEADER SCALE: 3"=1'-0" 12




EXTERIOR DOOR JAMB SCALE: 3"=1'-0" 7




COLUMN AT CORNER SCALE: 3"=1'-0" 2




HVAC UNIT (PLAN) SCALE: 1"=1'-0" 18




WINDOW SILL SCALE: 3"=1'-0" 13




COLUMN AT CORNER SCALE: 3"=1'-0" 8




COLUMN AT MODULE LINE (FULL PANEL CLOSE-UP) SCALE: 3"=1'-0" 3




NOT USED 19




SOFFIT AT ROOF HEADER WITH VENT SCALE: 3"=1'-0" 14




INTERIOR DOOR JAMB SCALE: 3"=1'-0" 9




COLUMN AT MODULE LINE (CLOSURE STRIP) SCALE: 3"=1'-0" 4




NOT USED 20



NOT USED 15



INTERIOR DOOR JAMBS SCALE: 3"=1'-0" 10



TOP PLATE AT ROOF HEADER SCALE: 3"=1'-0" 5

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL
THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC. (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**ARCHITECTURAL
DETAILS
WOOD STUD - SHTG**

REVISIONS

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL

Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER

A-5.50

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
**ARCHITECTURAL
 DETAILS
 FLOOR**

REVISIONS

1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION
 FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-121999 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 08/31/2023

PC STATE AGENCY APPROVAL




MODULAR BUILDING DESIGN PROFESSIONAL


SILVER CREEK INDUSTRIES
 24' x 40' PC

PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023
 P.C. SHEET NUMBER


A-5.70




FLOOR AT SEPARATION (WOOD FLOOR) SCALE: 1 1/2"=1'-0" 6




SKIRT FLASHING (WOOD FLOOR) SCALE: 1 1/2"=1'-0" 7




SKIRT FLASHING (WOOD FLOOR) SCALE: 1 1/2"=1'-0" 2




FLOOR AT MODLINE (WOOD FLOOR) SCALE: 1 1/2"=1'-0" 3



THRESHOLD SCALE: 3"=1'-0" 4




FLOOR AT SEPARATION (WOOD FLOOR) SCALE: 1 1/2"=1'-0" 6




SKIRT FLASHING (WOOD FLOOR) SCALE: 1 1/2"=1'-0" 7




SKIRT FLASHING (WOOD FLOOR) SCALE: 1 1/2"=1'-0" 2




FLOOR AT MODLINE (WOOD FLOOR) SCALE: 1 1/2"=1'-0" 3




THRESHOLD SCALE: 3"=1'-0" 4




FLOOR AT SEPARATION (CONCRETE FLR) SCALE: 1 1/2"=1'-0" 16




SKIRT FLASHING (CONCRETE FLOOR) SCALE: 1 1/2"=1'-0" 11




SKIRT FLASHING (CONCRETE FLOOR) SCALE: 1 1/2"=1'-0" 12



FLOOR AT MODLINE (CONCRETE FLOOR) SCALE: 1 1/2"=1'-0" 13



THRESHOLD SCALE: 3"=1'-0" 14




FLOOR AT SEPARATION (CONCRETE FLR) SCALE: 1 1/2"=1'-0" 16




SKIRT FLASHING (CONCRETE FLOOR) SCALE: 1 1/2"=1'-0" 11



SKIRT FLASHING (CONCRETE FLOOR) SCALE: 1 1/2"=1'-0" 12



FLOOR AT MODLINE (CONCRETE FLOOR) SCALE: 1 1/2"=1'-0" 13



THRESHOLD SCALE: 3"=1'-0" 14


NOTE:

1. WHEN THE BUILDING IS INSTALLED AT GROUND LEVEL (BELOW GRADE FOUNDATION OPTION) DETAILS 1, 2, 5, 11, 12+15 CAN ONLY BE USED WHERE THE BUILDING SIZE DOES NOT EXCEED 2,160 SF. SEE SHEETS A-5.71 THRU A-5.78 FOR ALTERNATE FLASHING DETAILS FOR BUILDINGS LARGER THAN 2,160 SF.
2. THE DETAILS ON SHEETS A-5.71 THRU A-5.78 MAY BE USED FOR BUILDINGS LESS THAN 2,160 SF.
3. FOR BUILDINGS INSTALLED ON ABOVE GRADE FOUNDATION SYSTEMS (WOOD FOUNDATION OR CONCRETE FOUNDATION WITH ABOVE GRADE STEMWALL) THE DETAILS SHOWN ON THIS SHEET MAY BE USED FOR ANY SIZE BUILDING.
4. FOR BUILDINGS INSTALLED ON ABOVE GRADE FOUNDATION SYSTEMS (WOOD FOUNDATION OR CONCRETE FOUNDATION WITH ABOVE GRADE STEMWALL) THE FLATWORK/PAVING/MOW STRIP WHICH IS INDICATED IN THE DETAILS ON THIS SHEET SHALL BE OMITTED.

WALL BASE AT TOILET ROOMS SCALE: 1 1/2"=1'-0" 10

TYPICAL SILL AT FLOOR (CONCRETE FLOOR) SCALE: 1 1/2"=1'-0" 15


TYPICAL SILL AT FLOOR (WOOD FLOOR) SCALE: 1 1/2"=1'-0" 5




T.V. BLOCKING ATTACHMENT AT WOOD STUD SCALE: 1/2" = 1'-0" 16




NOT USED SCALE: 1/2" = 1'-0" 11




TALL CABINET WALL ANCHORAGE SCALE: 1 1/2" = 1'-0" 7




BASE CABINET WALL ANCHORAGE SCALE: 1" = 1'-0" 1




T.V. BLOCKING ATTACHMENT AT STEEL STUD SCALE: 1/2" = 1'-0" 17




WALL OPENING AT HEADER AND JAMB SCALE: 3" = 1'-0" 12




ATTACHMENT TO BLOCKING - CONC. FLOOR SCALE: 3" = 1'-0" 8




WALL HUNG ANCHORAGE CABINET SCALE: 1 1/2" = 1'-0" 2




PROJECTION SCREEN MOUNTING SCALE: NTS 18




MARKER BOARD ATTACHMENT SCALE: 3" = 1'-0" 14




ATTACHMENT TO BLOCKING - WOOD FLOOR SCALE: 3" = 1'-0" 3



ACCESSIBLE COUNTER SCALE: 1" = 1'-0" 4




ATTACHMENT TO BLOCKING PLATE SCALE: 3" = 1'-0" 19



TEACHING WALL - ELEVATION / SECTION - OPTION SCALE: 3/8" = 1'-0" 15



NOT USED SCALE: 3" = 1'-0" 10



NOT USED SCALE: 1" = 1'-0" 5

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL
THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc.) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**ARCHITECTURAL
DETAILS
MISCELLANEOUS/OPTIONS**

REVISIONS

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

















PC STATE AGENCY APPROVAL

Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER
A-5.80



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL
THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**ARCHITECTURAL
DETAILS
MISCELLANEOUS/OPTIONS**

REVISIONS

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL



MODULAR BUILDING DESIGN PROFESSIONAL



SILVER CREEK INDUSTRIES
24' x 40' PC
PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER

A-5.81

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc.) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
 ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
**INTERIOR ELEVATION
 24' x 40'**

REVISIONS

1	
2	
3	
4	

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

~~IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-121999 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 08/31/2023~~

~~PC STATE AGENCY APPROVAL~~



Silver Creek

2830 BARRETT AVE PERRIS, CALIFORNIA 92571
 PHONE: 951-943-5393 FAX: 951-943-2211



MODULAR BUILDING DESIGN PROFESSIONAL



SILVER CREEK INDUSTRIES
 24' x 40' PC

PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023

P.C. SHEET NUMBER
A-6.01





FRONT ELEVATION

REAR ELEVATION

SCALE: 1/4" = 1' - 0" 1

REFER TO PROJECT SPECIFIC SHEET A-6.01N







SIDE ELEVATION

SIDE ELEVATION

SCALE: 1/4" = 1' - 0" 4

SCALE: 1/4" = 1' - 0" 2

KEY PLAN VENTING CALCULATIONS w/o PARAPET



WOOD FOUNDATION PLATE SCHEDULE

50 + 15 PSF

PLATES	END WALL	SIDE WALL	MODLINE PAD AT END WALL	MODLINE PAD AT INTERIOR	SEPARATION PAD AT ENDWALL		SEPARATION PAD AT INTERIOR	
					SEPARATE	CONTINUOUS	SEPARATE	CONTINUOUS
ADDITIONAL (AS NEEDED)	2x4	2x4	2x6	2x6	(2) ROWS OF 2x4	2x12	(2) ROWS OF 2x4	2x12
TOP	2x6	2x6	2x8	2x8	(2) ROWS OF 2x6	2x12	(2) ROWS OF 2x6	2x12
BLOCK	2x8	2x8	2x10	2x10	(2) ROWS OF 2x8	2x12	(2) ROWS OF 2x8	2x12
SILL	2x12 (2x14) ¹⁵	2x12 (2x14) ¹⁵	2x12 x 2'-0"	2x12 x 2'-0"	(2) ROWS OF 2x14	(9) 2x12 x 2'-0"	(2) ROWS OF 2x14	(8) 2x12 x 2'-0"

KEY PLAN VENTING SCHEDULE

VENT "A" (SIDEWALL): 3'-6" x 6" = 1.75 S.F. VENTILATION
 "VENT OPENING BELOW CONT UPPER PLATE"


VENT "B" (ENDWALL): 3'-0" x 3" = 0.88 S.F. VENTILATION
 (OPTIONAL AT MULTIPLE BLDG SETS)
 "VENT OPENING ABOVE CONT. SILL AND BLOCK PLATE"

VENT "C" (ENDWALL): 3'-0" x 4 1/2" = 1.125 S.F. VENTILATION
 (OPTIONAL AT MULTIPLE BLDG SETS)
 "VENT OPENING ABOVE CONT. SILL AND BLOCK PLATES"

VENT "D" (ENDWALL): 3'-0" x 6" = 1.5 S.F. VENTILATION
 (OPTIONAL AT MULTIPLE BLDG SETS)
 "VENT OPENING ABOVE CONT. SILL AND BLOCK PLATES"

NOTE:
 @ BUILDINGS WITH PARAPETS UP TO 48" HIGH, SIDE WALL VENTS CHANGE FROM 3'-6" TO 3'-0", SEE VENTING SCHEDULE

FOUNDATION PLATE DESCRIPTION



NOTES

- BUILDINGS OVER 2,160 SF, MUST BE INSTALLED ON A PERMANENT CONCRETE FOUNDATION PER IR 16-1 ITEM 1.4.
- FOUNDATION PLAN HAS A 1/4" ADDED AT EACH MODULE LINE AND DOES NOT MATCH THE FLOOR PLAN. ADDITIONAL ALLOWED FOR GROWTH THAT IS EXPERIENCED WHEN SETTING MULTIPLE MODULAR FLOORS.
- FOUNDATION VENTS THAT OCCUR UNDER RAMP LANDINGS, PROVIDE AN EQUAL AREA OF SCREENED VENT IN LANDING SKIRT.
- WOOD SILL (FOOTING) PLATES SHALL BE PRESSURE TREATED HEM-FIR AND MAY BEAR DIRECTLY ON SOIL OR PAVED SURFACE. GRASS OR TURF SHALL BE CLEARED TO BARE SOIL UNDER THE ENTIRE AREA OF THE BUILDING BY OTHERS. THE WOOD SILL FOOTING PLATE MAY SUPPORT CONTINUOUS BLOCKING AND SHEATHING SKIRT WHICH NEED NOT BE TREATED.
- SILL RESTRAINT:
 THE FOUNDATION SHALL BE DESIGNED TO PREVENT SLIDING ON THE SUPPORTING SURFACE BY ATTACHING THE WOOD FOUNDATION PLATES FOR THE BUILDING, RAMPS AND STAIRS TO THE GROUND WITH RESTRAINING DEVICES. AN ACCEPTABLE DESIGN WOULD INCORPORATE ONE-INCH DIAMETER STANDARD WEIGHT (1.315" ACTUAL O.D.) HOT DIPPED GALVANIZED PIPES OR ONE-INCH DIAMETER SOLID STEEL RODS SPACED AT NOT MORE THAN 10'-0" O.C. ONE PIPE / ROD SHALL BE LOCATED A MAXIMUM OF TWO FEET FROM EACH CORNER IN BOTH DIRECTIONS AND A MINIMUM OF TWO PIPES / RODS PER DISCONTINUOUS FOUNDATIONS STRIP. PIPES SHOULD PENETRATE INTO SOIL, CONCRETE, AND/OR PAVING A MINIMUM OF 12" MEASURED VERTICALLY. ALTERNATE OR EQUIVALENT DESIGNS, WHEN PROVIDED WITH STRUCTURAL CALCULATIONS AND DETAILS, WILL BE SUBMITTED TO DSA FOR REVIEW AND APPROVAL.
- STACKED WOOD MEMBERS FOR FOUNDATIONS AND PRESSURE TREATED LUMBER SHALL BE NAILED WITH HOT DIPPED GALVANIZED PER ASTM A-153.
- VENTILATION OPENINGS SHALL BE COVERED FOR EITHER HEIGHT AND WIDTH WITH CORROSION - RESISTANT WIRE MESH, WITH A CLEAR "THROUGH" DIMENSION NOT EXCEEDING 1/8" ACTING AS A VERMIN BARRIER.
- VENTING CALCULATION REQUIREMENTS FOR MULTIPLE BUILDING SETS MUST BE CALCULATED WITH OVERALL SQUARE FOOTAGE INCLUDING SEPARATION.
- FOR FOUNDATION ANCHORAGE ON CONCRETE PAD, SEE DETAIL 15/F-0.50.
- IF OPTIONAL ENDWALL VENTS ARE APPLIED, SILL PLATE AND BLOCK PLATE MUST BE CONTINUOUS. VENT OPENINGS SHALL BE BROKEN ABOVE THE BLOCK PLATE.
- FOR FOUNDATION SPLICE - SEE SIF-0.50.
- CRAWLSPACE VAPOR RETARDERS (WHERE INDICATED):
 THE OPTIONAL TOTAL AREA OF VENTILATION OPENINGS IS PERMITTED TO BE REDUCED TO 1/1500 FACTOR WITH AN APPROVED VAPOR RETARDER MATERIAL PER CBC SECTION 1202.4.1.2.
 MATERIALS:
 GROUND SURFACE COVERED WITH AN APPROVED VAPOR RETARDER MATERIAL; MUST HAVE A PERM RATING OF ONE OR LESS; SHOULD BE CONTINUOUS; POLYETHYLENE FILM (6 MIL), POOL LINER (PUNCTURE RESISTANT); AND POLYETHYLENE FILM WITH RAT SLAB INSTALLATION RECOMMENDATIONS.
 OVERLAP JOINTS BY 6 INCHES, TAPE OR SEAL ALL JOINTS; ATTACH VAPOR RETARDER OVER SILL PLATE PER 10/F-0.50; SEAL TO ALL PIERS AND OTHER PENETRATIONS.
- ENDWALL VENTS (IF REQ'D) SHALL BE LOCATED A MIN OF 24" FROM BUILDING CORNERS. MAXIMUM ONE ENDWALL VENT PER 12'-0" MODULE.
- CONCRETE FLOOR LOAD IS INCLUDED IN THE CONCRETE FOUNDATION OPTION FOR FOUNDATION & ANCHORAGE DESIGN. I.E. THERE IS NO CONCRETE FLOOR FOR WOOD FOUNDATION OPTION. THERE IS CONCRETE FLOOR FOR CONCRETE FOUNDATION OPTION.
- IF PARAPET IS HIGHER THAN 18". COMBINATION REQUIRES A 2 X 14" OR 2 X 16" SILL PLATE @ EXTERIOR OF BUILDING.
- 150 PSF FLOOR LIVE LOAD OPTION CANNOT BE USED WITH THE STUCCO WALL OR PARAPET OPTION.
- VENTS AT MODLINE FOUNDATIONS. THE MINIMUM CRITERIA REQUIREMENT AS FOLLOWS:
 A. VENTS HAVE A MINIMUM OF 2 SILL / BLOCKING PLATES BENEATH.
 B. VENTS ARE A MAXIMUM OF 6'-0" LONG X 3" MIN. HIGH.
 C. VENTS ARE SPACED A MINIMUM OF 8'-0" APART (EDGE TO EDGE) AND 24" MIN. FROM CORNERS.
- WHERE THE BUILDING OCCURS ON OR ADJACENT TO A SLOPE (GREATER THAN 33%) THE SETBACK SHALL COMPLY WITH CBC SECTION 1808A.7. THE MINIMUM SETBACK AT THE TOP OF THE SLOPE SHALL BE NOT LESS THAN SMALLER OF 40'-0" OR 1/3 THE HEIGHT OF THE SLOPE. THE MINIMUM SETBACK AT THE BOTTOM OF THE SLOPE SHALL BE NOT LESS THAN THE SMALLER OF 15'-0" OR 1/2 THE HEIGHT OF THE SLOPE. THE SETBACK DISTANCES INDICATED HERE MAY BE REDUCED WHEN A SITE SPECIFIC GEOTECHNICAL REPORT IS PROVIDED.

NAILING SCHEDULE

BUILDING SIZE	(2) 16d BOX NAILS PLATE TO PLATE ATTACHMENT BELOW UPPER MOST PLATE
24' x 40'	5" OC AT ENDWALL - 1 / F-0.50 12" OC AT SIDEWALL - 2 / F-0.50 10" OC AT SEPARATION - 4 / F-0.50

VENTING SCHEDULE

W/O PARAPET	BUILDING SIZE	BUILDING AREA	REQ. VENTING	SIDE VENTING	END VENTING	TOTAL VENTING SUPPLIED
W/O PARAPET	24' x 40'	960 SF	6.4 SF (1/150)	3'-6" x 6" = (4) 1.75 SF/EA	-	7.0 SF
W/ PARAPET	24' x 40'	960 SF	6.4 SF (1/150) SILEX (6 SF TOTAL SILEX) (7.5 SF TOTAL)	3'-0" x 6" = (4) 1.5 SF/EA	(8) 1.5 SF/EA	7.5 SF

TIE PLATE SCHEDULE

BUILDING SIZE	SIDE WALL TIE PLATES	END WALL TIE PLATES	TOTAL NUMBER OF TIE PLATES
24' x 40'	4	7	22

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR:
 SS FLS ACS
 DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM INC) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM INC. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM INC SHALL BE THE PROPERTY OF SCM INC.

PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
**WOOD
 FOUNDATION PLAN
 24x40
 (50+15 PSF)**

REVISIONS

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION
 FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-121999 INC:
 REVIEWED FOR:
 SS FLS ACS
 DATE: 08/31/2023

PC STATE AGENCY APPROVAL





Silver Creek
 2830 BARRETT AVE PERRIS, CALIFORNIA 92571
 PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
 24' x 40' PC

PROJECT NO:
 DRAWN BY: AS NOTED
 DATE: 02-27-2023

P.C. SHEET NUMBER
F-0.02



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL





THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc.) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.

ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**FOUNDATION
DETAILS
WOOD**




REVISIONS






PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL



SILVER CREEK INDUSTRIES
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211







MODULAR BUILDING DESIGN PROFESSIONAL

REGISTERED PROFESSIONAL ENGINEER
JOHN W. STARBUCK
STRUCTURAL
STATE OF CALIFORNIA


SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER



PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER

F-0.50



NOTE:
 * SEE BEAM AND COLUMN SCHEDULE ON SHEETS S-3.01 THRU S-3.02 FOR APPLICABLE FLOOR BEAM SIZE

- NOTES:**
- FOR FLOOR BLOCKING SEE DETAILS 4.7B / S-1.50 (STD), 4.7A / S-1.50 (ALT)
 - FOR BUILDINGS ON WOOD FOUNDATION SYSTEMS, PROVIDE 1 1/16" DIA. HOLE AT BOTTOM FLANGE OF FLOOR BEAM FOR LAG SCREW ATTACHMENT TO FOUNDATION PLATES BELOW. FOR EXACT HOLE LOCATIONS, SEE FOUNDATION PLAN.
 - FLOOR SHEATHING SHALL BE PRESSURE TREATED WOOD OR NATURALLY DURABLE IF BOTTOM OF PLYWOOD IS LESS THAN 18" CLEAR FROM EXPOSED EARTH.
 - HSS COLUMN SCHEDULES ON SHEETS S-3.01 THRU S-3.02

FLOOR JOIST TABLE

	LIVE LOAD PSF	JOIST SPACING	
		CLASSROOM <input checked="" type="checkbox"/>	OFFICE <input type="checkbox"/>
<input type="checkbox"/>	50	48"	48" DBL JOIST
<input type="checkbox"/>	50	32"	32" DBL JOIST
<input type="checkbox"/>	50	24"	24" DBL JOIST
<input type="checkbox"/>	50	16"	16" DBL JOIST
<input checked="" type="checkbox"/>	50 + 15	32"	
<input type="checkbox"/>	50 + 15	24"	
<input type="checkbox"/>	50 + 15	16"	
<input type="checkbox"/>	100	24"	
<input type="checkbox"/>	100	16"	
<input type="checkbox"/>	150	16"	

- FLOOR SHEATHING**
- PRESSURE TREATED
 - NON-PRESSURE TREATED
- NOTE:**
 PRESSURE TREATED SHEATHING SHALL ONLY BE PROVIDED WHEN WOOD FOUNDATIONS ARE USED AND EXPOSED EARTH OCCURS WITHIN THE FOUNDATION AT A DISTANCE OF LESS THAN 18" BELOW THE UNDERSIDE OF THE FLOOR SHEATHING. SEE 16IF-0.50 FOR ADDITIONAL INFORMATION.

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC. (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
**FLOOR FRAMING PLAN
 WOOD FLOOR**

REVISIONS

1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-121999 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 08/31/2023

PC STATE AGENCY APPROVAL

Silver Creek
 2830 BARRETT AVE PERRIS, CALIFORNIA 92571
 PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
 24' x 40' PC

PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023

P.C. SHEET NUMBER
S-1.01

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM INC) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM INC
 ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM INC SHALL BE THE PROPERTY OF SCM INC

PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
**FLOOR FRMNG
 DETILS
 WOOD FLOOR**

REVISIONS

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION
 FOR CONSTRUCTION IS REQUIRED

~~IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-121999 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 08/31/2023~~

~~PC STATE AGENCY APPROVAL~~

Silver Creek
 2830 BARRETT AVE PERRIS, CALIFORNIA 92571
 PHONE: 951-943-5393 FAX: 951-943-2211



MODULAR BUILDING DESIGN PROFESSIONAL

John W. Starling
 REGISTERED PROFESSIONAL ENGINEER
 STRUCTURAL
 STATE OF CALIFORNIA

SILVER CREEK INDUSTRIES
 24' x 40' PC




PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023

P.C. SHEET NUMBER
S-1.50



16 MODULE LINE - BOLTED CONNECTION SCALE: 3"=1'-0" 11


SHIPPING HOLD DOWN DETAIL SCALE: 3"=1'-0" 6





17 MODULE LINE CONNECTION (OPTION 1) SCALE: 3"=1'-0" 12

FLOOR JOIST SCALE: 3"=1'-0" 7B

FLOOR JOIST SCALE: 3"=1'-0" 7A




FLOOR BEAM TO COLUMN CONNECTION SCALE: 1 1/2"=1'-0" 2




18 MODULE LINE CONNECTION (OPTION 2) SCALE: 3"=1'-0" 14


FLOOR JOIST HOLES (OPTIONAL) SCALE: 1/8"=1'-0" 8




CORNER CONNECTION SCALE: 3"=1'-0" 3



19 MODULE LINE CONNECTION (OPTION 2) SCALE: 3"=1'-0" 14




BLOCKING TO END BEAM SCALE: 3"=1'-0" 4



20 FLOOR BEAM SPLICE SCALE: 3"=1'-0" 15



NOT USED 10



JOIST TO SIDE BEAM SCALE: 3"=1'-0" 5

NOTES

- FOR WALL MOUNTED HVAC UNIT, PROVIDE OPENING THROUGH REAR ROOF HEADER WHERE IT OCCURS. SEE FLOOR PLAN FOR HVAC LOCATION. SEE 5.15 / S-2.50 ~~OR S-2.60~~ FOR DETAILS.
- PROVIDE ADDITIONAL JOIST FOR FIRE SPRINKLER LINE AS NEEDED. LOCATION OF FIRE SPRINKLER PURLIN TO BE DETERMINED BY SITE STIFFENER PLATE OR ANGLE BRACE REQUIRED AT THIS LOCATION. FOR FIRE SPRINKLER LINE SIDE BEAM PENETRATION, SEE 14 / S-2.50 ~~OR S-2.60~~ FOR DETAILS.
- FOR OPTIONAL SIDE BEAM OPENING SEE 10, 15/S-2.50 ~~OR S-2.60~~ FOR DETAILS.



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**ROOF FRAMING PLAN
MONO SLOPE**

REVISIONS

1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL




Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023

P.C. SHEET NUMBER
S-2.01



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc




ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

NOT USED 16

ROOF PURLIN SCALE: 6"=1'-0"

TYPICAL PURLIN CONNECTION DETAIL SCALE: 3"=1'-0"

COLUMN AT ROOF - PLAN SCALE: 3"=1'-0"






NOT USED 17

ROOF HEADER SCALE: NTS

BEAM SPLICE SCALE: 3"=1'-0"

COLUMN AT ROOF - SECTION SCALE: 3"=1'-0"





NOT USED 18

SIDE BEAM SCALE: NTS

PURLIN TO ROOF BEAM @ STIFFENER SCALE: 3"=1'-0"

COLUMN AT ROOF OVERHANG SCALE: 3"=1'-0"






NOT USED 19

SIDEWALL BEAM PENETRATION SCALE: 1 1/2"=1'-0"

MODULE CONNECTION AT ROOF (OPTION) SCALE: 3"=1'-0"

NOT USED 4



NOT USED 20

WEB OPENING AT ROOF BEAM (OPTION) SCALE: 3"=1'-0"

OPENING AT ROOF BEAM (OPTION) SCALE: 1 1/2"=1'-0"

OPENING AT HEADER SCALE: 1 1/2"=1'-0"

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**ROOF FRAMING
DETAILS
MONO SLOPE**

REVISIONS

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL



MODULAR BUILDING DESIGN PROFESSIONAL



SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER
S-2.50

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
 ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**


SHEET TITLE:
**ROOF FRAMING
 DETAILS**

REVISIONS

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION
 FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-121999 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 08/31/2023

PC STATE AGENCY APPROVAL



Silver Creek
 2830 BARRETT AVE PERRIS, CALIFORNIA 92571
 PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL




SILVER CREEK INDUSTRIES
 24' x 40' PC


PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023

P.C. SHEET NUMBER


S-2.60




REF: S2.01, ~~S2.02, S2.11, S2.12~~
REAR OVERHANG SECTION SCALE: 1/2" = 1'-0" **11**




REF: S2.01 - S2.03; S211 - S213
HVAC CURB ATTACHMENT SCALE: 3/4" = 1'-0" **6**




REF: S3.01
SOFFIT JOIST TO OVERHANG BEAM SCALE: 3" = 1'-0" **1**




REF: S2.01, ~~S2.02~~
FRONT OVERHANG SECTION - MONO SLOPE SCALE: 3/4" = 1'-0" **12**




SCALE: 3/4" = 1'-0" **7**




REF: S3.01
SOFFIT ANGLE TO HEADER CONNECTION SCALE: 3" = 1'-0" **2**




REF: S2.11, S2.13
FRONT OVERHANG SECTION - DUAL SLOPE SCALE: 3/4" = 1'-0" **13**




SCALE: 3/4" = 1'-0" **8**




REF: S2.01, ~~S2.02, S2.11, S2.12~~
OVERHANG FASCIA TO BEAM CONNECTION SCALE: 6" = 1'-0" **3**



CANOPY SECTION



REF: S2.01 - S2.03; S211 - S213
DOUBLE PURLINS AT HVAC SCALE: 1 1/2" = 1'-0" **9**




REF: S2.01, ~~S2.02, S2.11, S2.12~~, S3.01
SOFFIT JOIST SCALE: 6" = 1'-0" **4**



OPTIONAL CANOPY SCALE: 1 1/2" = 1'-0" **20**



REF: S2.01, ~~S2.02, S2.11, S2.12~~
OVERHANG FASCIA & BEAM SCALE: 3" = 1'-0" **5**



CANOPY ISOMETRIC SCALE: 1 1/2" = 1'-0" **20**

NOT USED **16**

NOT USED **17**

NOT USED **14**

NOT USED **15**

NOT USED **10**

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 02-122160 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
**ROOF FRAMING
 DETAILS
 TRUSS**


REVISIONS

1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION
 FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 APP: 04-121999 INC:
 REVIEWED FOR
 SS FLS ACS
 DATE: 08/31/2023

PC STATE AGENCY APPROVAL



Silver Creek
 2830 BARRETT AVE PERRIS, CALIFORNIA 92571
 PHONE: 951-943-5393 FAX: 951-943-2211


MODULAR BUILDING DESIGN PROFESSIONAL





SILVER CREEK INDUSTRIES
 24' x 40' PC

PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023
 P.C. SHEET NUMBER


S-2.90





TYP. VERTICAL & DIAGONAL (U.N.O.) SCALE: 1 1/2" = 1'-0" 6




FILLET WELD TERMINATION 7A CONNECTION @ MODULE LINE 7 MONO SLOPE TRUSS SCALE: 1/2" = 1'-0" 1




BRACE @ TRUSS & MATING LINE SCALE: 1 1/2" = 1'-0" 8



PURLIN TO VERT. ANGLE CONN. 9B PURLIN TO TRUSS CONN. SCALE: 3" = 1'-0" 9A



TRUSS TO COLUMN / OH FRAME CONN. SCALE: 1 1/2" = 1'-0" 10




- NOTES:
- SEE SHEET S-0.1 FOR STEEL GRADES.
 - REQUIRED ELECTRODES FOR ALL WELDS TO BE E-70
 - VOLTAGE & AMPERAGE SHALL BE PER ELECTRODE MANUFACTURERS SPECIFICATIONS
 - BOLTS AND NUTS GRADES TO BE A307
- REF: ROOF FRAMING PLAN

TRUSS MARK:

	Y=
A TOP CHORD	4" x 4" x 3/8" (LLV) 1 1/4
B BOTTOM CHORD	4" x 4" x 3/8" (LLV) 1 1/4
C END DIAGONALS (2 EACH END)	2" x 2" x 10 GA. 9/16
D TYPICAL DIAGONALS	1 1/2" x 1 1/2" x 10 GA. 7/16
E END VERTICAL (2 EACH END)	1 1/2" x 1 1/2" x 10 GA. 7/16
F TYPICAL VERTICALS	1 1/2" x 1 1/2" x 10 GA. 7/16

NOTE: "Y" MAY BE 1/4" MAX. OUT OF ALIGNMENT

FILLET WELD TERMINATION 7A CONNECTION @ MODULE LINE 7 MONO SLOPE TRUSS SCALE: 1/2" = 1'-0" 1




- NOTES:
- SEE SHEET S-0.1 FOR STEEL GRADES.
 - REQUIRED ELECTRODES FOR ALL WELDS TO BE E-70
 - VOLTAGE & AMPERAGE SHALL BE PER ELECTRODE MANUFACTURERS SPECIFICATIONS
 - BOLTS AND NUTS GRADES TO BE A307
- REF: ROOF FRAMING PLAN

TRUSS MARK:


	Y=
A TOP CHORD	4" x 4" x 3/8" (LLV) 1 1/4
B BOTTOM CHORD	4" x 4" x 3/8" (LLV) 1 1/4
C END DIAGONALS (2 EACH END)	2" x 2" x 10 GA. 9/16
D TYPICAL DIAGONALS	1 1/2" x 1 1/2" x 10 GA. 7/16
E END VERTICAL (2 EACH END)	1 1/2" x 1 1/2" x 10 GA. 7/16
F TYPICAL VERTICALS	1 1/2" x 1 1/2" x 10 GA. 7/16

NOTE: "Y" MAY BE 1/4" MAX. OUT OF ALIGNMENT


PURLIN TO VERT. ANGLE CONN. 9B PURLIN TO TRUSS CONN. SCALE: 3" = 1'-0" 9A DUAL SLOPE TRUSS SCALE: 1/2" = 1'-0" 2




VERT. & DIAG. AT MID-POINT SCALE: 1 1/2" = 1'-0" 5



VERT. & DIAG. AT MID-POINT SCALE: 1 1/2" = 1'-0" 4




TRUSS CHORD SPLICE SCALE: 3" = 1'-0" 3



BUILDING SECTION


SCALE: 1/2" = 1'-0" 1



BUILDING SECTION

SCALE: 1/2" = 1'-0" 3

ENCL. SOFFIT PLAN-OPT.



SCALE: 3/8" = 1'-0" 2

NOTES

1. ALL INFORMATION SUCH AS DETAILS, SECTIONS, CONNECTIONS, AND MATERIAL ATTACHMENT SHALL BE REFERENCED FROM OTHER SHEETS WITHIN THIS SET WHERE IT APPLIES.


FLOOR CONSTRUCTION

- WOOD FLOOR
- CONCRETE FLOOR

HSS COLUMN SCHEDULE

COLUMN HEIGHT	NO PARAPET	ROOF W/ PARAPET
<input checked="" type="checkbox"/> 9'-0"	<input checked="" type="checkbox"/> 6 x 6 x 1/4	<input type="checkbox"/> 6 x 6 x 1/4 *
<input type="checkbox"/> 9'-6"	<input type="checkbox"/> 6 x 6 x 1/4	<input type="checkbox"/> 6 x 6 x 1/4 *
<input type="checkbox"/> 10'-0"	<input type="checkbox"/> 6 x 6 x 1/4	<input type="checkbox"/> 6 x 6 x 1/4 *
<input type="checkbox"/> 10'-6"	<input type="checkbox"/> 6 x 6 x 1/4	<input type="checkbox"/> 6 x 6 x 1/4 *

FLOOR BEAM
 C7x9.8 (TYP) PERIMETER BEAM FOR WOOD FLOOR
 *C9x13.4 PERIMETER BEAM FOR WOOD FLOOR
 C10x16.0 TYP PERIMETER BEAM FOR CONCRETE FLOOR



PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc


PROJECT NAME:
**SYLVAN USD
 FREEDOM E.S.
 (2) 24' x 40'
 CLASSROOM BUILDINGS**

SHEET TITLE:
**BUILDING SECTIONS
 MONO SLOPE**


REVISIONS

1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT
 CODE: 2022 CBC
 A SEPARATE PROJECT APPLICATION
 FOR CONSTRUCTION IS REQUIRED




PC STATE AGENCY APPROVAL




SILVER CREEK INDUSTRIES
 24' x 40' PC

PROJECT NO:
 DRAWN BY:
 SCALE: AS NOTED
 DATE: 02-27-2023


P.C. SHEET NUMBER
S-3.01




TYPICAL SIDE WALL




TYPICAL END WALL




TYPICAL HVAC



FIRE EXTINGUISHER CABINET BLOCKOUT



TYPICAL DOOR




TYPICAL WINDOW

NOTES

WALL HEIGHT SCHEDULE

COLUMN HEIGHT	9'-0"	9'-6"	10'-0"	10'-6"
CONCRETE FLOOR	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
WOOD FLOOR	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

NOTE:
ALL EXTERIOR WALL FRAMING SHALL BE 2x6 (MIN).
EXCEPTION: UNCONDITIONED RESTROOM MODULES MAY UTILIZE 2x4 FRAMING.



PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc


PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**WALL FRAMING
ELEVATIONS
WOOD STUDS**

REVISIONS

1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED



PC STATE AGENCY APPROVAL



Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211


MODULAR BUILDING DESIGN PROFESSIONAL




SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023


P.C. SHEET NUMBER
S-5.00




PARTITION CONNECTION AT CONC FLOOR SCALE: 3\"/>



PARTITION CONNECTION AT WOOD FLOOR SCALE: 3\"/>



VERTICAL SHEATHING LAP JOINT SCALE: 3\"/>



OPTIONAL BOLTED WALL TO FLOOR SCALE: NTS

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL
THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**WALL FRAMING
DETAILS
WOOD STUDS**

REVISIONS

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL


Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL


SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023


P.C. SHEET NUMBER
S-5.10




WALL SILL AT CONCRETE FLOOR SCALE: 3\"/>



WALL SILL AT WOOD FLOOR SCALE: 3\"/>




VERTICAL SHEATHING BUTT JOINT SCALE: 3\"/>




COLUMN AT ENDWALL (2x6) SCALE: 3\"/>

COLUMN HEIGHT	OPENING SIZE	EXT FINISH	HEADER				SILL				FULL HEIGHT KING STUD			
			NUMBER	SIZE	LUMBER	TYPE	NUMBER	SIZE	LUMBER	TYPE	NUMBER	SIZE	LUMBER	TYPE
LESS THAN 9'-6"	3070	NO PLASTER	(1)	2X4	HF	#2	N/A				(2)	2X4	HF	#2
		NO PLASTER (OPT)	(1)	2X4	DF	#2	N/A				(2)	2X4	DF	#2
		PLASTER	(2)	2X4	DF	#2	N/A				(3)	2X4	DF	#2
9'-6" TO 10'-6"	3070	NO PLASTER	(1)	2X4	HF	#2	N/A				(2)	2X4	HF	#2
		NO PLASTER (OPT)	(1)	2X4	DF	#2	N/A				(2)	2X4	DF	#2
		PLASTER	(2)	2X4	DF	#2	N/A				(3)	2X4	DF	#2


NOTE:
OPENINGS LARGER THAN 3'x7' ARE NOT PERMITTED IN 2x4 WALLS WITH PLASTER FINISH.



DOOR/WINDOW HEADER AND JAMB SCALE: 1 1/2\"/>




COLUMN AT ENDWALL (2x4) SCALE: 3\"/>




HORIZONTAL SHEATHING JOINT SCALE: 3\"/>


COLUMN HEIGHT	OPENING SIZE	EXT FINISH	HEADER				SILL				FULL HEIGHT KING STUD			
			NUMBER	SIZE	LUMBER	TYPE	NUMBER	SIZE	LUMBER	TYPE	NUMBER	SIZE	LUMBER	TYPE
9'-6" TO 10'-6"	3070	NO PLASTER	(1)	2X4	HF	#2	N/A				(2)	2X4	HF	#2
		NO PLASTER (OPT)	(1)	2X4	DF	#2	N/A				(2)	2X4	DF	#2
		PLASTER	(2)	2X4	DF	#2	N/A				(3)	2X4	DF	#2



WINDOW SILL AND JAMB SCALE: 3\"/>




LET-IN BLOCK ATTACHMENT SCALE: 3\"/>



SECTION AT SHEATHING TO STUD ATTACHMENT SCALE: 3\"/>

COLUMN HEIGHT	EXT FINISH	WOOD WALL FRAMING				4' CORNER OF WOOD WALL FRAMING (ZONE 5)			
		NUMBER	SIZE	LUMBER	TYPE	OC	NUMBER	SIZE	LUMBER
LESS THAN 9'-6"	NO PLASTER	(1)	2X4	HF	#2	16\"/>			
	NO PLASTER (OPT)	(1)	2X4	DF	#2	16\"/>			
	PLASTER	(1)	2X4	DF	#2	16\"/>			
9'-6" TO 10'-6"	NO PLASTER	(1)	2X4	HF	#2	16\"/>			
	NO PLASTER (OPT)	(1)	2X4	DF	#2	16\"/>			
	PLASTER	(1)	2X4	DF	#2	16\"/>			


NOTES:
1. 2X4 WALL FRAMING NOT PERMITTED FOR STUCCO FINISH WALLS OVER 9'-0" TALL
2. 2X4 EXTERIOR WALL FRAMING IS ONLY PERMITTED AT UNCONDITIONED RESTROOM MODULES
3. 2X4 INTERIOR WALLS SHALL BE HF #2 (OR BETTER) AND SHALL BE SPACED NOT MORE THAN 24" OC MAX



TOP PLATE AT ROOF BEAM SCALE: 3\"/>







NOT USED



COLUMN AT ENDWALL (2x8) SCALE: 3\"/>

COLUMN HEIGHT	EXT FINISH	WOOD WALL FRAMING				4' CORNER OF WOOD WALL FRAMING (ZONE 5)			
		NUMBER	SIZE	LUMBER	TYPE	OC	NUMBER	SIZE	LUMBER
LESS THAN 9'-6"	NO PLASTER	(1)	2X4	HF	#2	16\"/>			
	NO PLASTER (OPT)	(1)	2X4	DF	#2	16\"/>			
	PLASTER	(1)	2X4	DF	#2	16\"/>			
9'-6" TO 10'-6"	NO PLASTER	(1)	2X4	HF	#2	16\"/>			
	NO PLASTER (OPT)	(1)	2X4	DF	#2	16\"/>			
	PLASTER	(1)	2X4	DF	#2	16\"/>			

2x4 WALL FRAMING SCHEDULE



INTERIOR PARTITION SCALE : 3" = 1'-0" 14



INTERIOR PARTITION SCALE : 3" = 1'-0" 14

CUTTING AND NOTCHING SCALE : 1 1/2" = 1'-0" 7

FULL HEIGHT INTERIOR PARTITION SCALE : 3" = 1'-0" 2

COLUMN HEIGHT	OPENING SIZE	EXT FINISH	HEADER				SILL				FULL HEIGHT KING STUD			
			NUMBER	SIZE	LUMBER TYPE	OC	NUMBER	SIZE	LUMBER TYPE	OC	NUMBER	SIZE	LUMBER TYPE	OC
UP TO 10'-6"	3070	ANY	(1)	2X6	HF	#2	N/A				(1)	2X6	HF	#2
		ANY (OPT)	(1)	2X6	DF	#2	N/A				(1)	2X6	DF	#2
	4070	ANY	(1)	2X6	HF	#2	N/A				(1)	2X6	HF	#2
		ANY (OPT)	(1)	2X6	DF	#2	N/A				(1)	2X6	DF	#2
	6040	ANY	(1)	2X6	HF	#2	(1)	2X6	HF	#2	(2)	2X6	HF	#2
		ANY (OPT)	(1)	2X6	DF	#2	(1)	2X6	DF	#2	(2)	2X6	DF	#2
8040	ANY	(1)	2X6	HF	#2	(1)	2X6	HF	#2	(2)	2X6	HF	#2	
	ANY (OPT)	(1)	2X6	DF	#2	(1)	2X6	DF	#2	(2)	2X6	DF	#2	

COLUMN HEIGHT	OPENING SIZE	EXT FINISH	HEADER				SILL				FULL HEIGHT KING STUD			
			NUMBER	SIZE	LUMBER TYPE	OC	NUMBER	SIZE	LUMBER TYPE	OC	NUMBER	SIZE	LUMBER TYPE	OC
UP TO 10'-6"	3070	NO PLASTER	(1)	2X8	HF	#2	N/A				(1)	2X8	HF	#2
		NO PLASTER (OPT)	(1)	2X8	DF	#2	N/A				(1)	2X8	DF	#2
	4070	NO PLASTER	(1)	2X8	HF	#2	N/A				(1)	2X8	HF	#2
		NO PLASTER (OPT)	(1)	2X8	DF	#2	N/A				(1)	2X8	DF	#2
	6040	NO PLASTER	(1)	2X8	HF	#2	(1)	2X8	HF	#2	(1)	2X8	HF	#2
		NO PLASTER (OPT)	(1)	2X8	DF	#2	(1)	2X8	DF	#2	(1)	2X8	DF	#2
8040	NO PLASTER	(1)	2X8	HF	#2	(1)	2X8	HF	#2	(1)	2X8	HF	#2	
	NO PLASTER (OPT)	(1)	2X8	DF	#2	(1)	2X8	DF	#2	(1)	2X8	DF	#2	




2x6 OPENING STUDS SCHEDULE 19

COLUMN HEIGHT	EXT FINISH	WOOD WALL FRAMING				4' CORNER OF WOOD WALL FRAMING (ZONE 5)					
		NUMBER	SIZE	LUMBER TYPE	OC	NUMBER	SIZE	LUMBER TYPE	OC		
UP TO 10'-6"	NO PLASTER	(1)	2X6	HF	#2	16" OC	(1)	2X6	HF	#2	16" OC
	NO PLASTER (OPT)	(1)	2X6	DF	#2	16" OC	(1)	2X6	DF	#2	16" OC
	W/ PLASTER	(1)	2X6	HF	#2	16" OC	(1)	2X6	HF	#2	16" OC
	W/ PLASTER (OPT)	(1)	2X6	DF	#2	16" OC	(1)	2X6	DF	#2	16" OC

2x8 OPENING STUDS SCHEDULE 14

COLUMN HEIGHT	EXT FINISH	WOOD WALL FRAMING				4' CORNER OF WOOD WALL FRAMING (ZONE 5)					
		NUMBER	SIZE	LUMBER TYPE	OC	NUMBER	SIZE	LUMBER TYPE	OC		
UP TO 10'-6"	NO PLASTER	(1)	2X8	HF	#2	16" OC	(1)	2X8	HF	#2	16" OC
	NO PLASTER (OPT)	(1)	2X8	DF	#2	16" OC	(1)	2X8	DF	#2	16" OC
	W/ PLASTER	(1)	2X8	HF	#2	16" OC	(1)	2X8	HF	#2	16" OC
	W/ PLASTER (OPT)	(1)	2X8	DF	#2	16" OC	(1)	2X8	DF	#2	16" OC

BORED HOLES SCALE : 1 1/2" = 1'-0" 8



2x6 WALL FRAMING SCHEDULE 20

COLUMN HEIGHT	EXT FINISH	WOOD WALL FRAMING				4' CORNER OF WOOD WALL FRAMING (ZONE 5)					
		NUMBER	SIZE	LUMBER TYPE	OC	NUMBER	SIZE	LUMBER TYPE	OC		
UP TO 10'-6"	NO PLASTER	(1)	2X6	HF	#2	16" OC	(1)	2X6	HF	#2	16" OC
	NO PLASTER (OPT)	(1)	2X6	DF	#2	16" OC	(1)	2X6	DF	#2	16" OC
	W/ PLASTER	(1)	2X6	HF	#2	16" OC	(1)	2X6	HF	#2	16" OC
	W/ PLASTER (OPT)	(1)	2X6	DF	#2	16" OC	(1)	2X6	DF	#2	16" OC

2x8 WALL FRAMING SCHEDULE 15

COLUMN HEIGHT	EXT FINISH	WOOD WALL FRAMING				4' CORNER OF WOOD WALL FRAMING (ZONE 5)					
		NUMBER	SIZE	LUMBER TYPE	OC	NUMBER	SIZE	LUMBER TYPE	OC		
UP TO 10'-6"	NO PLASTER	(1)	2X8	HF	#2	16" OC	(1)	2X8	HF	#2	16" OC
	NO PLASTER (OPT)	(1)	2X8	DF	#2	16" OC	(1)	2X8	DF	#2	16" OC
	W/ PLASTER	(1)	2X8	HF	#2	16" OC	(1)	2X8	HF	#2	16" OC
	W/ PLASTER (OPT)	(1)	2X8	DF	#2	16" OC	(1)	2X8	DF	#2	16" OC

NOT USED 9

INTERIOR PARTITION WALL TO ROOF TRUSS SCALE : 3" = 1'-0" 4

2x6 WALL FRAMING SCHEDULE 20

2x8 WALL FRAMING SCHEDULE 15

NOT USED 10

5

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL
THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**WALL FRAMING
DETAILS
WOOD STUDS**

REVISIONS

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL




MODULAR BUILDING DESIGN PROFESSIONAL



SILVER CREEK INDUSTRIES
24' x 40' PC
PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER

S-5.11

LEGEND		
SYMBOL	ABB.	DESCRIPTION
	SAD	SUPPLY AIR DUCT
	RAD	RETURN AIR DUCT
	EAD	EXHAUST AIR DUCT
	(L)	LINED DUCTWORK
	CD	SUPPLY CEILING DIFFUSER
	CR	RETURN CEILING REGISTER
	ER	EXHAUST CEILING REGISTER
	VTR	VENT THRU ROOF
	FD	FIRE DAMPER
	MVD	MANUAL VOLUME DAMPER
	UC	UNDERCUT DOOR
	STAT	THERMOSTAT
	BT	BYPASS TIMER
	P.O.C	POINT OF CONNECTION
	CO2	CO2 SENSOR



MEP COMPONENT ANCHORAGE NOTE:

ALL MECHANICAL, PLUMBING AND ELECTRICAL COMPONENTS SHALL BE ANCHORED AND INSTALLED PER THE DETAILS ON THE DSA APPROVED CONSTRUCTION DOCUMENTS. THE FOLLOWING COMPONENTS SHALL BE ANCHORED OR BRACED TO MEET THE FORCE AND DISPLACEMENT REQUIREMENTS PRESCRIBED IN THE 2022 CBC, SECTIONS 1617A.1.18 THROUGH 1617A.1.26 AND ASCE 7-16 CHAPTERS 13, 26 AND 30:

- ALL PERMANENT EQUIPMENT AND COMPONENTS.
- TEMPORARY, MOVABLE OR MOBILE EQUIPMENT THAT IS PERMANENTLY ATTACHED (E.G. HARD WIRED) TO THE BUILDING UTILITY SERVICES SUCH AS ELECTRICITY, GAS OR WATER. "PERMANENTLY ATTACHED" SHALL INCLUDE ALL ELECTRICAL CONNECTIONS EXCEPT PLUGS FOR 110/220 VOLT RECEPTACLES HAVING A FLEXIBLE CABLE.
- TEMPORARY, MOVABLE OR MOBILE EQUIPMENT WHICH IS HEAVIER THAN 400 POUNDS OR HAS A CENTER OF MASS LOCATED 4 FEET OR MORE ABOVE THE ADJACENT FLOOR OR ROOF LEVEL THAT DIRECTLY SUPPORTS THE COMPONENT IS REQUIRED TO BE RESTRAINED IN A MANNER APPROVED BY DSA.C

THE FOLLOWING MECHANICAL AND ELECTRICAL COMPONENTS SHALL BE POSITIVELY ATTACHED TO THE STRUCTURE, BUT NEED NOT DEMONSTRATE DESIGN COMPLIANCE WITH THE REFERENCES NOTED ABOVE. THESE COMPONENTS SHALL HAVE FLEXIBLE CONNECTIONS PROVIDED BETWEEN THE COMPONENT AND ASSOCIATED DUCTWORK, PIPING, AND CONDUIT. FLEXIBLE CONNECTIONS MUST ALLOW MOVEMENT IN BOTH TRAVERSE AND LONGITUDINAL DIRECTIONS.

- COMPONENTS WEIGHING LESS THAN 400 POUNDS AND HAVE A CENTER OF MASS LOCATED 4 FEET OR LESS ABOVE THE ADJACENT FLOOR OR ROOF LEVEL THAT DIRECTLY SUPPORT THE COMPONENT.
- COMPONENTS WEIGHING LESS THAN 20 POUNDS, OR IN THE CASE OF DISTRIBUTED SYSTEMS, LESS THAN 5 POUNDS PER FOOT, WHICH ARE SUSPENDED FROM A ROOF OR FLOOR OR HUNG FROM A WALL.

THE ANCHORAGE OF ALL MECHANICAL, ELECTRICAL AND PLUMBING COMPONENTS SHALL BE SUBJECT TO THE APPROVAL OF THE DESIGN PROFESSIONAL IN GENERAL RESPONSIBLE CHARGE OR STRUCTURAL ENGINEER DELEGATED RESPONSIBILITY AND ACCEPTANCE BY DSA. THE PROJECT INSPECTOR WILL VERIFY THAT ALL COMPONENTS AND EQUIPMENT HAVE BEEN ANCHORED IN ACCORDANCE WITH THE ABOVE REQUIREMENTS.

PIPING, DUCTWORK AND ELECTRICAL DISTRIBUTION SYSTEM BRACING NOTE

PIPING, DUCTWORK AND ELECTRICAL DISTRIBUTION SYSTEMS SHALL BE BRACED TO COMPLY WITH THE FORCES AND DISPLACEMENTS PRESCRIBED IN ASCE 7-16 SECTION 13.3 AS DEFINED IN ASCE 7-16 SECTION 13.6.5, 13.6.6, 13.6.7, 13.6.8; AND 2022 CBC, SECTIONS 1617A.1.24, 1617A.1.25 AND 1617A.1.26.

THE METHOD OF SHOWING BRACING AND ATTACHMENTS TO THE STRUCTURE FOR THE IDENTIFIED DISTRIBUTION SYSTEM ARE AS NOTED BELOW. WHEN BRACING AND ATTACHMENTS ARE BASED ON A PREAPPROVED INSTALLATION GUIDE (E.G., HCAI OPM FOR 2013 CBC OR LATER), COPIES OF THE BRACING SYSTEM INSTALLATION GUIDE OR MANUAL SHALL BE AVAILABLE ON THE JOBSITE PRIOR TO THE START OF THE DURING THE HANGING AND BRACING OF THE DISTRIBUTION SYSTEMS. THE STRUCTURAL ENGINEER OF RECORD SHALL VERIFY THE ADEQUACY OF THE STRUCTURE TO SUPPORT TO SUPPORT THE HANGER AND BRACE LOADS.

MECHANICAL PIPING (MP), MECHANICAL DUCTS (MD), PLUMBING PIPING (PP), ELECTRICAL DISTRIBUTION SYSTEMS (E):

MP□MD□PP□E□OPTION 1: DETAILED ON THE APPROVED DRAWINGS WITH PROJECT SPECIFIC NOTES AND DETAILS.

MP□MD□PP□E□OPTION 2: SHALL COMPLY WITH HCAI PREAPPROVAL (OPM #) #-----.

Device Type	Climate Zones	Required High Limit (Economizer Off When)
Fixed Dry Bulb	1, 3, 5, 11-16	$T_{in} > 55^{\circ}\text{F}$ Outdoor air temperature exceeds 55°F
	2, 4, 9	$T_{in} > 53^{\circ}\text{F}$ Outdoor air temperature exceeds 53°F
	7	$T_{in} > 51^{\circ}\text{F}$ Outdoor air temperature exceeds 51°F
Differential Dry Bulb	1, 3, 5, 11-16	$T_{in} - T_{out} > 9^{\circ}\text{F}$ Outdoor air temperature exceeds return air temperature
	2, 4, 9	$T_{in} - T_{out} > 8^{\circ}\text{F}$ Outdoor air temperature exceeds return air temperature
	7	$T_{in} - T_{out} > 7^{\circ}\text{F}$ Outdoor air temperature exceeds return air temperature
Fixed Enthalpy + Fixed Drybulb	7	$h_{in} > 28 \text{ Btu/l}$ or $T_{in} > 55^{\circ}\text{F}$ Outdoor air enthalpy exceeds 28 Btu/lb of dry air or outdoor air temperature exceeds 55°F

*Only the high limit control devices listed are allowed to be used and at the setpoints listed. Others such as Dew Point, Fixed Enthalpy, Electronic Enthalpy, and Differential Enthalpy Controls, may not be used in any Climate Zone for compliance with Section 140.4(e) unless approval for use is provided by the Energy Commission Executive Director.

†Devices with selectable (rather than adjustable) setpoints shall be capable of being set to within 2°F and 2 Btu/lb of the setpoint listed.

‡At altitudes substantially different than sea level, the Fixed Enthalpy limit value shall be set to the enthalpy value at 55°F and 50% relative humidity. As an example, at approximately 6,000 foot elevation, the fixed enthalpy limit is approximately 30.7 Btu/lb.

CEILING MOUNTED EXHAUST FAN SCHEDULE

SYM.	LOCATION	SERVICE	MANUF.	MODEL	CFM	SONES	SP	ELECTRICAL			WGT	REMARKS
								VOLTS	Ø	POWER		
EF 1	CEILING	TOILET EXHAUST	BROAN	L100	109	1.0	0.25	120	1	87 WATTS	22.80 LBS.	WITH BROAN ROOF CAP #634. PROVIDE 6" DIA. EXHAUST DUCT UP TO ROOF. INTERLOCK WITH LIGHT SWITCH.
EF 2	CEILING	TOILET EXHAUST	BROAN	L200	210	2.0	0.25	120	1	127 WATTS	31.0 LBS.	WITH BROAN ROOF CAP #634. PROVIDE 8" DIA. EXHAUST DUCT UP TO ROOF. INTERLOCK WITH LIGHT SWITCH.
EF 3	CEILING	TOILET EXHAUST	BROAN	L300	308	2.8	0.25	120	1	212 WATTS	23.10 LBS.	WITH BROAN ROOF CAP #634. PROVIDE 8" DIA. EXHAUST DUCT UP TO ROOF. INTERLOCK WITH LIGHT SWITCH.

OR APPROVED EQUAL.

PERFORATED FACE GRILLE SCHEDULE (SUPPLY)

ITEM	NECK SIZE	RANGE CFM	MFG & MODEL #
T-BAR SUPPLY 	6"Ø	0 - 150	Fixed Curve Blade, 4-way throw
	8"Ø	150 - 230	For lay-in T-bar ceilings use Harth & Cooley SD-9419. (Sizes as shown on Mech Plan)
	10"Ø	230 - 350	
	12"Ø	350 - 460	
	14"Ø	460 - 640	

PERFORATED FACE GRILLE SCHEDULE (RETURN)


ITEM	NECK SIZE	RANGE CFM	MFG & MODEL #
T-BAR RETURN 	6"Ø	0 - 230	Perforated face
	10"Ø	230 - 460	For lay-in T-bar ceilings use Shoemaker 10SP with 24 ga., 45 deg. angle. (Sizes as shown on Mech Plan.)
	14"Ø	460 - 710	

DUCT NOTES:


- ALL DUCTING SHALL BE INSULATED WITH MIN OF R-4.2.
- DUCT INSTALLATION AND PLENUMS SHALL MEET THE REQUIREMENTS OF ENERGY CODE SECTION 120.4 AND THE MANUFACTURERS INSTALLATION INSTRUCTIONS.
- HORIZONTAL FLEX DUCT SHALL BE SUPPORTED AT A MAXIMUM 4 FT INTERVALS, WITH HANGING STRAPS A MINIMUM 1 1/2" WIDE.
- DUCTS MUST BE PULLED TIGHT WITH A MAXIMUM SAG OF 1/2" PER FOOT OF HORIZONTAL RUN.
- DUCT SHALL NOT BE KINKED OR CRUSHED.
- BEND/RADIUS EQUAL TO THE DUCT DIAMETER OR GREATER.

GENERAL NOTES:

- THERMOSTAT SHALL BE PROGRAMMED WITH EXPECTED OCCUPIED TIMES.
- AIR HANDLER FAN WILL BE PROGRAMMED TO RUN DURING ALL OCCUPIED TIMES.
- PRE-OCCUPANCY PURGE SHALL BE PROGRAMMED ONE HOUR PRIOR TO THE MODULAR BUILDING BEING NORMALLY OCCUPIED PER ENERGY CODE 120.1(D)1.
- ECONOMIZERS SHALL BE PROGRAMMED FOR HIGH LIMIT SHUT OFF PER TABLE 140.4-E.
- THE OUTDOOR AIR CO2 CONCENTRATION SHALL BE ASSUMED TO BE 400 ppm.




△ PROVIDE MIN 30"x48" CLR FLOOR SPACE FOR PERPENDICULAR APPROACH AT EACH LOCATION



SUPPLY CEILING DIFFUSER MOUNTING

SCALE NONE


D



UNIT TO THERMOSTAT WIRING

SCALE NONE


A



RETURN CEILING DIFFUSER MOUNTING

SCALE NONE

B



AC UNIT MOUNTING

SCALE NONE

C

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:

**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:

**MECHANICAL NOTES,
SCHEDULES, & DETAILS**


REVISIONS

1		
2		
3		

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL



Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL



SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:



DRAWN BY:

SCALE: AS NOTED

DATE: 02-27-2023

P.C. SHEET NUMBER

M-0.1



WALL MOUNTED MECHANICAL EQUIPMENT SCHEDULE

	SPVU-1	SPVU-2
HVAC Equipment	SPVU-1	SPVU-2
Make and Model	BARB #W60HC-A00VN	BARB #T60S1-A00VN
Nominal Tonnage	5	5
BTUH:		
Heating	52,500	56,000
Cooling	54,500	52,000
Indoor/Blower Fan:		
BHP/Hp	0.75/0.75	0.75/0.75
CFM	1,750	1,650
Strip Heating	NA	NA
SEER	NA	NA
EER	11.0	11.0
HSPF	NA	NA
COP	3.3	3.3
Voltage	230/208-1	230/208-1
MCA	42	42
MCOP	60	60
Wire Size (Pwr/ Grnd)	8 / 10	8 / 10
Thermostat:		
Make and Model	Venstar #T4900SCH	Venstar #T4900SCH
Setback	Yes	Yes
Heat Pumps	Yes	Yes
Shut-off and Reset:	Occupancy Sensor	Occupancy Sensor
Economizer:		
Make and Model	Integrated	Integrated
Controls	Fixed Dry Bulb	Fixed Dry Bulb
Fault Detection	Yes	Yes
Outside Air Damper Position	Varies	Varies
Demand Control Ventilation	Yes	Yes
Minimum DCV Outside Air in CFM	0.15 CFM / SF	0.15 CFM / SF
Minimum Designed Outside Air in CFM	See Below	See Below
Demand Shed Thermostat	NA	NA
Operating Weight	595 #	660 #

NOTES:

PROVIDE SET-BACK THERMOSTAT.

DESIGNED MINIMUM OUTSIDE AIR SHALL BE NO LESS THAN 15 CFM PER EXPECTED OCCUPANT

PROVIDE AN OCCUPANCY SENSOR WITH AN AUTOMATIC SHUT DOWN CONTROLS

PROVIDE 2" MERV 13 FILTER

AIR HANDLERS WITH OTHER VOLTAGES SHALL BE ACCEPTABLE.

AIR HANDLERS OTHER THAN THE MAKE AND MODEL LISTED ABOVE SHALL BE ACCEPTABLE WHEN THE NOMINAL TONNAGE IS EQUAL TO THE INDICATED TONNAGE AND THE EER AND COP VALUES ARE NO LESS THAN THOSE SHOWN ABOVE.

PROVIDE A CO2 SENSOR WITH LCD DISPLAY (CARROER #B3ZCSP02LCD-01 or EQUAL) ADJACENT TO THE THERMOSTAT MOUNTED AT + 48" AFF.

PROVIDE A HONEYWELL JADE CONTROL SYSTEM (or EQUAL) CAPABLE OF OUTPUTTING FDD ALARMS TO THE THERMOSTAT PER ENERGY CODE SECTION 120.2(j).

ECONOMIZERS SHALL HAVE AN INTEGRATED BAROMETRIC DAMPER OR OTHER MEANS OF EXHAUSTING THE BUILDING WHEN THE SYSTEM IS DELIVERING 100% OUTSIDE AIR.

MECHANICAL EQUIPMENT SCHEDULE

NOTE:

THIS MECHANICAL SYSTEM SHALL PROVIDE A MINIMUM OUTSIDE AIR RATE OF 0.38 CFM / SF OR 15 CFM PER OCCUPANT, WHICHEVER IS GREATER. THE BUILDING MANUFACTURER SHALL VERIFY THE EXPECTED OCCUPANT LOAD WITH THE SCHOOL DISTRICT PRIOR TO SELECTION OF THE MECHANICAL EQUIPMENT. THE SELECTED EQUIPMENT SHALL BE CAPABLE OF MEETING THE OUTSIDE AIR REQUIREMENTS UNDER PEAK DESIGN CONDITIONS FOR THE CLIMATE ZONE IN WHICH THE BUILDING WILL BE LOCATED. AT THE TIME OF OCCUPANCY, THE BUILDING MANUFACTURER SHALL PROVIDE TO THE BUILDING OWNER A CALCULATION INDICATING THE VOLUMES OF OUTSIDE AIR AND OF RECIRCULATED AIR THAT THE VENTILATION SYSTEM HAS BEEN DESIGNED TO PROVIDE.

VENTILATION CALCULATIONS:

24' X 40' CLASSROOM

MINIMUM REQUIRED VENTILATION

ROOM AREA = 960 SF

REQUIRED VENTILATION RATE = 0.38 CFM / SF

REQUIRED OUTSIDE AIR VOLUME = 960 X 0.38 = 365 CFM

VENTILATION AS DESIGNED

BUILDING AREA = 960 SF

OCCUPANCY FOR EGRESS PURPOSES = 960 / 20 = 48 OCCUPANTS

EXPECTED # OF OCCUPANTS = 48 OCCUPANTS X 0.65 = 31 OCCUPANTS

REQUIRED VENTILATION RATE = 15 CFM / OCCUPANT

REQUIRED OUTSIDE AIR VOLUME = 31 X 15 = 465 CFM

NOTE:

THE DEMAND CONTROL VENTILATION SYSTEM SHALL NOT BE REQUIRED TO PROVIDE THE OUTSIDE AIR IN EXCESS OF THE DESIGNED VOLUME INDICATED ABOVE. THE DEMAND CONTROL VENTILATION SYSTEM SHALL NOT REDUCE THE OUTSIDE AIR TO LESS THAN 25% OF THE DESIGNED VOLUME INDICATED ABOVE.

NOTE:

BUILDING MANUFACTURER SHALL LEAVE FOR THE BUILDING OWNER, AT OCCUPANCY, OPERATING INFORMATION FOR ALL APPLICABLE MECHANICAL AND ELECTRICAL FEATURES, MATERIALS, COMPONENTS, AND DEVICES INSTALLED IN THE BUILDING RELATED TO EFFICIENT ENERGY USE. IN ADDITION, THE BUILDING MANUFACTURER SHALL LEAVE MAINTENANCE INFORMATION FOR ALL FEATURES, MATERIALS, COMPONENTS, AND MANUFACTURED DEVICES THAT REQUIRE ROUTINE MAINTENANCE FOR EFFICIENT OPERATION OF THE MECHANICAL AND LIGHTING SYSTEMS.

NOTE:

THE OCCUPANCY SENSOR USED TO CONTROL THE HVAC EQUIPMENT SHALL BE SEPARATE FROM THE OCCUPANCY SENSOR USED TO CONTROL THE LIGHTING SYSTEM. THIS SENSOR MAY BE INTEGRATED INTO THE THERMOSTAT OR MAY BE A SEPARATE DEVICE.

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.

ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:

**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:

**MECHANICAL PLAN
WALL MOUNT
24' x 40'**

REVISIONS

1

2

3

4

5

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL

Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:


DRAWN BY:

SCALE: AS NOTED


DATE: 02-27-2023

P.C. SHEET NUMBER





M-1.01



REFER TO PROJECT SPECIFIC SHEET E-1.01N



- NOTES:
- SIZE OF CONDUCTORS SHALL COMPLY WITH CEC TABLE 250.66
 - ELEC. TRADE SHALL CHECK AREA FOR EXISTING CONDUITS, SEWER, GAS & WATER PIPING BEFORE DRIVING GROUND RODS.
 - BOND SEPARATE CONDUCTORS FROM GROUND ROD TO ELECTRICAL PANEL & TO METAL BUILDING FRAME (CEC 250.52) IN ADDITION TO THE DETAIL SHOWN ABOVE. BOND THE ELECTRICAL GROUND TO METAL UNDERGROUND WATER PIPE IN DIRECT CONTACT WITH THE EARTH FOR 10 FT. OR MORE, IF AVAILABLE (CEC 250.52)
 - ALL MODULES OF METAL FRAME BLDGS. SHALL BE ELECTRICALLY BONDED TOGETHER (BOLTING ONLY IS NOT ACCEPTABLE BONDING). BONDING SHALL INCLUDE METAL RAMP.
 - CHECK RESISTANT TO GROUND ROD, IF RESISTANCE EXCEEDS 25 OHMS, INSTALL ADDITIONAL GROUND RODS WITH CONDUCTORS AS SHOWN SEPARATED AT LEAST 6'-0" UNTIL RESISTANCE IS REDUCED TO 25 OHMS OR LESS (CEC 250.56).



TESTING: TEST FOR RESISTANCE TO GROUND, IF RESISTANCE EXCEEDS 25 OHMS, INSTALL ADDITIONAL GROUND RODS SEPARATED AT LEAST 6'-0" UNTIL RESISTANCE IS REDUCED TO 25 OHMS OR LESS. (BY SITE ELECTRICAL).

APPROVAL OF THIS PLAN DOES NOT CONSTITUTE APPROVAL OF THIS FIRE ALARM FOR ALL SITES. THE FIRE ALARM SYSTEM AND/OR COMPONENTS MAY BE REQUIRED TO BE CHANGED DUE TO SITE LOCATION EXISTING CONDITIONS OR INCOMPATIBLE COMPONENTS.

GROUND MG TEST SHALL BE DONE IN THE PRESENCE OF THE PROJECT INSPECTOR. ALL GROUNDING SHALL BE IN ACCORDANCE WITH CEC ARTICLE 250.

- FIRE ALARM NOTES
- SMOKE AND HEAT DETECTOR CONDUIT AND DEVICES PROVIDED AND INTERCONNECTED BY OTHERS TO FIRE ALARM SYSTEM
 - PROVIDE DEDICATED FIRE ALARM 120 VOLT CIRCUIT CONNECTED TO LOCKED-ON BREAKER. THE CIRCUIT BREAKER SHALL BE LOCKED-ON WITH APPROVED LOCKING DEVICE, MARKED RED AND IDENTIFIED AS "FIRE ALARM CONTROL CIRCUIT". NFPA 72 SECTION 10.6.5.2

MEP COMPONENT ANCHORAGE NOTE

ALL MECHANICAL, PLUMBING AND ELECTRICAL COMPONENTS SHALL BE ANCHORED AND INSTALLED PER THE DETAILS ON THE DSA APPROVED CONSTRUCTION DOCUMENTS. THE FOLLOWING COMPONENTS SHALL BE ANCHORED OR BRACED TO MEET THE FORCE AND DISPLACEMENT REQUIREMENTS PRESCRIBED IN THE 2022 CBC SECTIONS 1617A.1.18 THROUGH 1617A.1.26 AND ASCE 7-16 CHAPTERS 13, 26, AND 30:

- ALL PERMANENT EQUIPMENT AND COMPONENTS.
- TEMPORARY OR MOVABLE EQUIPMENT THAT IS PERMANENTLY ATTACHED (E.G. HARD WIRED) TO THE BUILDING UTILITY SERVICES SUCH AS ELECTRICITY, GAS OR WATER. "PERMANENTLY ATTACHED" SHALL INCLUDE ALL ELECTRICAL CONNECTIONS EXCEPT PLUGS FOR 110/220 VOLT RECEPTACLES HAVING A FLEXIBLE CABLE.
- TEMPORARY, MOVABLE OR MOBILE EQUIPMENT WHICH IS HEAVIER THAN 400 POUNDS OR HAS A CENTER OF MASS LOCATED 4 FEET OR MORE ABOVE THE ADJACENT FLOOR OR ROOF LEVEL THAT DIRECTLY SUPPORT THE COMPONENT IS REQUIRED TO BE RESTRAINED IN A MANNER APPROVED BY DSA.

THE FOLLOWING MECHANICAL AND ELECTRICAL COMPONENTS SHALL BE POSITIVELY ATTACHED TO THE STRUCTURE, BUT NEED NOT DEMONSTRATE DESIGN COMPLIANCE WITH THE REFERENCES NOTED ABOVE. THESE COMPONENTS SHALL HAVE FLEXIBLE CONNECTIONS PROVIDED BETWEEN THE COMPONENT AND ASSOCIATED DUCTWORK, PIPING, AND CONDUIT. FLEXIBLE CONNECTIONS MUST ALLOW MOVEMENT IN BOTH TRANSVERSE AND LONGITUDINAL DIRECTIONS:

- COMPONENTS WEIGHING LESS THAN 400 POUNDS AND HAVE A CENTER OF MASS LOCATED 4 FEET OR LESS ABOVE THE ADJACENT FLOOR OR ROOF LEVEL THAT DIRECTLY SUPPORT THE COMPONENT.
- COMPONENTS WEIGHING LESS THAN 200 POUNDS, OR IN THE CASE OF DISTRIBUTED SYSTEMS, LESS THAN 5 POUNDS PER FOOT, WHICH ARE SUSPENDED FROM A ROOF OR FLOOR OR HUNG FROM A WALL.

THE ANCHORAGE OF ALL MECHANICAL, ELECTRICAL AND PLUMBING COMPONENTS SHALL BE SUBJECT TO THE APPROVAL OF THE DESIGN PROFESSIONAL IN GENERAL RESPONSIBLE CHARGE OR STRUCTURAL ENGINEER DELEGATED RESPONSIBILITY AND ACCEPTANCE BY DSA. THE PROJECT INSPECTOR WILL VERIFY THAT ALL COMPONENTS AND EQUIPMENT HAVE BEEN ANCHORED IN ACCORDANCE WITH THE ABOVE REQUIREMENTS.

PIPING, DUCTWORK AND ELECTRICAL DISTRIBUTION SYSTEMS SHALL BE BRACED TO COMPLY WITH THE FORCES AND DISPLACEMENTS PRESCRIBED IN ASCE 7-16 SECTION 13.3 AS DEFINED IN ASCE 7-16 SECTION 13.6.5, 13.6.6, 13.6.7, 13.6.8 AND 2022 CBC SECTIONS 1617A.1.24, 1617A.1.25 & 1617A.1.26.

THE METHOD OF SHOWING BRACING AND ATTACHMENTS TO THE STRUCTURE FOR THE IDENTIFIED DISTRIBUTION SYSTEM ARE AS NOTED BELOW. WHEN BRACING AND ATTACHMENTS ARE BASED ON A PREAPPROVED INSTALLATION GUIDE (E.G., OSHPD OPA FOR 2013 CBC OR LATER), COPIES OF THE BRACING SYSTEM INSTALLATION GUIDE OR MANUAL SHALL BE AVAILABLE ON THE JOBSITE PRIOR TO THE START OF AND DURING THE HANGING AND BRACING OF THE DISTRIBUTION SYSTEMS. THE STRUCTURAL ENGINEER OF RECORD SHALL VERIFY THE ADEQUACY OF THE STRUCTURE TO SUPPORT THE HANGER AND BRACE LOADS.

MECHANICAL PIPING (MP), MECHANICAL DUCTS (MD), PLUMBING PIPING (PP), ELECTRICAL DISTRIBUTION SYSTEM (E):

MP MD PP E OPTION 1: DETAILED ON THE APPROVED DRAWINGS WITH PROJECT SPECIFIC NOTES AND DETAILS.

LIGHTING CONTROL SYSTEM SEQUENCE OF OPERATIONS

THE LIGHTING CONTROL SYSTEM BASIS OF DESIGN SHALL BE THE LUTRON VIVE WIRELESS LIGHTING CONTROL SYSTEM. THE SYSTEM SHALL BE CAPABLE OF PROVIDING MANUAL CONTROL, OCCUPANCY SENSING CONTROL AND DAYLIGHT HARVESTING CONTROL.

SEQUENCE:

OCCUPANT ENTERS:
ALL LIGHTS AUTOMATICALLY TURN ON TO 50% LIGHT LEVEL. OCCUPANT MAY INCREASE LIGHTS TO MAXIMUM LEVEL MANUALLY WITH WALL CONTROL.

WHEN OCCUPIED:
LIGHTING IN DAYLIT ZONES AUTOMATICALLY DIM/BRIGHTEN BASED ON DAYLIGHT AVAILABILITY.
OCCUPANT MAY MANUALLY DIM/BRIGHTEN THE LIGHTS WITH WALL CONTROL.

OCCUPANT EXITS:
ALL LIGHTS AUTOMATICALLY TURN OFF 15 MINUTES AFTER VACANCY.

CONDUIT FILL AND CONDUCTOR CAPACITY TABLE

(ALL CONDUCTORS SHALL BE TYPE THHN/THWN 90°C. COPPER)						
WIRE SIZE	CAPACITY	WIRE TYPE	NO. OF CONDUCTOR PERMITTED	1/2" C	3/4" C	1" C
#12	20A	THHN	9	16	25	45
#10	30A	THHN	5	10	16	28
#8	45A	THHN	2	5	8	14
#6	65A	THHN	1	3	5	10
#4	85A	THHN	1	2	4	7

JUNCTION BOX SIZE TABLE


BOX	SIZE	CU. IN.	MAX NO. OF CONDUCTORS			
			#12	#10	#8	#6
4SS	1 1/4" x 4" SQ	18.0	8	7	6	0
4S	1 1/2" x 4" SQ	21.0	9	8	7	0
4SD	2 1/8" x 4" SQ	30.3	13	12	10	6
4SX	2 7/8" x 4" SQ	43.5	23	21	17	10
5SD	2 1/8" x 4-11/16" SQ	42.0	18	16	14	6
5SX	3 7/8" x 4-11/16" SQ	86.0	38	34	28	17
664	4" x 6" SQ	144.0	64	57	48	28

* DEDUCT ONE CONDUCTOR FOR (1) OR MORE GROUNDING CONDUCTORS ENTERING THE BOX

LEGEND

- 2x4 CEILING RECESSED LIGHT, LED LIGHT FIXTURE WITH DIMMING WATTAGE: 51 WATTS (MAX), 5000L (MIN)
- WALL MOUNTED HVAC UNIT. SEE MECHANICAL DWGS
- ROOF MOUNTED HVAC UNIT-SEE MECHANICAL DWGS
- ELECTRICAL PANEL AT +60" AFF TO TOP OF ELECTRICAL PANEL WITH 1 1/2" DIA POWER STUB OUT (U.N.O.)
- CEILING MOUNTED OCCUPANCY SENSOR
- CEILING MOUNTED PHOTOCELL
- ULTRASONIC CEILING OCCUPANCY SENSOR. SENSOR TO BE CONNECTED TO KEYPAD LIGHT SWITCHES FOR MANUAL OVERRIDE AND USE FOR RESTROOM W/ PARTITIONS.
- SINGLE SWITCH WALL OCCUPANCY SENSOR. WATTSOPPER PW-100 OR EQUAL. SENSOR TO BE MOUNTED AT +44" AFF
- DIMMER SWITCH, AT +48" AFF. TO TOP OF OUTLET BOX
- LIGHT SWITCH. MOUNT AT +48" AFF TO TOP OF OUTLET BOX
- 3-WAY LIGHT SWITCH. MOUNT AT +48" AFF TO TOP OF OUTLET BOX
- KEYPAD SWITCH MOUNT AT +48" AFF TO TOP OF OUTLET BOX
- DUPLEX (WALL MOUNTED) RECEPTACLE 15A - 125V - 3 WIRE. MOUNT AT +18" AFF U.O.N. TO CENTERLINE OF DEVICE
- EXTERIOR WEATHER PROOF GFI RECEPTACLE AT +24" AFF FOR A/C SERVICES (MAX 25'-0" FROM UNITS)
- GROUND FAULT CIRCUIT INTERRUPT RECEPTACLE WITHIN 6'-0" OF ALL SINKS
- ROOF MOUNTED WEATHER PROOF GFI RECEPTACLE
- EXTERIOR LED LIGHT FIXTURE W/ 90 MIN. EMERGENCY BATTERY BACKUP WHEN 'EM' IS DESIGNATED NEXT TO FIXTURE W/ PHOTOCELL W/ 30W MAX. MOUNT AT +93" AFF
- CLOCK OUTLET AT +90" AFF TO CENTERLINE OF DEVICE
- EXIT SIGN WITH 90 MIN. BATTERY BACK UP. EXIT SIGN REQUIRED FOR CLASSROOMS WITH TWO OR MORE EXTERIOR DOORS. CLASSROOMS WITH ONE EXTERIOR DOOR - OPTIONAL
- 4SD J-BOX FOR FIRE ALARM PULL STATION (DEVICE BY OTHERS). MOUNT AT +48" AFF TO TOP OF OUTLET BOX WITH 3/4" CONDUIT TO FIRE ALARM STROBE WITH PULL STRING
- 4SD J-BOX FOR FIRE ALARM STROBE OR VOICE EVAC SPEAKER (DEVICE BY OTHERS). BOTTOM OF LENS SHALL BE BETWEEN 80" AND 96" AFF AND WITH 3/4" CONDUIT TO EXTERIOR FIRE ALARM HORN WITH PULL STRING
- 4SD J-BOX FOR EXTERIOR FIRE ALARM SPEAKER (DEVICE BY OTHERS). MOUNT AT +90" AFF TO TOP OF DEVICE WITH 3/4" CONDUIT STUBBED TO ATTIC WITH PULL STRING
- RECESSED 4SD J-BOX W/ COVER PLATE FOR FUTURE FIRE ALARM SYSTEM BY OTHERS. MOUNT AT +18" AFF U.O.N. TO CENTERLINE OF BOX AND PROVIDE 1" CO STUB TO ATTIC SPACE WITH PULL STRING
- 4SD J-BOX IN ATTIC FOR CEILING MOUNTED SMOKE DETECTOR (DEVICE BY OTHERS). MAXIMUM 21'-0" FROM ANY POINT IN ROOM AND 30'-0" BETWEEN THEM. PROVIDE A 6'-0" CONDUIT FROM EACH J-BOX TO SMOKE DETECTOR LOCATION. CONDUIT & CONNECTION TO CEILING DEVICE & DEVICE BY OTHERS (ALARM NOTE #1)
- 4SD J-BOX IN ATTIC FOR ATTIC MOUNTED HEAT DETECTOR (DEVICE BY OTHERS). MAXIMUM 35'-0" FROM ANY POINT IN ATTIC AND 50'-0" BETWEEN THEM. PROVIDE A 6'-0" CONDUIT FROM EACH J-BOX TO HEAT DETECTOR LOCATION. CONDUIT & CONNECTION TO CEILING DEVICE & DEVICE BY OTHERS (ALARM NOTE #1)
- 4SD J-BOX FOR WATER HEATER LOCATE ABOVE CEILING W/ COVER PLATE. HARD WIRE TO UNIT
- 100 CFM CEILING MOUNTED EXHAUST FAN. INTERLOCKED WITH LIGHT SWITCH
- 300 CFM CEILING MOUNTED EXHAUST FAN. INTERLOCKED WITH LIGHT SWITCH
- 2x4 CEILING RECESSED LIGHT, LED LIGHT FIXTURE WITH DIMMING WATTAGE: 51 WATTS (MAX), 5000L (MIN) EACH LIGHT FIXTURE WHICH IS INDICATED AS BEING AN EMERGENCY LIGHT SHALL HAVE A BALLAST BATTERY PACK INSTALLED ON THE FIXTURE. THE BATTERY PACK SHALL PROVIDE POWER TO A SINGLE LAMP WITHIN THE FIXTURE FOR NO LESS THAN 90 MINUTES. ANY LIGHT FIXTURE EQUIPPED WITH A BATTERY PACK SHALL BE WIRE IN SUCH A MANNER THAT THE BATTERY WILL BE ACTIVATED IMMEDIATELY UPON LOSS OF POWER TO THE FIXTURE. ADDITIONALLY THE BATTERY PACK SHALL BE OPERATED USING BATTERY POWER LIGHTING CONTROL SWITCHES AND SENSORS SHALL NOT BE ABLE TO SHUT THE FIXTURE OFF.
- WALL MOUNTED LIGHT FIXTURE, 30 WATTS
- 4SD J-BOX FOR FUTURE DATA W/ SINGLE GANG RING W/ 1" CO STUB IN ATTIC AND PULL STRING
- DEDICATED CIRCUIT w/ LOCK ON DEVICE FOR FIRE SPRINKLER FLOW SWITCH.
- DEDICATED CIRCUIT w/ LOCK ON DEVICE FOR FIRE SPRINKLER TAMPER SWITCH.
- DEDICATED CIRCUIT w/ LOCK ON DEVICE FOR FIRE SPRINKLER BELL.

NOTE: PROVIDE A MINIMUM OF 72 SF SOLAR READY AREA PER MODULE. AREA TO BE A MINIMUM OF 5' IN ANY DIRECTION WITH A MINIMUM SPACE OF 80 SF PER BUILDING.



PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.

ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:

**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**


SHEET TITLE:

**ELECTRICAL PLAN
AND SCHEDULE
24' x 40'**

REVISIONS

NO.	DESCRIPTION
1	
2	
3	

PRE-CHECK (PC) DOCUMENT CODE: 2022 CBC A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED



MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:

DRAWN BY: AS NOTED

SCALE: AS NOTED

DATE: 02-27-2023

P.C. SHEET NUMBER

E-1.01

ELECTRICAL PLAN


SCALE: 1/4" = 1'-0" 4

ELECTRICAL PANEL											
VOLTS: 120/208 V				PANEL: WALL MOUNTED HVAC				FEED: REAR			
MAIN: 100 A				LOCATION: INTERIOR ACCESS				MOUNTING: FLUSH			
LOAD	QTY	WATTS	BREAKER	A	B	WATTS	BREAKER	WATTS	QTY	LOAD	QTY
		Aφ	Bφ	Amps	P	Aφ	Bφ	Aφ	Bφ		
RECEPTACLES	4	720	20	1	1	4830	20	1	1	HVAC - WALL MOUNT	1
RECEPTACLES/CLOCK	5	900	20	1	3	4830	20	1	3		
INTERIOR LIGHTING	8	960	20	1	5		20	1	5		
EXTERIOR LIGHTING	1	40	20	1	7		20	1	7		
WALL RECEPTACLE (GFI)	1	180	20	1	9		20	1	9		
DED - SOLAR READY					11	40	20	1	11	FIRE ALARM CONTROL PANEL (FIRE ALARM NOTE #2)	
DED - SOLAR READY					13		20	1	13		
A = 1860 WATTS / PHASE		1860	940			4830	4870	B = 5810 WATTS / PHASE			
TOTAL = 12,500 WATTS		61	AMPS	120/208	VOLTS	1 φ		3 WIRE			


ELECTRICAL PANEL

SCALE: 1/4" = 1'-0" 4


ELECTRICAL PANEL											
VOLTS: 120/208 V				PANEL: "A" ROOF MOUNTED HVAC				FEED: REAR			
MAIN: 100 A				LOCATION: INTERIOR ACCESS				MOUNTING: RECESSED			
LOAD	QTY	WATTS	BREAKER	A	B	WATTS	BREAKER	WATTS	QTY	LOAD	QTY
		Aφ	Bφ	Amps	P	Aφ	Bφ	Aφ	Bφ		
RECEPTACLES	4	720	20	1	1	4542	20	1	1	HVAC - ROOF MOUNT	1
RECEPTACLES/CLOCK	5	900	20	1	3	4542	20	1	3		
INTERIOR LIGHTING	8	960	20	1	5		20	1	5		
EXTERIOR LIGHTING	1	40	20	1	7		20	1	7		
ROOF RECEPTACLE (GFI)	1	180	20	1	9		20	1	9		
DED - SOLAR READY					11	40	20	1	11	FIRE ALARM CONTROL PANEL (FIRE ALARM NOTE #2)	
DED - SOLAR READY					13		20	1	13		
A = 6402 WATTS / PHASE		1860	940			4542	4582	B = 5522 WATTS / PHASE			
TOTAL = 11,924 WATTS		57	AMPS	120/208	VOLTS	1 φ		3 WIRE			




RAMP AND LANDING ELEVATION SCALE: 1/2" = 1'-0" 4




SECTION AT RAMP AND LANDING SCALE: 1/2" = 1'-0" 5




SECTION AT LANDING SCALE: 1/2" = 1'-0" 9




LANDING ELEVATION SCALE: 1/2" = 1'-0" 6




RAMP TRANSITION SCALE: NTS 10




RETURN EXTEND HANDRAIL ELEVATION SCALE: 1" = 1'-0" 7



LANDING PLAN SCALE: 1/4" = 1'-0" 1



LANDING FRAME SCALE: 1/4" = 1'-0" 2



SILL PLAN FOR RAMP AND LANDING SCALE: 1/4" = 1'-0" 3

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL
THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM INC) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM INC. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM INC SHALL BE THE PROPERTY OF SCM INC.

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
RAMP LANDING

REVISIONS

1	
2	
3	
4	
5	

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL










Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER

R-1.03



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024

PROJECT SPECIFIC STATE AGENCY APPROVAL
THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc. ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
**SWITCHBACK RAMP
PLAN**

REVISIONS

PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION
FOR CONSTRUCTION IS REQUIRED





IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL
Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211

MODULAR BUILDING DESIGN PROFESSIONAL

REGISTERED PROFESSIONAL ENGINEER
JOHN W. STAMPA
STRUCTURAL
STATE OF CALIFORNIA

SILVER CREEK INDUSTRIES
24' x 40' PC
PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER
R-1.05



IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 02-122160 INC:
REVIEWED FOR
SS FLS ACS
DATE: 2/27/2024





PROJECT SPECIFIC STATE AGENCY APPROVAL

THESE DRAWINGS AND ALL MATERIAL CONTAINED HEREIN ARE THE PROPERTY OF SILVER CREEK MODULAR, INC (SCM Inc) AND SHALL NOT BE REPRODUCED, COPIED OR OTHERWISE DISPOSED OF DIRECTLY OR INDIRECTLY AND SHALL NOT BE USED IN WHOLE OR IN PART TO ASSIST IN THE MAKING OF OR FOR THE PURPOSE OF FURNISHING ANY INFORMATION FOR THE MAKING OF DRAWINGS, PRINTS, APPARATUS OR PARTS THEREOF WITHOUT THE FULL KNOWLEDGE AND WRITTEN CONSENT OF SCM Inc.
ALL PATENTABLE MATERIAL CONTAINED HEREIN AND ORIGINATING WITH SCM Inc SHALL BE THE PROPERTY OF SCM Inc.

PROJECT NAME:
**SYLVAN USD
FREEDOM E.S.
(2) 24' x 40'
CLASSROOM BUILDINGS**

SHEET TITLE:
RAMP DETAILS





REVISIONS



PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023





PC STATE AGENCY APPROVAL



PRE-CHECK (PC) DOCUMENT
CODE: 2022 CBC
A SEPARATE PROJECT APPLICATION FOR CONSTRUCTION IS REQUIRED





IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
APP: 04-121999 INC:
REVIEWED FOR
SS FLS ACS
DATE: 08/31/2023

PC STATE AGENCY APPROVAL



Silver Creek
2830 BARRETT AVE PERRIS, CALIFORNIA 92571
PHONE: 951-943-5393 FAX: 951-943-2211


MODULAR BUILDING DESIGN PROFESSIONAL



REGISTERED PROFESSIONAL ENGINEER
JOHN W. STARBUCK
STRUCTURAL
STATE OF CALIFORNIA

SILVER CREEK INDUSTRIES
24' x 40' PC

PROJECT NO:
DRAWN BY:
SCALE: AS NOTED
DATE: 02-27-2023
P.C. SHEET NUMBER



R-2.01